

SIMATIC DP, INTERFACE MODULE IM151-3 PN HF FOR ET 200S, TRANSMISS. RATE UP TO 100MBIT/S MAX. OF 63 PERIPHERAL MODULES UP TO 2M WIDTH CONNECTABLE; 2 X BUS INTERFACING VIA RJ45 INCL. TERMINATING MODULE



Figure similar

<b>Configuration control</b>	
via dataset	Yes
<b>Supply voltage</b>	
<b>Mains buffering</b>	
• Mains/voltage failure stored energy time	20 ms
<b>Input current</b>	
from supply voltage 1L+, max.	200 mA
<b>Power loss</b>	
Power loss, typ.	3.3 W
<b>Address area</b>	
<b>Addressing volume</b>	
• Inputs	256 byte
• Outputs	256 byte
<b>Interfaces</b>	
Number of PROFINET interfaces	1

PROFINET IO	
• Autocrossing	Yes
• automatic detection of transmission rate	Yes
• Transmission rate, max.	100 Mbit/s
• Services	Ping; arp; LLDP; network diagnostics (SNMP) / MIB-2, reset SNMP parameters to factory settings; prioritized startup; media redundancy MRP; shared device
• RJ 45	Yes

## 1. Interface

### Functionality

• PROFINET IO Device	Yes
----------------------	-----

### PROFINET IO Device

#### Services

— Isochronous mode	No
— IRT	Yes
— PROFINergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

### Protocols

Supports protocol for PROFINET IO	Yes
-----------------------------------	-----

MRP	Yes
-----	-----

### Protocols (Ethernet)

• SNMP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes

### Interrupts/diagnostics/status information

Alarms	Yes
--------	-----

Diagnostic functions	Yes
----------------------	-----

### Diagnostics indication LED

• Bus fault BF (red)	Yes
• Group error SF (red)	Yes
• Monitoring 24 V voltage supply ON (green)	Yes
• Connection to network LINK (green)	Yes

### Potential separation

between backplane bus and electronics	No
---------------------------------------	----

between supply voltage and electronics	No
--	----

between Ethernet and electronics	Yes
----------------------------------	-----

### Permissible potential difference

between different circuits	75 V DC/60 V AC
----------------------------	-----------------

### Isolation

Isolation tested with	500 V
-----------------------	-------

### Standards, approvals, certificates

CE mark	Yes
---------	-----

UL approval	Yes
-------------	-----

### Ambient conditions

Ambient temperature during operation	
--------------------------------------	--

• min.	0 °C
--------	------

• max.	60 °C
--------	-------

### Dimensions

Width	60 mm
-------	-------

Height	119.5 mm
--------	----------

Depth	75 mm; with mounting rail
-------	---------------------------

### Weights

Weight, approx.	150 g
-----------------	-------

<b>last modified:</b>	07/13/2016
-----------------------	------------