



### Single Darlington Transistor Module 100 Amperes/600 Volts



#### Description:

The Powerex Single Darlington Transistor Modules are high power devices designed for use in switching applications. The modules are isolated, consisting of one Darlington Transistor with a reverse parallel connected high-speed diode and base-to-emitter speed-up diode.

#### Features:

- Isolated Mounting
- Planar Chips
- Discrete Fast Recovery Feedback Diode
- High Gain ( $h_{FE}$ )
- TAB Quick-Connect Terminals
- Base-Emitter Speed-up Diode

#### Applications:

- Inverters
- DC Motor Control
- Switching Power Supplies
- AC Motor Control

#### Ordering Information:

Example: Select the complete eight digit module part number you desire from the table - i.e. KS224510 is a 450  $V_{CE0(sus)}$  (600  $V_{CEV}$ ), 100 Ampere Single Darlington Module.

Outline Drawing

Dimensions	Inches	Millimeters
A	3.701 Max.	94 Max.
B	3.150 ± 0.010	80 ± 0.25
C	1.339 Max.	34 Max.
D	1.181 Max.	30 Max.
E	1.063	27
F	0.906	23
G	0.787	20
H	0.512	13

Dimensions	Inches	Millimeters
J	0.472	12
K	0.413	10.5
L	0.344	8.75
M	0.315	8
N	0.256 Dia.	6.5 Dia.
P	0.256 Min.	6.5 Min.
Q	0.157	4
R	M5 Metric	M5

Type	$V_{CE0(sus)}$ Volts (X 10)	Current Rating Amperes (X 10)
KS22	45	10



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

KS224510  
Single Darlington Transistor Module  
100 Amperes/600 Volts

**Absolute Maximum Ratings,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Ratings	Symbol	KS224510	Units
Junction Temperature	$T_j$	-40 to 150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-40 to 125	$^\circ\text{C}$
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	450	Volts
Collector-Emitter Sustaining Voltage, $V_{BE} = -2V$	$V_{CEV(sus)}$	600	Volts
Collector-Base Voltage	$V_{CBO}$	600	Volts
Emitter-Base Voltage	$V_{EBO}$	7	Volts
Collector-Emitter Voltage	$V_{CEV}$	600	Volts
Continuous Collector Current	$I_C$	100	Amperes
Diode Forward Current	$I_{FM}$	100	Amperes
Continuous Base Current	$I_B$	6	Amperes
Diode Surge Current	$I_{FSM}$	1000	Amperes
Power Dissipation	$P_t$	620	Watts
Max. Mounting Torque M5 Terminal Screws	-	17	in.-lb.
Max. Mounting Torque M6 Mounting Screws	-	17	in.-lb.
Module Weight (Typical)	-	250	Grams
V Isolation	$V_{RMS}$	2000	Volts

**Electrical Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units	
Collector Cutoff Current	$I_{CEV}$	$V_{CE} = 600V, V_{BE} = -2V$	-	-	2	mA	
		$V_{CE} = 600V, V_{BE} = -2V, T_C = 125^\circ\text{C}$	-	-	15	mA	
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = 7V$	-	-	400	mA	
DC Current Gain	$h_{FE}$	$I_C = 100A, V_{CE} = 2V$	75	-	-	-	
		$I_C = 100A, V_{CE} = 5V$	100	-	-	-	
Diode Forward Voltage	$V_{FM}$	$I_{FM} = 100A$	-	-	1.75	Volts	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 100A, I_B = 1.3A$	-	-	2.0	Volts	
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 100A, I_B = 1.3A$	-	-	2.5	Volts	
Resistive	Turn-on	$t_{on}$	$V_{CC} = 300V$	-	-	2.0	$\mu\text{s}$
Load	Storage Time	$t_s$	$I_C = 100A$	-	-	12	$\mu\text{s}$
Switch Times	Fall Time	$t_f$	$I_{B1} = 2A, I_{B2} = -2A$	-	-	3.0	$\mu\text{s}$










**Thermal and Mechanical Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Case-to-Sink	$R_{\theta(c-s)}$	-	-	-	0.15	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case	$R_{\theta(j-c)}$	Transistor Part	-	-	0.2	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case	$R_{\theta(j-c)}$	Diode Part	-	-	0.65	$^\circ\text{C/W}$



Powerex, Inc., 200 Hills Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

**KS224510**  
**Single Darlington Transistor Module**  
 100 Amperes/600 Volts



Powerex, Inc., 200 Hills Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

**KS224510**  
**Single Darlington Transistor Module**  
**100 Amperes/600 Volts**

