

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | VEM4 |
| Product ID: | 1SBN030111R1000 |
| EAN: | 3471523130616 |
| Catalog Description: | VEM4 Mechanical and Electrical Interlock Unit |
| Long Description: | VEM4 Mechanical and Electrical Interlock Unit |

Additional Information

| | |
|--|---|
| ABB Industrial IT Suite: | Control IT |
| CB Certificate: | CB_SE_70922A2 |
| CCC Certificate: | CCC_2013010304651497 |
| Connecting Capacity Auxiliary Circuit: | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1...2.5 mm ² |
| Conventional Free-air Thermal Current (I_{th}): | acc. to IEC 60947-5-1, q = 40 °C 16 A |
| Country of Origin: | Poland (PL) |
| Customs Tariff Number: | 85389099 |
| Data Sheet, Technical Information: | 1SBC100173C0201 |
| Declaration of Conformity - CE: | 1SBD250007U1000 |
| E-nummer: | 3210004 |
| EAN: | 3471523130616 |
| ETIM 4: | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5: | EC002498 - Accessories for low-voltage switch technology |
| ETIM 6: | EC002498 - Accessories for low-voltage switch technology |
| Environmental Information: | 1SBD250142E1000 |
| GOST Certificate: | GOST_POCCFR.ME77.B07175.pdf |
| IIT Publishing Status: | Level 0 - Information enabled |
| Industrial IT Certification Level: | 0 |
| Instructions and Manuals: | 1SBC101028M6801 |
| Invoice Description: | VEM4 Mechanical and Electrical Interlock Unit |
| Maximum Electrical Switching Frequency: | 1200 _B7HUR cycles per hour |
| Maximum Mechanical Switching Frequency: | 1800 cycles per hour |
| Minimum Order Quantity: | 1 piece |
| Number of Auxiliary Contacts NC: | 1 |
| Number of Auxiliary Contacts NO: | 1 |
| Order Multiple: | 1 piece |
| Package Level 1 EAN: | 3471523130616 |
| Package Level 1 Gross Weight: | 0.035 kg |
| Package Level 1 Height: | 46 mm |
| Package Level 1 Length: | 35 mm |
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 92 mm |
| Package Level 2 Units: | 132 piece |
| Package Level 3 Units: | 3168 piece |

| | |
|--|--|
| Product Main Type: | Accessories for Block Contactors |
| Product Name: | Mechanical and Electrical Interlock Unit |
| Product Net Weight: | 0.035 kg |
| Product Packing Type: | Box |
| RINA Certificate: | RINA_ELE084013XG |
| Rated Impulse Withstand Voltage (U_{imp}): | 6 kV |
| Rated Insulation Voltage (U_i): | acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V |
| RoHS Date: | 20090609 |
| RoHS Information: | 1SBD251010E1000 |
| Selling Unit of Measure: | piece |
| Short Description: | VEM4 Mechanical and Electrical Interlock Unit |
| Suitable For: | AF09 AF12 AF16 AF26 AF30 AF38 |
| Terminal Type: | Screw Terminals |
| Tightening Torque: | Auxiliary Circuit 1.2 N·m |
| Tightening Torque UL/CSA: | Auxiliary Circuit 11 in·lb |
| UL Certificate: | UL_20091124-E312527-6-1 |
| UL Listing Card: | UL_E312527 |
| UNSPSC: | 39120000 |
| Wire Stripping Length: | Auxiliary Circuit 10 mm |