

SIMATIC HMI TP1200 COMFORT, COMFORT PANEL, TOUCH OPERATION, 12" WIDESCREEN-TFT-DISPLAY, 16 MIL. COLORS, PROFINET INTERFACE, MPI/PROFIBUS DP INTERFACE, 12 MB USER MEMORY, WINDOWS CE 6.0, CONFIGURABLE FROM WINCC COMFORT V11

General information

| | |
|--------------------------|----------------------------|
| Product type designation | SIMATIC HMI TP1200 Comfort |
|--------------------------|----------------------------|

Display

| | |
|-------------------|------------|
| Design of display | TFT |
| Screen diagonal | 12.1 in |
| Display width | 261.1 mm |
| Display height | 163.2 mm |
| Number of colors | 16 777 216 |

Resolution (pixels)

- | | |
|-------------------------------|-------------|
| • Horizontal image resolution | 1 280 Pixel |
| • Vertical image resolution | 800 Pixel |

Backlighting

- | | |
|--------------------------------|--------------|
| • MTBF backlighting (at 25 °C) | 80 000 h |
| • Backlight dimmable | Yes; 0-100 % |

Control elements

Keyboard fonts

- | | |
|------------------------------|------------------------|
| • Function keys | |
| — Number of function keys | 0 |
| • Keys with LED | No |
| • System keys | No |
| • Numeric/alphabetical input | |
| — Numeric keyboard | Yes; Onscreen keyboard |
| — alphanumeric keyboard | Yes; Onscreen keyboard |

Touch operation

- | | |
|--------------------------|-----|
| • Design as touch screen | Yes |
|--------------------------|-----|

Expansions for operator control of the process

- | | |
|---|----|
| • DP direct LEDs (LEDs as S7 output I/O) | |
| — F1...Fx | 0 |
| • Direct keys (keys as S7 input I/O) | |
| — F1...Fx | 0 |
| • Direct keys (touch buttons as S7 input I/O) | 40 |

Installation type/mounting

| | |
|---|----------|
| Mounting position | vertical |
| Mounting in portrait format possible | Yes |
| Mounting in landscape format possible | Yes |
| maximum permissible angle of inclination without external ventilation | 35° |

Supply voltage

| | |
|-------------------------------------|--------|
| Type of supply voltage | DC |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |

Input current

| | |
|--|-----------------------|
| Current consumption (rated value) | 0.85 A |
| Starting current inrush I ² t | 0.5 A ² ·s |

Power

| | |
|--------------------------|------|
| Active power input, typ. | 20 W |
|--------------------------|------|

Processor

| | |
|----------------|-----|
| Processor type | X86 |
|----------------|-----|

Memory

| | |
|--------------------------------|----------|
| Flash | Yes |
| RAM | Yes |
| Memory available for user data | 12 Mbyte |

Type of output

| | |
|-----------|-----|
| Info LED | No |
| Power LED | No |
| Error LED | No |
| Acoustics | |
| • Buzzer | No |
| • Speaker | Yes |

Time of day

| | |
|------------------------------|---|
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Software clock | Yes |
| • retentive | Yes; Back-up duration typically 6 weeks |
| • synchronizable | Yes |

Interfaces

| | |
|--|------------------------|
| Number of industrial Ethernet interfaces | 1; 2 ports (switch) |
| Number of RS 485 interfaces | 1; RS 422/485 combined |
| Number of RS 422 interfaces | 0; together with RS485 |
| Number of RS 232 interfaces | 0 |
| Number of USB interfaces | 2; USB 2.0 |

| | |
|---|----------------------|
| • USB Mini B | 1; 5-pole |
| Number of 20 mA interfaces (TTY) | 0 |
| Number of parallel interfaces | 0 |
| Number of other interfaces | 0 |
| Number of SD card slots | 2 |
| With software interfaces | No |
| Industrial Ethernet | |
| • Industrial Ethernet status LED | 2 |
| • Number of ports of the integrated switch | 2 |
| Protocols | |
| PROFINET | Yes |
| Supports protocol for PROFINET IO | Yes |
| IRT | Yes; As of WinCC V12 |
| MRP | Yes; As of WinCC V12 |
| PROFIBUS | Yes |
| MPI | Yes |
| Protocols (Ethernet) | |
| • TCP/IP | Yes |
| • DHCP | Yes |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| WEB characteristics | |
| • HTTP | Yes |
| • HTTPS | Yes |
| • HTML | Yes |
| • XML | Yes |
| • CSS | Yes |
| • Active X | Yes |
| • JavaScript | Yes |
| • Java VM | No |
| Further protocols | |
| • CAN | No |
| • EtherNet/IP | Yes |
| • MODBUS | Yes |
| EMC | |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes |
| • Limit class B, for use in residential areas | No |
| Degree and class of protection | |
| IP (at the front) | IP65 |

| | |
|--------------------------------|------|
| Enclosure Type 4 at the front | Yes |
| Enclosure Type 4x at the front | Yes |
| IP (rear) | IP20 |

Standards, approvals, certificates

| | |
|-----------------------|-----|
| CE mark | Yes |
| cULus | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |

Marine approval

| | |
|---|--------------------------------|
| <ul style="list-style-type: none"> • Germanischer Lloyd (GL) | Yes; As of product version: 10 |
| <ul style="list-style-type: none"> • American Bureau of Shipping (ABS) | Yes; As of product version: 10 |
| <ul style="list-style-type: none"> • Bureau Veritas (BV) | Yes; As of product version: 10 |
| <ul style="list-style-type: none"> • Det Norske Veritas (DNV) | Yes; As of product version: 10 |
| <ul style="list-style-type: none"> • Lloyds Register of Shipping (LRS) | Yes; As of product version: 10 |
| <ul style="list-style-type: none"> • Nippon Kaiji Kyokai (Class NK) | Yes; As of product version: 10 |
| <ul style="list-style-type: none"> • Polski Rejestr Statkow (PRS) | No |

Use in hazardous areas

| | |
|--|-----|
| <ul style="list-style-type: none"> • ATEX Zone 2 | Yes |
| <ul style="list-style-type: none"> • ATEX Zone 22 | Yes |
| <ul style="list-style-type: none"> • IECEx Zone 2 | Yes |
| <ul style="list-style-type: none"> • IECEx Zone 22 | Yes |
| <ul style="list-style-type: none"> • cULus Class I Zone 1 | No |
| <ul style="list-style-type: none"> • cULus Class I Zone 2, Division 2 | Yes |
| <ul style="list-style-type: none"> • FM Class I Division 2 | Yes |

Ambient conditions

Ambient temperature during operation

| | |
|--|---|
| <ul style="list-style-type: none"> • Operation (vertical installation) <ul style="list-style-type: none"> — For vertical installation, min. — For vertical installation, max. | 0 °C 50 °C; (55 °C, see entry ID:64847814) |
| <ul style="list-style-type: none"> • Operation (max. tilt angle) <ul style="list-style-type: none"> — At maximum tilt angle, min. — At maximum tilt angle, min. | 0 °C 40 °C |
| <ul style="list-style-type: none"> • Operation (vertical installation, portrait format) <ul style="list-style-type: none"> — For vertical installation, min. — For vertical installation, max. | 0 °C 40 °C |
| <ul style="list-style-type: none"> • Operation (max. tilt angle, portrait format) <ul style="list-style-type: none"> — At maximum tilt angle, min. — At maximum tilt angle, min. | 0 °C 35 °C |

Ambient temperature during storage/transportation

| | |
|--|--------|
| <ul style="list-style-type: none"> • min. | -20 °C |
| <ul style="list-style-type: none"> • max. | 60 °C |

| Relative humidity | |
|--|-----------------------|
| • Operation, max. | 90 %; no condensation |
| Operating systems | |
| proprietary | No |
| pre-installed operating system | |
| • Windows CE | Yes |
| Configuration | |
| Message indicator | Yes |
| Alarm system (incl. buffer and acknowledgment) | Yes |
| Process value display (output) | Yes |
| Process value default (input) possible | Yes |
| Recipe management | Yes |
| Configuration software | |
| • STEP 7 Basic (TIA Portal) | No |
| • STEP 7 Professional (TIA Portal) | No |
| • WinCC flexible Compact | No |
| • WinCC flexible Standard | No |
| • WinCC flexible Advanced | No |
| • WinCC Basic (TIA Portal) | No |
| • WinCC Comfort (TIA Portal) | Yes; from V11 |
| • WinCC Advanced (TIA Portal) | Yes; from V11 |
| • WinCC Professional (TIA Portal) | Yes; from V11 |
| Languages | |
| Online languages | |
| • Number of online/runtime languages | 32 |
| Project languages | |
| • Languages per project | 32 |
| Functionality under WinCC (TIA Portal) | |
| Libraries | Yes |
| Applications/options | |
| • Web browser | Yes |
| • Pocket Word | Yes |
| • Pocket Excel | Yes |
| • PDF Viewer | Yes |
| • Media Player | Yes |
| • SIMATIC WinCC Sm@rtServer | Yes |
| • SIMATIC WinCC Audit | Yes |
| Number of Visual Basic Scripts | Yes |
| Task planner | |
| • time-controlled | Yes |

| | |
|--|---------|
| • task-controlled | Yes |
| Help system | |
| • Number of characters per info text | 70 |
| Message system | |
| • Number of alarm classes | 32 |
| • Bit messages | |
| — Number of bit messages | 4 000 |
| • Analog messages | |
| — Number of analog messages | 200 |
| • S7 alarm number procedure | Yes |
| • System messages HMI | Yes |
| • System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.) | Yes |
| • Number of characters per message | 80 |
| • Number of process values per message | 8 |
| • Acknowledgment groups | Yes |
| • Message indicator | Yes |
| • Message buffer | |
| — Number of entries | 1 024 |
| — Circulating buffer | Yes |
| — retentive | Yes |
| — maintenance-free | Yes |
| Recipe management | |
| • Number of recipes | 300 |
| • Data records per recipe | 500 |
| • Entries per data record | 1 000 |
| • Size of internal recipe memory | 2 Mbyte |
| • Recipe memory expandable | Yes |
| Variables | |
| • Number of variables per device | 2 048 |
| • Number of variables per screen | 400 |
| • Limit values | Yes |
| • Multiplexing | Yes |
| • Structures | Yes |
| • Arrays | Yes |
| Images | |
| • Number of configurable images | 500 |
| • Permanent window/default | Yes |
| • Global image | Yes |
| • Pop-up images | Yes |
| • Slide-in images | Yes |

| | |
|--|--------|
| • Image selection by PLC | Yes |
| • Image number in the PLC | Yes |
| Image objects | |
| • Number of objects per image | 400 |
| • Text fields | Yes |
| • I/O fields | Yes |
| • Graphic I/O fields (graphics list) | Yes |
| • Symbolic I/O fields (text list) | Yes |
| • Date/time fields | Yes |
| • Switches | Yes |
| • Buttons | Yes |
| • Graphic display | Yes |
| • Icons | Yes |
| • Geometric objects | Yes |
| Complex image objects | |
| • Number of complex objects per screen | 20 |
| • Alarm view | Yes |
| • Trend view | Yes |
| • User view | Yes |
| • Status/control | Yes |
| • Sm@rtClient view | Yes |
| • Recipe view | Yes |
| • f(x) trend view | Yes |
| • System diagnostics view | Yes |
| • Media Player | Yes |
| • HTML browser | Yes |
| • PDF display | Yes |
| • IP camera display | Yes |
| • Bar graphs | Yes |
| • Sliders | Yes |
| • Pointer instruments | Yes |
| • Analog/digital clock | Yes |
| Lists | |
| • Number of text lists per project | 500 |
| • Number of entries per text list | 500 |
| • Number of graphics lists per project | 500 |
| • Number of entries per graphics list | 500 |
| Archiving | |
| • Number of archives per device | 50 |
| • Number of entries per archive | 20 000 |
| • Message archive | Yes |

| | |
|-----------------------------------|------------------------------------|
| • Process value archive | Yes |
| • Archiving methods | |
| — Sequential archive | Yes |
| — Short-term archive | Yes |
| • Memory location | |
| — Memory card | Yes |
| — USB memory | Yes |
| — Ethernet | Yes |
| • Data storage format | |
| — CSV | Yes |
| — TXT | Yes |
| — RDB | Yes |
| Security | |
| • Number of user groups | 50 |
| • Number of user rights | 32 |
| • Number of users | 50 |
| • Password export/import | Yes |
| • SIMATIC Logon | Yes |
| Logging through printer | |
| • Alarms | Yes |
| • Report (shift log) | Yes |
| • Hardcopy | Yes |
| • Electronic print to file | Yes; pdf, html |
| Character sets | |
| • Keyboard fonts | |
| — US English | Yes |
| Transfer (upload/download) | |
| • MPI/PROFIBUS DP | Yes |
| • USB | Yes |
| • Ethernet | Yes |
| • using external storage medium | Yes |
| Process coupling | |
| • S7-1200 | Yes |
| • S7-1500 | Yes |
| • S7-200 | Yes |
| • S7-300/400 | Yes |
| • LOGO! | Yes |
| • WinAC | Yes |
| • SINUMERIK | Yes; with SINUMERIK option package |
| • SIMOTION | Yes |
| • Allen Bradley (EtherNet/IP) | Yes |

- Allen Bradley (DF1) Yes
- Mitsubishi (MC TCP/IP) Yes
- Mitsubishi (FX) Yes
- OMRON (FINS TCP) No
- OMRON (LINK/Multilink) Yes
- Modicon (Modbus TCP/IP) Yes
- Modicon (Modbus) Yes
- OPC UA Client Yes
- OPC UA Server Yes

Service tools/configuration aids

- Backup/Restore manually Yes
- Backup/Restore automatically Yes
- Simulation Yes
- Device switchover Yes

Peripherals/Options

Peripherals

- Printer Yes
- SIMATIC HMI MM memory card: Multi Media Card Yes; Up to 128 MB
- SIMATIC HMI SD memory card: Secure Digital memory card Yes; Up to 2 GB
- SIMATIC HMI CF memory card Compact Flash Card No
- USB memory Yes
- SIMATIC IPC USB Flashdrive (USB stick) Yes; Up to 16 GB
- SIMATIC HMI USB stick Yes; Up to 8 GB
- Network camera Yes

Mechanics/material

Enclosure material (front)

- Plastic No
- Aluminum Yes
- Stainless steel No

Dimensions

| | |
|----------------------------|--------|
| Width of the housing front | 330 mm |
| Height of housing front | 241 mm |
| Mounting cutout, width | 310 mm |
| Mounting cutout, height | 221 mm |
| Overall depth | 65 mm |

Weights

| | |
|--------------------------|--------|
| Weight without packaging | 2.8 kg |
| Weight incl. packaging | 3.5 kg |

last modified:

04/24/2017