



SIMATIC DP,
RS485 REPEATER FOR THE CONNECTION OF
PROFIBUS/MPI BUS SYSTEMS WITH MAX. 31 NODES;
MAX. 12 MBIT/S,
DEGREE OF PRO-TECTION IP20

Supply voltage

24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption, max.	200 mA ; (200 mA without loads at PG/OP socket; 230 mA load at PG/OP socket (5 V/90 mA); 300 mA load at PG/OP socket (24 V/90 mA))
----------------------------------	--

Interfaces

Bus cables	2 terminal blocks
-------------------	-------------------

PROFIBUS DP

Transmission rate, max.	12 Mbit/s ; 9.6 kbit/s to 12 Mbit/s
--------------------------------	-------------------------------------

Degree and class of protection

IP20	Yes
-------------	-----

Ambient conditions

Operating temperature	
Min.	0 °C
max.	60 °C

Storage/transport temperature	
--------------------------------------	--

Min.	-40 °C
max.	70 °C
Relative humidity	
Operation, max.	95 % ; at 25 °C
Connection method	
Power supply	Terminal block
Dimensions	
Width	45 mm
Height	128 mm
Depth	67 mm
Weight	
Weight, approx.	350 g
Status	May 20, 2013