

J-type Thermocouple

- washer, ungrounded

Model BB-WTJ-10-36-TT

ADVANTECH

www.advantech.com



KEY FEATURES

- + J-type ungrounded thermocouple
- + #10 or M4.5 screw mounting
- + 20 AWG solid wire with PFA insulation
- + Stripped end, lead-wire termination connection
- + 91.4 cm (36 in) length


OVERVIEW

BB-WTJ-10-36-TT is a versatile thermocouple assembly that easily mounts to a variety of surfaces. It is suitable for surface temperature measurement applications where fixed mounting is possible.

ORDERING INFORMATION

MODEL NO.	DESCRIPTION
BB-WTJ-10-36-TT	J-type Thermocouple (ungrounded)

MECHANICAL DRAWING



SPECIFICATIONS

Thermocouple Type	Wire	Length	Screw, Nominal Size	Insulation	Temperature Rating	Washer Hole Diameter
J	20 AWG	900 mm (36 in)	#10 (America) M4.5 (metric)	PFA	260 °C (500 °F)	4.95 mm (0.195 in)

MOUNTING DIAGRAM

– Easily mounts to a variety of surfaces.



All product specifications are subject to change without notice.
BB-WTJ-10-36-TT_3319ds

ADVANTECH

Advantech B+B SmartWorx, 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 1 (800)346-3119/Toll Free | orders@advantech-bb.com | support@advantech-bb.com