


Time-Lag Brick SMD Fuse 2611

multicomp PRO

**RoHS
Compliant**



Description

The brick fuse for the small size and good electrical performance, reliability and quality. The solder-free design provides excellent on-off and temperature cycling characteristics during use and also makes our brick fuses more heat and shock tolerant than typical brick fuses.

Applications

Time-lag type brick fuse for over-current protection.

Features

- Rapid interruption of excessive current
- Compatible with reflow and wave soldering
- Ceramic body and silver plated copper terminal
- Excellent environmental integrity
- Lead-free and Halogen-free
- Designed to UL 248-14

Specifications

Operating Temperature	: -55°C to +125°C
Storage Conditions	: +10°C to +60°C
Relative Humidity	: ≤ 75% yearly average without dew, maximum 30 days at 95%
Vibration Resistance	: 24 cycles at 15 min. each 10-60Hz at 0.75mm amplitude 60-2000Hz at 10g acceleration


Electrical Characteristics

Part Number	Rated Current	Max. Voltage	Typical Voltage Drop (mV)	Breaking Capacity	Typical Melting I ² t (A ² sec)	Typical Cold Resistance (Ω)
MP001614	1A	250V AC 125V AC	300	100A@250V AC 100A@125V AC 50A@125V DC	0.87	0.256

Note:

- (1) Permissible continuous operating current is ≤100% at ambient temperature of 23°C (73.4°F)
- (2) The current values used for calculating I²T should be within the standard 10In.

Temperature Derating Curve



$$\text{Calculation for ideal fuse selection} = \frac{\text{Operating Current (A)}}{\text{Rating (\%} \times 0.75)}$$


Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

Time-Lag Brick SMD Fuse 2611


Time vs Current Characteristics Table

Average Time Current (I-T) Curves



Time vs Current Characteristics: UL-248-14		
Rated Current	100%	200%
1A	>4h	<120s

Soldering Parameters




Profile Feature		Pb-Free Assembly
Average Ramp-UP Rate(Tsmax to Tp)		3°C/s Max.
Preheat	Temperature Min (Ts min)	150°C
	Temperature Max (Ts max)	200°C
	Time (Tsmin to Ts max)	60sec to 120sec
Peak Temperature (TP)		260°C
Time within 5°C of actual Peak Temperature(TP)		5sec
Melting tin time (TL)		20sec to 40sec
Ramp-Down Rate		6°C/s Max.
Time 25°C to Peak Temperature(TP)		8 minutes Max.


- Infrared Reflow:**
 Temperature: 260°C
 Time: 5sec Max.
- Wave Soldering:**
 Reservoir Temperature: 260°C
 Time in Reservoir: 10sec Max.
- Hand Soldering**
 Temperature: 300°C
 Time: 3 sec. Max.
 Soldering iron avoid touch Brass Cap.

Time-Lag Brick SMD Fuse 2611


Mechanical Specifications



Diagram



Packing Information



Dimensions : Millimetres

Part Number Table

Description	Part Number
Brick SMD Fuse, Time-Lag, 1A, 250V AC, 2611	MP001614

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.