



SWITCH OPERATION
Horizontal or Vertical Mounting

Drawings not to scale
All dimensions in mm

SPECIFICATION

| | | |
|-----------------------|------------|--------------------------|
| SWITCHING VOLTAGE | Max. Vac | 60 |
| SWITCHING CURRENT | Max. A | 0.25 |
| SWITCHING CAPACITY | Max. VA | 3 |
| CONTACT RESISTANCE | Max. mΩ | 1000 |
| DIFFERENTIAL ANGLE | Max. Deg.° | 16 |
| OPERATING TEMPERATURE | Deg. °C | -20° +70° |
| STORAGE TEMPERATURE | Deg. °C | -25° +70° |
| CASE MATERIAL | | Blue Polystyrene |
| FEATURES | | Non-toxic moving contact |

TILT SWITCH ASSEMBLIES

PART NUMBER
TSW 30/60

| Rev. No. | Revision Note | Date | Signature |
|----------|------------------------|--------|-----------|
| C | 1998 Catalogue Page 20 | 1-4-98 | RG |



As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.