POWERSEM

Three Phase Rectifier Bridges

PSD 192

I_{dAV} = 248 A

V_{RRM} = 800-1800 V

Preliminary Data Sheet

V_{RSM} V	V_{RRM} V	Type
800	800	PSD 192/08
1200	1200	PSD 192/12
1400	1400	PSD 192/14
1600	1600	PSD 192/16
1800	1800	PSD 192/18



Symbol	Test Conditions			Maximum Ratings	
I_{dAV}	T_C = 90°C, module			248	A
I_{FSM}	T_{VJ} = 45°C	t = 10 ms	(50 Hz), sine	2800	A
	V_R = 0	t = 8.3 ms	(60 Hz), sine	3300	A
	T_{VJ} = T_{VJM}	t = 10 ms	(50 Hz), sine	2500	A
	V_R = 0	t = 8.3 ms	(60 Hz), sine	2750	A
$\int i^2 dt$	T_{VJ} = 45°C	t = 10 ms	(50 Hz), sine	39200	$A^2 s$
	V_R = 0	t = 8.3 ms	(60 Hz), sine	45000	$A^2 s$
	T_{VJ} = T_{VJM}	t = 10 ms	(50 Hz), sine	31200	$A^2 s$
	V_R = 0	t = 8.3 ms	(60 Hz), sine	31200	$A^2 s$
T_{VJ}				-40 ... + 150	°C
T_{VJM}				150	°C
T_{stg}				-40 ... + 125	°C
V_{ISOL}	50/60 HZ, RMS	t = 1 min		2500	V ~
	I_{ISOL} ≤ 1 mA	t = 1 s		3000	V ~
M_d	Mounting torque		(M6)	5	Nm
	Terminal connection torque		(M6)	5	Nm
Weight	typ.			270	g

Symbol	Test Conditions			Characteristic Value	
I_R	V_R = V_{RRM}	T_{VJ} = 25°C	≤	0.3	mA
	V_R = V_{RRM}	T_{VJ} = T_{VJM}	≤	5	mA
V_F	I_F = 300 A	T_{VJ} = 25°C	≤	1.43	V
V_{TO}	For power-loss calculations only			0.8	V
r_T	T_{VJ} = T_{VJM}			2.2	mΩ
R_{thJC}	per diode; DC current			0.45	K/W
	per module			0.075	K/W
R_{thJK}	per diode; DC current			0.6	K/W
	per module			0.1	K/W
d_S	Creeping distance on surface			10	mm
d_A	Creeping distance in air			9.4	mm
a	Max. allowable acceleration			50	m/s^2

Features

- Package with screw terminals
- Isolation voltage 3000 V~
- Planar glasspassivated chips
- Blocking voltage up to 1800 V
- Low forward voltage drop
- UL registered E 148688

Applications

- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling capability

Package, style and outline

Dimensions in mm (1mm = 0.0394“)



POWERSEM GmbH, Walpersdorfer Str. 53
91126 D- Schwabach
Phone: 09122 - 9764-0 Fax.: 09122 - 9764-20

© 2003 POWERSEM reserves the right to change limits, test conditions and dimensions



Fig. 1 Forward current versus voltage drop per diode



Fig. 2 Surge overload current per diode I_{FSM}: Crest value. t: duration



Fig. 3 $\int i^2dt$ versus time (1-10ms) per diode (or thyristor)



Fig. 4 Power dissipation versus direct output current and ambient temperature



Fig.5 Maximum forward current at case temperature



Fig. 6 Transient thermal impedance per diode (or thyristor), calculated

POWERSEM GmbH, Walpersdorfer Str. 53
91126 D- Schwabach
Phone: 09122 - 9764-0 Fax.: 09122 - 9764-20

© 2003 POWERSEM reserves the right to change limits, test conditions and dimensions