

Enhanced 50 Series Sensors



NanoView Series Sensors



SM Series Sensors



5.0 Introduction

Quick Reference Guide	V8-T5-2
Technical Reference	V8-T5-4
Product Selection Guide	V8-T5-6

5.1 Enhanced 50 Series Sensors

Product Description	V8-T5-9
Product Selection	V8-T5-10

5.2 NanoView Series Sensors

Product Description	V8-T5-27
Product Selection	V8-T5-28

5.3 IntelliView Series Sensors

Product Description	V8-T5-33
Product Selection	V8-T5-34

5.4 SM Series Sensors

Product Description	V8-T5-48
Product Selection	V8-T5-50

5.5 Comet Series Sensors

Product Description	V8-T5-54
Product Selection	V8-T5-56

5.6 Prism Series Sensors

Product Description	V8-T5-69
Product Selection	V8-T5-70

5.7 OEM Prism Series Sensors

Product Description	V8-T5-78
Product Selection	V8-T5-79

5.8 E58 Harsh Duty Series Sensors

Product Description	V8-T5-84
Product Selection	V8-T5-86

5.9 E67 Long Range Perfect Prox Series Sensors

Product Description	V8-T5-93
Product Selection	V8-T5-94

5.10 E51 Limit Switch Style, Modular Sensors

Product Description	V8-T5-97
Product Selection	V8-T5-98










Unless otherwise noted, the products contained in this section should not be used for functional safety applications. These products were not designed or tested to IEC 60947-5-3 or recommended for functional safety.



For Customer Service in the U.S. call 1-877-ETN CARE (386-2273),
in Canada call 1-800-268-3578.
For Application Assistance in the U.S. and Canada
call 1-800-426-9184.

Quick Reference Guide

Photoelectric Sensors

Sensing Application	Sensing Style	Maximum Range	Product Family	Page
	Through beam	500 ft (152m)	Enhanced 50 Series Sensors	V8-T5-9
		50 ft (15m)	SM Series Sensors	V8-T5-48
		80 ft (24m)	Comet® Series Sensors	V8-T5-54
		20 ft (6m)	Prism™ Series Sensors	V8-T5-69
		800 ft (250m)	E58 Harsh Duty Series Sensors	V8-T5-84
		19 ft (6m)	NanoView Series Sensors	V8-T5-27
	Diffuse reflective	10 ft (3m)	Enhanced 50 Series Sensors	V8-T5-9
		2 ft (610 mm)	Comet Series Sensors	V8-T5-54
		8 in (200 mm)	SM Series Sensors	V8-T5-48
		8 in (200 mm)	Prism Series Sensors	V8-T5-69
		13.8 in (350 mm)	NanoView Series Sensors	V8-T5-27
	Fixed Focus Perfect Prox®	4 in (50 mm)	SM Series Sensors	V8-T5-48
		9 in (225 mm)	Comet Series Sensors	V8-T5-54
		11 in (280 mm)	E58 Harsh Duty Series Sensors	V8-T5-84
		79 in (200 cm)	E67 Long Range Perfect Prox Series Sensors	V8-T5-93
		3.9 in (100 mm)	NanoView Series Sensors	V8-T5-27
	Background suppression	47.2 in (120 cm)	IntelliView Series Sensors	V8-T5-33
	Standard reflex	30 ft (9m)	Enhanced 50 Series Sensors	V8-T5-9
		25 ft (7.6m)	Comet Series Sensors	V8-T5-54
		15 ft (4.5m)	Prism Series Sensors	V8-T5-69
		59 ft (18m)	E58 Harsh Duty Series Sensors	V8-T5-84
	Polarized reflex	16 ft (4.9m)	Enhanced 50 Series Sensors	V8-T5-9
		15 ft (4.5m)	Comet Series Sensors	V8-T5-54
		10 ft (3m)	SM Series Sensors	V8-T5-48
		34 ft (10m)	E58 Harsh Duty Series Sensors	V8-T5-84
		8.2 ft (2.5m)	NanoView Series Sensors	V8-T5-27
	Clear object detector	45 in (120 cm)	Enhanced 50 Series Sensors	V8-T5-9
		31.5 in (80 cm)	NanoView Series Sensors	V8-T5-27
		6 in (150 mm)	Comet Series Sensors (wide-angle)	V8-T5-54