

## Coupling relay - PSR-PS22-1NO-1NC-24VDC-SC - 2702524

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Coupling relay for SIL 3 high and low-demand applications, couples digital output signals to the I/O, 1 enabling current path, 1 confirmation current path, safe state off applications, test pulse filter, fixed screw terminal block

### Your advantages

- ✓ Up to SIL 3 according to IEC 61508
- ✓ Forcibly guided contacts according to EN 50205
- ✓ Easy proof test according to IEC 61508
- ✓ Low housing width of just 6.8 mm
- ✓ Long service life thanks to filtering of controller test pulses
- ✓ 1 enabling current path, 1 diagnostic current path
- ✓ Couples digital output signals from failsafe controllers to I/O devices (valves, etc.) for electrical isolation and power adaptation



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 280240
GTIN	4055626280240
Weight per Piece (excluding packing)	71.490 g
Custom tariff number	85364900
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Width	6.8 mm
Height	93.1 mm

# Coupling relay - PSR-PS22-1NO-1NC-24VDC-SC - 2702524

## Technical data

### Dimensions

Depth	102.5 mm
-------	----------

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C (observe derating)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	75 % (on average, 85% infrequently, non-condensing)
Max. permissible humidity (storage/transport)	75 % (on average, 85% infrequently, non-condensing)
Maximum altitude	≤ 2000 m (Above sea level)

### Power supply

Rated control circuit supply voltage $U_s$	24 V DC -15 % / +10 % (A1/A2)
	20.4 V DC ... 26.4 V DC
Rated control supply current $I_s$	typ. 45 mA
Power consumption at $U_s$	typ. 1.08 W
Inrush current	typ. 150 mA ( $\Delta t < 5$ ms at $U_s$ )
Filter time	max. 3 ms (at A1-A2 in the event of voltage dips at $U_s$ )
	max. 3 ms (at A1-A2; low test pulse width)
	≥ 50 ms (at A1-A2; low test pulse rate)
	max. 17 ms (at A1-A2; high test pulse width)
	≥ 600 ms (at A1-A2; high test pulse rate)
Diagnostic supply voltage $U_D$	24 V DC -15 % / +10 % (21/0V)
Input current at $U_D$	6 mA (at the contacts 21/0V for $U_D$ ; + 100 mA depending on load at contact 22)
Inrush current at $U_D$	typ. 200 mA ( $\Delta t < 1$ ms; for contacts 21 - 0 V at $U_D$ )
Protective circuit	Serial protection against polarity reversal 33 V suppressor diode (A1-A2)33 V suppressor diode (21/0V)

### Relay outputs: enabling current path

Output name	Enabling current path
Output description	2 N/O contacts in series, without delay, floating
Number of outputs	1 (safety-related N/O contacts: 13/14)
Contact type	1 enabling current path
Contact material	AgSnO <sub>2</sub>
Switching voltage	min. 12 V AC/DC
	max. 250 V AC/DC (Observe the load curve)
Limiting continuous current	6 A (High demand)
	4 A (Low demand)
Inrush current	min. 3 mA
	max. 6 A
Sq. Total current	36 A <sup>2</sup> (observe derating)
Switching capacity	min. 60 mW
Switching frequency	max. 1 Hz