



Platinum Temperature Sensors

6W – Product Series

Temperature Range: –200°C...+600°C

Platinum temperature sensors elements with wire connections

Technical Data

Specification:	DIN EN 60751	
Temperature range:	-200°C to +600°C	
Temperature Coefficient:	TCR = 3850 ppm/K	
Tolerance Classes:	F 0.1 (Class Y)	-50°C to +150°C
	F 0.15 (Class A)	-90°C to +300°C
	F 0.3 (Class B)	-200°C to +600°C
	F 0.6 (Class C)	-200°C to +600°C
	1/5 F 0.3 (Class K)	on request
	1/10 F 0.3 (Class K)	on request
Leads:	Platinum-coated nickel wire ($\varnothing = 0.2$ mm) Recommended connection technology: Soldering, Welding, Crimping	
Lead Lengths:	7/10/15 mm	
Long-term stability:	Max. Drift = Less than 0.03% after 1000h at max. operating temperature	
Note:	Other connection lengths on request	



INNOVATIVE SENSOR TECHNOLOGY


ISTAG, Industriestrasse 2, CH-9630 Wattwil, Switzerland, Phone (+)41 71 987 73 73, Fax (+)41 71 987 73 77
e-mail info@ist-ag.com, www.ist-ag.com

6W – Product Series

Temperature Range: $-200^{\circ}\text{C} \dots +600^{\circ}\text{C}$


6W 161

Chip Dimensions, L x W:	1.6 x 1.2 mm	
Nominal Resistance at 0°C (ohm) :	100/500/1000	
Self Heating (mK):	Water (v= 0 m/s) Air (v= 0 m/s)	$\Delta T_w = 8.3$ at 0°C $\Delta T_a = 56$ at 0°C
Response Time (s):	Water (v= 0.4 m/s) Air (v= 1 m/s)	$T_{0.5} = 0.05$ $T_{0.63} = 0.08$ $T_{0.9} = 0.18$ $T_{0.5} = 1$ $T_{0.63} = 1.2$ $T_{0.9} = 2.5$
Measuring Current (mA):	100 Ω : 1 500 Ω : 0.5 1000 Ω : 0.3	



7W 161

Chip Dimensions, L x W:	1.6 x 1.2 mm	
Nominal Resistance at 0°C (ohm) :	100/1000	
Self Heating (mK):	Water (v= 0 m/s) Air (v= 0 m/s)	$\Delta T_w = 8.3$ at 0°C $\Delta T_a = 56$ at 0°C
Response Time (s):	Water (v= 0.4 m/s) Air (v= 1 m/s)	$T_{0.5} = 0.05$ $T_{0.63} = 0.08$ $T_{0.9} = 0.18$ $T_{0.5} = 1$ $T_{0.63} = 1.2$ $T_{0.9} = 2.5$
Measuring Current (mA):	100 Ω : 1 1000 Ω : 0.3	
Note:	Pure platinum wire, 0.2 mm diameter	



INNOVATIVE SENSOR TECHNOLOGY