



**Compact size 2 Form A and 2 Form A 1 Form B 35A power relays for energy management and industrial equipment**

## HE-S RELAYS

**New**



**RoHS compliant**

Protective construction: Flux-resistant type

### FEATURES

**1. High-capacity and long life 35A 277V AC  $5 \times 10^4$  (long life type)**

**2. Electrical life (resistive load)**

| Form A contact | Standard type   | Long life type  |
|----------------|-----------------|-----------------|
| 35A 277V AC    | $3 \times 10^4$ | $5 \times 10^4$ |
| 30A 220V AC    | —               | $1 \times 10^5$ |
| 20A 277V AC    | $1 \times 10^5$ | $2 \times 10^5$ |

**3. Compact size and low operating power**

W: 30 × L: 36 × H: 40 mm **W: 1.181 × L: 1.417 × H: 1.575 inch**  
Operating power: 1,880 mW (holding power: 170 mW)

**4. Reduced coil holding voltage contributes to saving energy of equipment**

The coil holding voltage can be reduced up to 30%V of the nominal coil voltage. This equals to operating power of approximately 170 mW, which contributes equipment energy savings.

\* Coil holding voltage is the coil voltage after 100 ms from the applied nominal coil voltage.

**5. Contact gap: 3.2 mm .126 inch (VDE0126 compliant)**

Compliant with European photovoltaic standard VDE0126  
Compliant with EN61810-1 2.5 kV surge breakdown voltage (between contacts)

**6. Insulation distance (initial)**

- Between Form A contact and coil: Min. 11.0 mm .433 inch (Clearance/Creepage)
- Between Form B contact and coil: Min. 3.2 mm .126 inch (Clearance/Creepage)
- Between Form A contact sets: Min. 8.2 mm .323 inch (Clearance/Creepage)
- Between Form A contact and Form B contact: Min. 12.8 mm .504 inch (Clearance/Creepage)

### TYPICAL APPLICATIONS

- Photovoltaic power generation systems (Solar inverter)
- Uninterruptible Power Supplies (UPS)
- Inverter
- Office air conditioner
- Industrial equipment

**7. Contact gap (initial)**

- Form A contact: Min. 3.2 mm .126 inch/each contact
- Form B contact: Min. 0.7 mm .028 inch  
Min. 0.5 mm .020 inch (When Form A contact welded)

**8. Mirror contact mechanisms (Compliant with EN60947-4-1 mirror contact)**

**Detection of main contact welding makes it possible to construct a safety circuit.**

- Designed so that Form A contact and Form B contact will not close at the same time.
- When Form A contact welded, Form B contact gap of at least 0.5 mm .020 inch is maintained.

\* Form B contact, when used to monitor the condition of Form A contact, can be used exclusively as an auxiliary contact.

| Condi-<br>tions                      | Normal operation |            | When Form A<br>contact welded |
|--------------------------------------|------------------|------------|-------------------------------|
|                                      | Non-excitation   | Excitation | Non-excitation                |
| Mirror<br>contact<br>mecha-<br>nisms |                  |            |                               |

ORDERING INFORMATION

AHES

9

Contact arrangement / Operating function

3: 2 Form A Single side stable type

4: 2 Form A 1 Form B Single side stable type

Contact specifications

1: Standard type

2: Long life type

Terminals form

9: PC board terminal type

Nominal coil voltage (DC)

Part No.

Nominal coil voltage (V)

|   |    |    |    |   |
|---|----|----|----|---|
| 0 | 1  | 2  | 3  | 5 |
| 6 | 12 | 24 | 48 | 9 |

Note: Certified by UL/C-UL and VDE

TYPES

| Contact arrangement | Nominal coil voltage | Part No.      |                |
|---------------------|----------------------|---------------|----------------|
|                     |                      | Standard type | Long life type |
| 2 Form A            | 6V DC                | AHES3190      | AHES3290       |
|                     | 9V DC                | AHES3195      | AHES3295       |
|                     | 12V DC               | AHES3191      | AHES3291       |
|                     | 24V DC               | AHES3192      | AHES3292       |
|                     | 48V DC               | AHES3193      | AHES3293       |
| 2 Form A 1 Form B   | 6V DC                | AHES4190      | AHES4290       |
|                     | 9V DC                | AHES4195      | AHES4295       |
|                     | 12V DC               | AHES4191      | AHES4291       |
|                     | 24V DC               | AHES4192      | AHES4292       |
|                     | 48V DC               | AHES4193      | AHES4293       |

Standard packing: Carton: 25 pcs.; Case: 100 pcs.

RATING

1. Coil data

| Nominal coil voltage | Pick-up voltage<br>(at 20°C 68°F)<br>(Initial) | Drop-out voltage<br>(at 20°C 68°F)<br>(Initial) | Nominal operating current<br>[±10%] (at 20°C 68°F) | Coil resistance<br>[±10%] (at 20°C 68°F) | Nominal operating power<br>(at 20°C 68°F) | Max. applied voltage<br>(at 55°C 131°F)                          |
|----------------------|------------------------------------------------|-------------------------------------------------|----------------------------------------------------|------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| 6V DC                | 75%V or less of nominal voltage                | 5%V or more of nominal voltage                  | 313mA                                              | 19.1Ω                                    | ON: 1,880mW<br>Holding: 170mW*1           | 110%V of nominal coil voltage<br>150%V of nominal coil voltage*2 |
| 9V DC                |                                                |                                                 | 209mA                                              | 43.1Ω                                    |                                           |                                                                  |
| 12V DC               |                                                |                                                 | 157mA                                              | 76.6Ω                                    |                                           |                                                                  |
| 24V DC               |                                                |                                                 | 78mA                                               | 306.4Ω                                   |                                           |                                                                  |
| 48V DC               |                                                |                                                 | 39mA                                               | 1,225.5Ω                                 |                                           |                                                                  |

Notes: \*1. With 30%V coil holding voltage  
\*2. With no more than 24 hours per time with non-consecutive voltage application time.