

SOCKET COMPATIBLE & FLANGE MOUNT RELAYS



782XBX

MANUFACTURED UNDER
ISO 9002 QS 9000

1.54 x 0.83 x 1.10

- ✦ 0.187 QUICK CONNECT/SOLDER PLUG-IN OR PRINTED CIRCUIT TERMINALS
- ✦ FLAG INDICATOR
- ✦ L.E.D. STATUS LAMP
- ✦ PUSH BUTTON WITH LOCK DOWN DOOR
- ✦ FINGER GRIP COVER
- ✦ I.D. TAG/WRITE LABEL
- ✦ OPTIONAL FLANGE AND DIN ADAPTERS
- ✦ UL LISTED WHEN USED WITH 70-459-1 OR 70-782D-1 SOCKETS



783XCX

MANUFACTURED UNDER
ISO 9002 QS 9000

1.54 x 1.21 x 1.10

- ✦ 0.187 QUICK CONNECT/SOLDER PLUG-IN OR PRINTED CIRCUIT TERMINALS
- ✦ FLAG INDICATOR
- ✦ L.E.D. STATUS LAMP
- ✦ PUSH BUTTON WITH LOCK DOWN DOOR
- ✦ FINGER GRIP COVER
- ✦ I.D. TAG/WRITE LABEL
- ✦ OPTIONAL FLANGE AND DIN ADAPTERS
- ✦ UL LISTED WHEN USED WITH 70-783D-1 SOCKET



784DX

MANUFACTURED UNDER
ISO 9002 QS 9000

1.54 x 1.60 x 1.10

- ✦ 0.187 QUICK CONNECT/ SOLDER PLUG-IN OR PRINTED CIRCUIT TERMINALS
- ✦ FLAG INDICATOR
- ✦ PUSH BUTTON WITH LOCK DOWN DOOR
- ✦ FINGER GRIP COVER
- ✦ I.D. TAG/WRITE LABEL
- ✦ OPTIONAL FLANGE AND DIN ADAPTERS
- ✦ UL LISTED WHEN USED WITH 70-784D-1 SOCKET

6, 12, 24, 110 / 120, 220 / 230, 240
6, 12, 24, 48, 110 /125

1.2

0.9

Class B (130°C)

6, 12, 24,110 / 120, 220 / 230, 240
6, 12, 24, 48, 110 /125

1.7

1.5

CLASS B (130°C)

6, 12, 24,110 / 120, 220 / 230, 240
6, 12, 24, 48, 110 /125

2

1.5

Class B (130°C)

DPDT

Silver alloy, gold flashed

50

15 / 12

120 / 277

12 / 0.5

28 / 220

1/2 @ 120 V

1 @ 250 V

25

20

2500

1000 @ 500

-40

+70

-40

+70

-40

+105

200,000

10,000,000

40

36

70-459-1, 70-782D-1, 70-401-1, 70-402-1

3PDT

Silver alloy, gold flashed

50

15 / 12

120 / 277

15 / 0.5

28 / 220

1/2 @ 120 V

3/4 @ 250 V

25

20

2500

1000 @ 500

-40

+70

-40

+70

-40

+105

150,000

10,000,000

40

60

70-783D-1

4PDT

Silver alloy, gold flashed

50

15 / 12

120 / 277

15 / 0.5

28 / 220

1/2 @ 120 V

3/4 @ 250 V

20

20

2500

100 @ 500

-40

+70

-40

+70

-40

+105

150,000

10,000,000

40

80

70-784D-1



UL Recognized
File No. E43641



40787



LISTED



PAGE 11, 12, 13, 16



UL Recognized
File No. E43641



40787



LISTED



PAGE 11, 12, 13, 17



UL Recognized
File No. E43641



40787



LISTED



PAGE 11, 12, 13, 18

9/04



**782XBX1
& 782XDX1**

MANUFACTURED UNDER
ISO 9002 QS 9000



**782XBX2
& 782XDX2**

MANUFACTURED UNDER
ISO 9002 QS 9000

PRODUCT

L X W X H (INCHES)

1.54 x 0.83 x 1.10

1.54 x 0.83 x 1.10

FEATURES

- ✦ 0.100 QUICK CONNECT/ SOLDER PLUG-IN OR PRINTED CIRCUIT TERMINALS
 - ✦ FLAG INDICATOR
 - ✦ L.E.D. STATUS LAMP
 - ✦ PUSH BUTTON
 - ✦ FINGER GRIP COVER
 - ✦ I.D. TAG/WRITE LABEL
 - ✦ OPTIONAL FLANGE AND DIN ADAPTERS AVAILABLE
 - ✦ UL LISTED WHEN USED WITH 70-461-1 SOCKET

- ✦ 0.100 QUICK CONNECT/ SOLDER PLUG-IN OR PRINTED CIRCUIT TERMINALS
 - ✦ FLAG INDICATOR
 - ✦ L.E.D. STATUS LAMP
 - ✦ PUSH BUTTON WITH LOCK DOWN DOOR
 - ✦ FINGER GRIP COVER
 - ✦ I.D. TAG/WRITE LABEL
 - ✦ OPTIONAL FLANGE AND DIN ADAPTERS AVAILABLE
 - ✦ UL LISTED WHEN USED WITH 70-461-1 SOCKET

COIL		UNITS		
Standard Voltage AC:		50/60 Hz	6, 12, 24, 110 / 120, 220 / 230, 240	6, 12, 24, 110 / 120, 220 / 230, 240
DC:			6, 12, 24, 48, 110 /125	6, 12, 24, 48, 110 /125
Coil Power AC (60 Hz):		VA	1.2	1.2
Coil Power DC:		W	0.9	0.9
Insulation System Per UL Standard 1446:			Class B (130°C)	Class B (130°C)
CONTACTS				
Contact Configuration:			DPDT, 4PDT	DPDT, 4PDT
Contact Material:			Silver alloy, gold flashed	Silver alloy, gold flashed
Contact Resistance (Initial):	m Ohms		50	50
Contact Rating AC Amperes (AC1):	A		3	10 / 8.0
Contact Rating AC Voltage:	V		240	120 / 277
Contact Rating DC Amperes (DC1):	A		3 / 0.25	8 / 0.25
Contact Rating DC Voltage:	V		28 / 220	28 / 220
Horse Power (AC):	Hp			1/3 @ 120 V
Horse Power (AC):	Hp		1/10 @ 240 V	1 @ 277 V
TIMING				
Operate Time:	ms		20	20
Release Time:	ms		20	20
DIELECTRIC STRENGTH				
Coil to Contacts:	V rms		1500	1500
Insulation Resistance:	megohms minimum @ VDC		100 @ 500	100 @ 500
TEMPERATURE				
Operating, AC Lower:	°C		-40	-40
Operating, AC Upper:	°C		+70	+70
Operating, DC Lower:	°C		-40	-40
Operating, DC Upper:	°C		+70	+70
Storage, Lower:	°C		-40	-40
Storage, Upper:	°C		+105	+105
LIFE EXPECTANCY				
Electrical @ Rated Load (AC1):	operations		200,000	200,000
Mechanical @ no Load :	operations		10,000,000	10,000,000
MISCELLANEOUS				
Cover Protection Category:	IP		40	40
Weight:	grams		36	36

MATING SOCKETS
SEE SECTION 7

70-461-1, 70-378-1, 70-379-1

70-461-1, 70-378-1, 70-379-1

AGENCY APPROVALS



PAGE NUMBER

PAGE 11, 19, 20, 21, 22, 23

PAGE 11, 19, 20, 21, 22, 23