# Slim I/O Relay
## G2RV-SR/G3RV-SR



## Global standard size, low profile slim I/O relay with width 6.2 mm, slim I/O solid state relay

- Realized about 25% lower profile than conventional products, contributing to further miniaturization of the control panel.
- Push-In Plus technology are used to save wiring work in comparison with conventional screw terminals. (Wiring time is reduced by 60%* in comparison with traditional screw terminals.)
- No screw loosening means maintenance-free application, realizing high reliability
- 'Hand-free' structure that holds an inserted flat-blade screwdriver to achieve easier wiring work for stranded wires.
- Screw terminal is also stocked to meet the screw type needs.
- Mounted relay or solid-state relay has a plug-in terminal that is difficult to bend at the time of exchange.

* According to OMRON actual measurement data from November 2015.

For the recent information on models that have been certified for safety standards, refer to your OMRON website.

⚠ Refer to ***Safety Precautions*** on page 20.

## Slim I/O Relay Types

**G2RV-SR series mounted relay: electromagnetic relay ..... from page 2**
**G3RV-SR series mounted relay: solid state relay ..... from page 10**

## Common matter

**Common precautions ..... from page 20**
**Common accessories (order separately)..... from page 24**

Slim I/O Relay

# G2RV-SR

## Global standard size, low profile slim I/O relay with width 6.2 mm

- Realized about 25% lower profile than conventional products, contributing to further miniaturization of the control panel.
- Realized opening and closing ability with one pole 6 A slim shape.
- Micro load products for one pole 50 mA using Au-plated contacts for small load switching also available.
- Since G2RV is a transparent case, confirming the state of the contact with the naked eye is possible, and easy to confirm abnormality on-site (installed location).
- Screw terminal is also stocked to meet the screw type needs.
- Mounted relay uses plug-in terminals that are difficult to bend when exchanging.

⚠ Refer to ***Safety Precautions*** on page 20.



For the recent information on models that have been certified for safety standards, refer to your OMRON website.

## Features

**Standard model/Micro load**




**With latching lever (Test switch)**




• Circuit check operation Confirmation, reducing the inspection effort

**PAT**

"Foreign matter intrusion prevention structure"
"Malfunction prevention stopper"

**Push-in plus technology**




**Transparent case**

Relay contact
Easy confirmation of the situation

**Release lever**

Relay easily fixed/removed



**Plug-in terminal**

Peace of mind as the terminal does not bend when replacing