



Main

| | |
|-------------------------------|--|
| Range of product | OsiSense XU |
| Series name | General purpose single mode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XU9 |
| Sensor design | Cylindrical M18 |
| Detection system | Polarised reflex |
| Material | Metal |
| Line of sight type | Axial |
| Type of output signal | Discrete |
| Supply circuit type | AC/DC |
| Wiring technique | 2-wire |
| Discrete output function | 1 NC |
| Electrical connection | Cable |
| Cable length | 2 m |
| Product specific application | - |
| Emission | Red polarised reflex |
| [Sn] nominal sensing distance | 2 m polarised reflex need reflector XUZC50 |

Complementary

| | |
|---------------------------|---|
| Enclosure material | Nickel plated brass |
| Lens material | PMMA |
| Maximum sensing distance | 3 m |
| Output type | Solid state |
| Add on output | Without |
| Wire insulation material | PvR |
| Status LED | 1 LED (red) for instability 1 LED (yellow) for output state |
| [Us] rated supply voltage | 24...240 V AC/DC |
| Supply voltage limits | 20...264 V AC/DC |
| Residual current | < 1.5 mA (open state) |
| Switching capacity in mA | 10...200 mA (to be used with 0.4 A quick-blow fuse in series with the load) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------|----------------------------|
| Switching frequency | <= 25 Hz |
| Voltage drop | 6 V (closed state) |
| Delay first up | < 300 ms |
| Delay response | < 20 ms |
| Delay recovery | < 20 ms |
| Setting-up | Sensitivity adjustment |
| Diameter | 18 mm |
| Length | 95 mm |
| Product weight | 0.095 kg |
| Kit composition | Sensor Reflector XUZC50 |

Environment

| | |
|---------------------------------------|---|
| Product certifications | CE CSA UL |
| Ambient air temperature for operation | -25...55 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27 |
| IP degree of protection | IP67 conforming to IEC 60529 |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0924 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|