

## Description

# Magnecraft General Purpose Relays

## 792 Control Series

DPDT 12 A; 4PDT 6 A and 3 A



UL listed when used with proper Magnecraft sockets



792 Clear Cover



792 Full-Feature Cover

## Description

The 792 Plug-in Control relays offer clear or full-feature covers with multiple mounting options and accessories; 4PDT models save valuable space while adding increased functionality.

| Feature                             | Benefit                                                                                                                          |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| 12 A / 6 A / 3 A switching current  | Ideal for various automation panels and controls                                                                                 |
| Clear or full-feature cover options | Full-feature covers include LED indicator and locking test button to facilitate maintenance and expedite commissioning           |
| DPDT and 4PDT contact options       | Simultaneously control 2 or 4 separate circuits                                                                                  |
| Socket mount option                 | Simplifies installation and maintenance while also allowing the use of protection modules, hold-down clips and other accessories |
| Gold-flashed contacts               | Reduces contact oxidation and increases shelf life                                                                               |
| Mechanical flag indicator           | Standard feature that displays relay status during testing or operation without having to power the relay                        |

| Contact Rating | Contact Configuration | Nominal Coil Voltage | Coil Resistance (Ω) | Contacts             | Part Number: Clear Cover | Part Number: Clear Cover with LED | Part Number: Full-Feature Cover |
|----------------|-----------------------|----------------------|---------------------|----------------------|--------------------------|-----------------------------------|---------------------------------|
| 3 A            | 4PDT                  | 12 Vac               | 44                  | Low Level Bifurcated | 792XDX3C-12A             | 792XDX3CL-12A                     | 792XDX3M4L-12A                  |
|                |                       | 24 Vac               | 177                 |                      | 792XDX3C-24A             | 792XDX3CL-24A                     | 792XDX3M4L-24A                  |
|                |                       | 48 Vac               | 708                 |                      | 792XDX3C-48A             | 792XDX3CL-48A                     | 792XDX3M4L-48A                  |
|                |                       | 120 Vac              | 3630                |                      | 792XDX3C-120A            | 792XDX3CL-120A                    | 792XDX3M4L-120A                 |
|                |                       | 240 Vac              | 17720               |                      | 792XDX3C-240A            | 792XDX3CL-240A                    | 792XDX3M4L-240A                 |
|                |                       | 12 Vdc               | 160                 |                      | 792XDX3C-12D             | 792XDX3CL-12D                     | 792XDX3M4L-12D                  |
|                |                       | 24 Vdc               | 640                 |                      | 792XDX3C-24D             | 792XDX3CL-24D                     | 792XDX3M4L-24D                  |
|                |                       | 48 Vdc               | 2560                |                      | 792XDX3C-48D             | 792XDX3CL-48D                     | 792XDX3M4L-48D                  |
|                |                       | 110 Vdc              | 13440               |                      | 792XDX3C-110D            | 792XDX3CL-110D                    | 792XDX3M4L-110D                 |
|                |                       |                      |                     |                      |                          |                                   |                                 |
| 12 A           | DPDT                  | 12 Vac               | 44                  | Standard             | 792XBXC-12A              | —                                 | 792XBXM4L-12A                   |
|                |                       | 24 Vac               | 177                 |                      | 792XBXC-24A              | —                                 | 792XBXM4L-24A                   |
|                |                       | 48 Vac               | 708                 |                      | 792XBXC-48A              | —                                 | 792XBXM4L-48A                   |
|                |                       | 120 Vac              | 3630                |                      | 792XBXC-120A             | —                                 | 792XBXM4L-120A                  |
|                |                       | 240 Vac              | 17720               |                      | 792XBXC-240A             | —                                 | 792XBXM4L-240A                  |
|                |                       | 12 Vdc               | 160                 |                      | 792XBXC-12D              | —                                 | 792XBXM4L-12D                   |
|                |                       | 24 Vdc               | 640                 |                      | 792XBXC-24D              | —                                 | 792XBXM4L-24D                   |
|                |                       | 48 Vdc               | 2560                |                      | 792XBXC-48D              | —                                 | 792XBXM4L-48D                   |
|                |                       | 110 Vdc              | 13440               |                      | 792XBXC-110D             | —                                 | 792XBXM4L-110D                  |
|                |                       |                      |                     |                      |                          |                                   |                                 |
| 6 A            | 4PDT                  | 12 Vac               | 44                  | Standard             | 792XDXC-12A              | 792XDXCL-12A                      | 792XDXM4L-12A                   |
|                |                       | 24 Vac               | 177                 |                      | 792XDXC-24A              | 792XDXCL-24A                      | 792XDXM4L-24A                   |
|                |                       | 48 Vac               | 708                 |                      | 792XDXC-48A              | 792XDXCL-48A                      | 792XDXM4L-48A                   |
|                |                       | 120 Vac              | 3630                |                      | 792XDXC-120A             | 792XDXCL-120A                     | 792XDXM4L-120A                  |
|                |                       | 240 Vac              | 17720               |                      | 792XDXC-240A             | 792XDXCL-240A                     | 792XDXM4L-240A                  |
|                |                       | 12 Vdc               | 160                 |                      | 792XDXC-12D              | 792XDXCL-12D                      | 792XDXM4L-12D                   |
|                |                       | 24 Vdc               | 640                 |                      | 792XDXC-24D              | 792XDXCL-24D                      | 792XDXM4L-24D                   |
|                |                       | 48 Vdc               | 2560                |                      | 792XDXC-48D              | 792XDXCL-48D                      | 792XDXM4L-48D                   |
|                |                       | 110 Vdc              | 13440               |                      | 792XDXC-110D             | 792XDXCL-110D                     | 792XDXM4L-110D                  |
|                |                       |                      |                     |                      |                          |                                   |                                 |

## Part Number Explanation

**Series:** **792** = 792 Series Control Relay

**Contact Configuration:**  
**XBX** = DPDT  
**XDX** = 4PDT

**Contact Code:**  
**None** = Standard 6–12 A Silver Alloy Contacts  
**3** = 3 A Bifurcated Contacts

**Cover Options:**  
**C** = Clear Cover  
**CL** = Clear Cover and LED  
**M4L** = Locking Push Button and LED

**Coil Voltages:**  
**12–240A** = 12–240 VAC  
**12–110D** = 12–110 VDC

**Part Number Example:** **792** **XDX** **3** **M4L** - **24D**

\*Please contact Customer Service for more information (847-441-2540).

## Specifications

| Part Number                                                    | 792XBX                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Contact Characteristics</b>                                 |                                                                                                                                                                                                                                                                           |
| Terminal Style                                                 | Blade                                                                                                                                                                                                                                                                     |
| Contact Material                                               | Silver Alloy                                                                                                                                                                                                                                                              |
| Contact Configuration                                          | DPDT                                                                                                                                                                                                                                                                      |
| Maximum Switching Current                                      | 12 A                                                                                                                                                                                                                                                                      |
| Maximum Switching Voltage                                      | IEC: 250 Vac / 28 Vdc<br>UL/CSA: 300 Vac / 30 Vdc                                                                                                                                                                                                                         |
| Rated Operational Current<br>(Conforming to IEC AC-1 and DC-1) | NO: 12 A at 250 Vac, NC: 6 A at 250 Vac<br>NO: 12 A at 28 Vdc, NC: 6 A at 28 Vdc                                                                                                                                                                                          |
| Rated Operational Current<br>(Conforming to UL)                | <b>Resistive:</b> 12 A at 277 Vac, 100k cycles<br><b>Resistive:</b> 12 A at 120 Vac, 200k cycles<br><b>Resistive:</b> 12 A at 30 Vdc, 100k cycles<br><b>Motor:</b> 1/2 HP at 120 Vac, 6k cycles<br><b>Motor:</b> 1 HP at 277 Vac, 6k cycles<br>B300 PILOT DUTY, 6k cycles |
| Minimum Switching Requirement                                  | 10 mA at 17 Vdc                                                                                                                                                                                                                                                           |
| <b>Coil Characteristics</b>                                    |                                                                                                                                                                                                                                                                           |
| Maximum Operating Voltage                                      | 110% (AC / DC)                                                                                                                                                                                                                                                            |
| Maximum Pickup Voltage                                         | 80% (AC); 80% (DC)                                                                                                                                                                                                                                                        |
| Drop-out Voltage Threshold                                     | 15% (AC); 10% (DC)                                                                                                                                                                                                                                                        |
| Average Consumption                                            | 0.9–1.2 VA (AC); 0.8–1.1 W (DC)                                                                                                                                                                                                                                           |
| <b>General Characteristics</b>                                 |                                                                                                                                                                                                                                                                           |
| Electrical Life at Rated Load                                  | 200,000 operations (where stated)                                                                                                                                                                                                                                         |
| Mechanical Life (Unpowered)                                    | 10,000,000 operations                                                                                                                                                                                                                                                     |
| Operating Time                                                 | 25 ms max. at 80% rated coil voltage<br>20 ms max. at 100% rated coil voltage                                                                                                                                                                                             |
| Release time                                                   | 20 ms max. (DC)<br>35 ms max. (AC)                                                                                                                                                                                                                                        |
| Impulse Withstand Voltage                                      | 4 kV (1.2 / 50 $\mu$ s)                                                                                                                                                                                                                                                   |
| Dielectric Strength - Between Coil and Contact (AC)            | 2000 V(rms)                                                                                                                                                                                                                                                               |
| Dielectric Strength - Between Poles (AC)                       | 2000 V(rms)                                                                                                                                                                                                                                                               |
| Dielectric Strength - Between Contacts (AC)                    | 1300 V(rms)                                                                                                                                                                                                                                                               |
| Ambient Air Temperature around the Device<br>- Storage         | -40 to +85 °C (-40 to +185 °F)                                                                                                                                                                                                                                            |
| Ambient Air Temperature around the Device<br>- Operation       | -40 to +55 °C (-40 to +131 °F)                                                                                                                                                                                                                                            |
| Vibration Resistance - In Operation                            | 3 g-n at 35–150 Hz                                                                                                                                                                                                                                                        |
| Vibration Resistance - Not Operating                           | 5 g-n at 35–150 Hz                                                                                                                                                                                                                                                        |
| Shock Resistance - In Operation                                | 10 g-n                                                                                                                                                                                                                                                                    |
| Shock Resistance - Not Operating                               | 30 g-n                                                                                                                                                                                                                                                                    |
| Degree of Protection (Housing Only)                            | IP 40                                                                                                                                                                                                                                                                     |
| Weight                                                         | 37 g (1.31 oz)                                                                                                                                                                                                                                                            |
| Agency Approvals                                               | UL with socket, UR (E164862), CE, CSA (225619), RoHS                                                                                                                                                                                                                      |

Note: Actual product performance may vary depending on application and environmental conditions.