

## Three phases, primary switched mode power supply **PC-0324-100-0**



Picture shows PC-0324-100-0

### Advantages

Stabilised and adjustable output voltage
Fast tripping of standard bi-metal circuit breakers
DC OK signal contact
Parallel operation
Push-in terminals
Robust DIN rail mounting
Resistant to transient overvoltages up to 4 kV
Optional with 50 % Power Boost (PC-0324-xxx-2)

### Applications

The economic power supplies in the Power Compact series set new standards in their class. Above-average robustness against transients and energetic surge pulses at their input and equipped with essential additional aspects for a worldwide high plant availability. The output voltage can be set easily using the rotary potentiometer on the front of the housing. The robust DIN rail fastening method and push-in connection terminals enable fast and secure mounting. All versions are available as option with 50% power reserves for high inrush current applications.

### Standards

Primary switched mode power supply  
to UL 60950, UL 508

Safety:  
EN 61558-2-16, EN 60950-1

EMC:  
EN 61204-3

### Approvals




UL/CSA 60950, UL 508, GL (in preparation)



## Three phases, primary switched mode power supply **PC-0324-100-0**

Type	PC-0324-100-0
<b>Electrical data</b>	
<b>Input</b>	
Input rated voltage	400 - 500 Vac
Input voltage range	320 - 575 Vac
Input voltage derating	-
Rated frequency range	44 Hz - 66 Hz / 0 Hz
Input rated current (rated load)	3 x 0.73 A (400 Vac) / 0.66 A (500 Vac)
Starting current limiter	< 30 A, NTC
Input fuse internal	-
Recommended back-up fuse (circuit breaker)	6 A, 10 A, 16 A, characteristic B, C
Transient surge voltage protection	Varistor
<b>Output</b>	
Output rated voltage	24 Vdc
Output voltage range	23 - 28.5 Vdc
Output rated current	10 A
Output limited current	typ. 11 A (constant current)
Power Boost	-
Tripping of LS circuit breakers	max B6/C2 @ 2.5mm <sup>2</sup> / 20m
Parallel connection	Yes
Serial operation	Yes
Power dissipation, no load/rated load	2.7 W / 27.6 W (400 Vac)
Efficiency	typ. 90 %
Ripple factor	typ. 30 mVss
Resistance to reverse feed max.	35 Vdc
Over-voltage-protection	max. 40 Vdc
<b>Signaling</b>	
Status indicator	LED green
Signal output	Relay contact
<b>Approvals</b>	
Approvals	cURus, cULus, GL (in preparation)
<b>Environment</b>	
Cooling method	natural convection
Ambient temperature	-25° C ... +70° C
Storage temperature	-25° C ... +85° C
Derating	-2.5 %/K > +55° C
Required minimum spacing (left/right)	0 mm
Required minimum spacing (over/under)	50 mm
<b>Safety and protection</b>	
Protection index	IP 20
Safety class	I, with PE connection
<b>Order numbers</b>	
<b>Order Number</b>	<b>PC-0324-100-0</b>

Type	PC-0324-100-0
<b>Mechanical data</b>	
<b>Input</b>	
Connections input (direct plug-in technology Push-In)	max 2,5 mm <sup>2</sup>
<b>Output</b>	
Connections output (direct plug-in technology Push-In)	max 2,5 mm <sup>2</sup>
<b>Signaling</b>	
Connections signalling (direct plug-in technology Push-In)	max 2,5 mm <sup>2</sup>
<b>Environment</b>	
Mounting position	horizontal for standard rail DIN TH 35
<b>Measures and weights</b>	
Weight	1.02 kg
Dimensions W x H x D	55 x 127 x 152 mm



Subjects to change.