

Switching Power Supplies

PS5R-V Series



STANDARDS COMPLIANCE

Applicable Standards	Mark	File No. or Organization
UL508 UL1310 ¹ ANSI/ISA 12.12.01 CSA C22.2 No.107.1 CSA C22.2 No.213 CSA C22.2 No.223 ¹		UL/c-UL Listed File No. E467154, E177168
EN60950-1 EN50178 EN61204-3 EN50581	 	TÜV SÜD ² EU Low Voltage Directive EMC Directive RoHS Directive
SEMI F47	—	EPRI

Note 1: PS5R-VB/VC/VD/VE only

Note 2: EN60950-1, EN50178 only

POWER SUPPLY PART NUMBERS

Output Capacity	Part Number	Input Voltage	Output Voltage	Output Current
10W	PS5R-VB05	100 to 240V AC (Voltage range: 85 to 264V AC / 100 to 370V DC)	5V	2.0A
15W	PS5R-VB12		12V	1.3A
	PS5R-VB24		24V	0.65A
30W	PS5R-VC12		12V	2.5A
	PS5R-VC24		24V	1.3A
60W	PS5R-VD24		24V	2.5A
90W	PS5R-VE24		24V	3.75A
120W	PS5R-VF24		24V	5.0A
240W	PS5R-VG24		24V	10.0A

Part Number Structure

PS5R - V ☐ ☐

Output Voltage

05: 5V³
12: 12V⁴
24: 24V

Output Capacity

B: 10W/15W
C: 30W
D: 60W
E: 90W
F: 120W
G: 240W

Note 3: PS5R-VB only

Note 4: PS5R-VB/VC only

Use only for interpreting part numbers.

Do not use for developing part numbers.

PRODUCT DESCRIPTION

DIN-rail mount switching power supplies with global approvals for both industrial and hazardous locations

KEY FEATURES

- Compact size preserves panel space
- Slim size (width):
22.5mm (10W/15W/30W)
36mm (60W/90W)
46mm (120W)
60mm (240W)
- Universal Voltage Input:
85-264V AC/100-370V DC
- Wide operating temperature range
- Spring-up terminals accept ring & fork terminals
- Approved for use in Class I Division 2 hazardous locations
- Can be installed in 6 directions
- 10W ~ 90W meet NEC Class 2 output ratings
- Overcurrent protection with auto-reset
- Meets SEMI F47 Sag Immunity (208V AC input)
- RoHS compliant
- Five-year factory warranty



SPECIFICATIONS

Model		5V DC output	PS5R-VB05		-		-		-									
		12V DC output	PS5R-VB12		PS5R-VC12		-		-									
		24V DC output	PS5R-VB24		PS5R-VC24		PS5R-VD24		PS5R-VE24									
Output Capacity			15W (5V Model is 10W)		30W		60W		90W		120W		240W					
Rated Input Voltage (Single-phase two-wire) ¹			100 to 240V AC (Voltage range: 85 to 264V AC/100 to 370V DC) (Load ≤ 80% at 100-105V DC)															
			50/60 Hz															
Input	Input Current (Typ.)		100V AC	5V: 0.25A 12V, 24V: 0.35A		0.7A		1.3A		1.1A		1.4A		2.7A				
			230V AC	5V: 0.14A 12V, 24V: 0.19A		0.3A		0.8A		0.6A		0.7A		1.2A				
	Inrush Current (Typ.) (Ta=25°C, cold start)		100V AC	18A										14A				
			230V AC	45A										41A		30A		
	Leakage Current		120V AC	0.5mA max.														
			230V AC	1.0mA max.														
	Efficiency (Typ.) (at rated output) ²		100V AC	5V: 77%, 12V: 82%, 24V: 84%		12V: 83%, 24V: 85%		86%				88%		89%				
			230V AC	5V: 73%, 12V: 80%, 24V: 81%		12V: 85%, 24V: 87%		86%				89%		90%				
Power Factor (Typ.)		100V AC	—		—		—				0.99							
		230V AC	—		—		—		0.86		0.92		0.96					
Output	Rated Voltage/Current		5V/2.0A ³ , 12V/1.3A, 24V/0.65A			12V/2.5A, 24V/1.3A		24V/2.5A		24V/3.75A		24V/5A		24V/10A				
	Adjustable Voltage Range					±10%				±5%				±10%				
	Output Holding Time (Typ.) (at rated output)		100V AC	5V: 53ms, 12V: 34ms, 24V: 36ms			12V: 13ms, 24V: 15ms		13ms		20ms		30ms					
			230V AC	5V: 330ms 12V: 215ms 24V: 230ms			12V: 110ms 24V: 110ms		105ms		30ms		33ms		40ms			
	Start Time (at rated input and output)		500ms max.			600 ms max.		800 ms max.				700 ms max.		800 ms max.				
	Rise Time (at rated input and output)		5V, 12V: 200ms max. 24V: 250ms max.					200ms max.										
	Regulation	Input Fluctuation		0.4% max.														
		Load Fluctuation		5V: 2.5% max. 12V, 24V: 1.0% max.					1.0% max.									
		Temperature Change		0.05%/oC max. (-10 to +65°C)			12V: 0.05%/°C max. (-10 to +50°C) 24V: 0.05%/°C max. (-10 to +55°C)		0.05%/°C max. (-10 to +55°C)		0.05%/°C max. (-10 to +50°C)		0.05%/°C max. (-25 to +55°C)		0.05%/°C max. (-25 to +50°C)			
		Ripple (including noise)		5V: 8% p-p max. (-25 to -10°C) 12V: 6% p-p max. (-25 to -10°C) 24V: 4% p-p max. (-25 to -10°C)			12V: 6% p-p max. (-25 to -10°C) 24V: 4% p-p max. (-25 to -10°C)				4% p-p max. (-25 to -10°C)							
				5V: 5% p-p max. (-10 to +0°C) 12V: 2.5% p-p max. (-10 to +0°C) 24V: 1.5% p-p max. (-10 to +0°C)			12V: 2.5% p-p max. (-10 to +0°C) 24V: 1.5% p-p max. (-10 to +0°C)				1.5% p-p max. (-10 to +0°C)							
			5V: 2.5% p-p max. (0 to +65°C) 12V: 1.5% p-p max. (0 to +65°C) 24V: 1% p-p max. (0 to +65°C)			12V: 1.5% p-p max. (0 to +50°C) 24V: 1% p-p max. (0 to +55°C)		1% p-p max. (0 to +55°C)		1% p-p max. (0 to +50°C)		1% p-p max. (0 to +55°C)		1% p-p max. (0 to +50°C)				
Overcurrent Protection			105% min. (auto reset)					101% min. (auto reset)		105% min. (auto reset)								
Operation Indicator			LED (green)															
Dielectric Strength	Between input and output terminals		3,000V AC, 1 minute															
	Between input and ground terminals		2,000V AC, 1 minute															
	Between output and ground terminals		500V AC, 1 minute															
Insulation Resistance			Between input and output terminals: 100MΩ min. (500V DC megger) Between input and ground terminals: 100MΩ min. (500V DC megger)															
Operating Temperature ⁴ (No freezing)			-25 to +75°C			-25 to +70°C			-25 to +65°C									
Operating Humidity			20 to 90% RH (no condensation)															
Storage Temperature (No freezing)			-25 to +75°C															
Storage Humidity			20 to 90% RH (no condensation)															
Vibration Resistance			10 to 55Hz, amplitude 0.375mm, 2 hours each in 3 axes (when used with BNL6 end clips)					10 to 55Hz, amplitude 0.33mm, 2 hours each in 3 axes (when used with BNL6 end clips) 10 to 55Hz, amplitude 0.375mm, 2 hours each in 3 axes (when used with BNL8 end clips)			10 to 55Hz, amplitude 0.21mm, 2 hours each in 3 axes (when used with BNL6 end clips) 10 to 55Hz, amplitude 0.375mm, 2 hours each in 3 axes (when used with BNL8 end clips)		10 to 55 Hz, amplitude 0.375mm, 2 hours each in 3 axes (when used with part no. BNL6 mounting clips)					
Shock Resistance			300 m/s ² (30G), 3 times each in 6 directions															
Expected Life ⁵			8 years minimum (at the rated input, 50% load, operating temperature +40°C, standard mounting direction)															
EMC	EMI	EN61204-3 (Class B)																
	EMS	EN61204-3 (industrial)																
Safety Standards			UL508 (Listing), UL1310 Class 2, ANSI/ISA-12.12.01 CSA C22.2 No. 107.1, 213, 223 EN60950-1, EN50178					UL508 (Listing) ANSI/ISA-12.12.01 CSA C22.2 No. 107.1, 213 EN60950-1, EN50178										
Other Standard			SEMI F47 (at 208V AC input only)															
Degree of Protection			IP20 (EN60529)															
Dimensions (mm)			90H × 22.5W × 95D					95H × 36W × 108D					115H × 46W × 121D		125H × 60W × 125D			
Weight (approx.)			140g			150g			260g			310g			470g		960g	
Terminal Screw			M3.5															

At normal temperature and humidity unless otherwise specified.

Note 1: DC input voltage is not subject to safety standards. When using on DC input, connect a fuse to the input terminal for DC input protection.

Note 2: Under stable state.

Note 3: PS5R-VB05 (5V DC/2.0A) is 10W (Up to 3.0A at Ta = 0 to 40°C. Not subject to safety standards above 2.0A.)

Note 4: See the output derating curves on page 3.

Note 5: Calculation of the expected life is based on the actual life of the aluminum electrolytic capacitor. The expected life depends on operating conditions.