

QUINT-ORING/24DC/2X20/1X40

Order No.: 2320186




<http://eshop.phoenixcontact.co.uk/phoenix/treeViewClick.do?UID=2320186>

Active redundancy module with ACB technology and monitoring functions



Commercial data

EAN	 4 046356 524919
Pack	1
Customs tariff	85044082
Country of Origin	CN
Catalog page information	Page 626 (IF-2011)

Product notes

WEEE/RoHS-compliant since:
26/08/2009



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Input data

Nominal input voltage	24 V DC
DC input voltage range	18 V DC ... 28 V DC (SELV)
Type of protection	Protection against static surge voltages > 35 V
Nominal input current I_N	2x 20 A (-25 °C ... 60 °C) 1x 40 A (-25 °C ... 60 °C)

Maximum current I_{max}	2x 26 A (-25°C ... 40°C)
	1x 52 A (-25°C ... 40°C)

Output data

Nominal output voltage	0.2 V (< DC input)
Output current	40 A (Increasing power)
	20 A (Redundancy)
Derating	60 °C ... 70 °C (2.5%/K)
Power loss nominal load max.	4 W ($I_{OUT} = 20$ A)

General data

Width	38 mm
Height	130 mm
Depth	125 mm
Net weight	0.6 kg
Efficiency	> 98 %
Degree of protection	IP20
Protection class	III
MTBF (IEC 61709, SN 29500)	> 500000 h
Ambient temperature (operation)	-25 °C ... 70 °C (> 60 °C derating)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, no condensation)
Mounting position	horizontal DIN rail NS 35, EN 60715
Assembly instructions	Can be aligned: 5 mm horizontally, 15 mm next to active components, 5 cm vertically
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Low Voltage Directive	Conformance with Low Voltage Directive 2006/95/EC
Standard – Electrical equipment of machines	EN 60204
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
Standard – Safety extra-low voltage	IEC 60950-1 (SELV) and EN 60204 (PELV)
UL approvals	UL/C-UL listed UL 508
	UL/C-UL Recognized UL 60950

Connection data, input

Connection method	Screw connection
-------------------	------------------