

## INSTA CP SNT 24W 12V 1.5A

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com



One-phase switched-mode power unit in installation housing in performance classes 24 and 48 W. .  
 The INSTA power units can be universally deployed because of their wide input range from 85 V AC to 265 V AC.  
 They are available with output voltages from 5 V to 48 V.

### General ordering data

Type	CP SNT 24W 12V 1.5A
Order No.	<a href="#">9928890012</a>
Version	Power supply, switch-mode power supply unit, 12 V
GTIN (EAN)	4032248217533
Qty.	1 pc(s).

**INSTA  
CP SNT 24W 12V 1.5A**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Width	52 mm	Width (inches)	2.047 inch
Height	90.5 mm	Height (inches)	3.563 inch
Depth	62.5 mm	Depth (inches)	2.461 inch
Weight	170.8 g	Net weight	170.8 g

**Temperatures**

Operating temperature	-20 °C...50 °C	Storage temperature	-40 °C...85 °C
-----------------------	----------------	---------------------	----------------

**Input**

Connection system	Screw connection	DC input voltage range	80...370 V DC
Input current	460 mA @ 115 V AC; 250 mA @ 230 V AC	Input current at 115 Vac	460 mA RMS ± 20%
Input current at 125 Vdc	235 mA ± 20%	Input current at 250 Vdc	120 mA ± 20%
Input frequency	50/ 60 Hz	Input fuse	2 A time-lag fuse (internal)
Input voltage (voltage mode input)	85...265 V AC, 120...300 V DC	Overload current protection	Thermistor
Surge protection	Varistor	Wire connection method	Screw connection

**output**

Control at 10...100% load	0.5%	Control at input voltage	0.2%
Mains failure bridge-over time	35 ms @ 115 V AC / 160 ms @ 230 V AC	Max. capacitance at output	8000 µF
Max. residual ripple	< 2 %	Output current	1.5 A
Output power	18 W	Output voltage	12 V
Output voltage type	DC	Overload protection	Surge current / thermal cut-out
Parallel connection option	yes, max 2.	Surge protection	Varistor
Wire connection method	Screw connection		

**General data**

Degree of efficiency at max. load	78%	EMC standards	EN 61000-6 /-2, -3
Mounting position, installation notice	horizontally, on terminal rail TS 35	Operating temperature	-20 °C...50 °C
Protection degree	IP20	Short-circuit protection	Yes
Standards	DIN EN 50178, DIN EN 60950, IEC950	Weight	170.8 g

**Insulation coordination**

electrical isolation, I/O rail	4 kV	electrical isolation, input-earth	1.5 kV
electrical isolation, input-output	3 kV	electrical isolation, output-earth	0.5 kV

**Connection data (input)**

Connection system	Screw connection
-------------------	------------------