

FEATURES

- ITE (2nd Ed.) and Medical (3rd ed.) MOPP safety approved
- 55-65W compact high density
- 2" x 4" standard footprint
- High efficiency up to 90%
- Remote Sense
- Universal AC input
- Low profile - 1U package
- Convection-cooled operation up to 65W
- Complies with 5000m altitude
- RoHS compliant
- Input power < 74W
- UL Class I and II approved
- Less than 0.3W no load input power
- Complies with ErP/Energy Star requirement excluding 5V output

DESCRIPTION

The MVAD065 series switching power supplies utilize advanced component and circuit technologies to deliver high efficiency. Designed for Medical, Telecom, and Industrial applications to satisfy 1U height design considerations, the MVAD065 Series measures only 2.0" x 4.0" x 1.3". All models offer universal AC input and compliance to worldwide safety and EMC standards.

ORDERING GUIDE

Model Number	Natural Convection Cooling	Main Output (V1)
MVAD065-05	55W	5V
MVAD065-12		12V
MVAD065-18	60W	18V
MVAD065-24		24V
MVAD065-48	65W	48V

INPUT CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Operating Range	Single phase	90	120/230	264	Vac
	DC	120		300	Vdc
Input Frequency		47	50/60	63	Hz
Turn-on Input Voltage	Input rising at full load	70		85	Vac
Turn-off Input Voltage	Input falling at full load	70		85	Vac
Input Current	90Vac input, full load			1.4	A
Inrush Current	5V		75		Apk
	Other	At 264Vac, at 25°C cold start	60		


OUTPUT CHARACTERISTICS

Model Number	Main Output Voltage (V1)	Load Current	Load Capacitance	Line, Load, Cross Regulation	Typical Efficiency @230Vac full load
MVAD065-05	5V	0 to 11A	0 to 2200µF	± 2%	84%
MVAD065-12	12V	0 to 5.0A	0 to 1000µF	± 2%	88%
MVAD065-18	18V	0 to 3.34A	0 to 680µF	± 2%	86%
MVAD065-24	24V	0 to 2.71A	0 to 560µF	± 2%	89%
MVAD065-48	48V	0 to 1.36A	0 to 330µF	± 2%	90%

MAIN OUTPUT CHARACTERISTICS

Parameter	Conditions	Min.	Max.		Units
			5V	Other	
Transient Response	50% load step, 1A/µsec slew rate		±5		%
Settling Time to 1% of Nominal			500	200	µsec
Turn On Delay	After application of input power		1		sec
Output Voltage Rise	Monotonic, 0 to 100% load		50		msec
Setpoint Accuracy	120Vac, 40W, 25°C		±1	±0.5	%
Output Holdup	115Vac, 100% load	10			msec
Temperature Coefficient			0.02		%/°C
Ripple Voltage & Noise ¹			2	1	%
Remote Sense ³	Compensates for up to 400mV of lead drop with remote sense connected. Protected against short circuit and reverse connection.		400		mV

1. Ripple and noise are measured with 0.1 µF of ceramic capacitance and 47 µF of electrolytic capacitance on each of the power supply outputs. The output noise requirements apply over a 0 Hz to 20 MHz bandwidth. A short coaxial cable with 50ohm scope termination is used.
2. Unless otherwise specified all readings are taken at 120Vac input and 25°C ambient temperature.
3. 0.4V lead drop is compensated in remote sense.



Available now at <http://power.murata.com/acdc3d>



ENVIRONMENTAL CHARACTERISTICS						
Parameter	Conditions	Min.	Typ.	Max.	Units	
Storage Temperature Range		-40		85	°C	
Operating Temperature Range	See thermal derating curves	-10		70		
	Start up	-20				
Operating Humidity	Non-condensing	10		95	%	
Operating Altitude	For Class I ITE Equipment deployment	-200		5000	m	
	Other	-200		2000		
MTBF	Telcordia SR-332 M1C3 25°C	1M			Hours	
Shock	Operating, IEC60068-2-27, half-sine 5G, 6ms, 3 times per face, 6 faces	Complies				
	Non-operating, IEC60068-2-27, half-sine, 30G, 18ms, 3 times per face, 6 faces	Complies				
Vibration	Operating, IEC60068-2-6, 1.0G, 10-150Hz, 10 minutes per axis, on all 3 axes	Complies				
	Non-operating, IEC60068-2-6, 2.0G, 10-150Hz, 10 minutes per axis, on all 3 axes	Complies				
Safety	IEC60950-1:2005 (2nd Edition); Am1:2009 UL60950-1 2nd Edition,2011-12-19, CSA C22.2 No. 60950-1-07, 2nd Edition,2011-12 EN60950-1:2006 + A11:2009 + A1:2010 + A12:2011 IEC60601-1:2005 + CORR.1(2006) + CORR.2(2007) ANSI/AAMI ES60601-1 (2005+C1:09 + A2:10), CSA-C22.2 No. 60601-1(2008), MOPP CE Marking per LVD					
Warranty	2 years					
Outside Dimensions	2.0" x 4.0" x 1.3" (50.8mm x 101.6mm x 33.02mm)					
Weight	MVAD065-05 / MVAD065-18	0.285lbs (130g) typical				
	Other	0.27lbs (123g) typical				

PROTECTION CHARACTERISTICS						
Parameter	Conditions	Min.	Typ.	Max.	Units	
Overvoltage Protection	MVAD065-05	Latching (50% load)	110		190	%V1
	Other	Latching (60% load)	110		160	
Overcurrent Protection	Hiccup mode		110		160	%A

ISOLATION CHARACTERISTICS						
Parameter	Conditions	Min.	Typ.	Max.	Units	
Isolation	Primary to Earth Ground (1xMOPP)	1500			Vac	
	Primary to Secondary (2xMOPP) ⁴	4000				
	Secondary to Earth Ground	500			Vdc	
Leakage Current (under normal conditions)	240Vac, 60Hz, 25°C			300	µA	
	264Vac, 60Hz, 25°C			350		
Touch Current	264Vac, 60Hz, 25°C			100		

EMISSIONS AND IMMUNITY		
Characteristic	Standard	Compliance
Input Current Harmonics	IEC/EN 61000-3-2	Class A
Voltage Fluctuation and Flicker	IEC/EN 61000-3-3	Complies
Conducted Emissions	EN 55022	Class B, Class A (at Class II equipment)
	FCC Part 15	Class B, Class A (at Class II equipment)
ESD Immunity	IEC/EN 61000-4-2	Level 4, Criterion A
Radiated Field Immunity	IEC/EN 61000-4-3	Level 2, Criterion A
Electrical Fast Transient Immunity	IEC/EN 61000-4-4	Level 3, Criterion A
Surge Immunity	IEC/EN 61000-4-5	Level 4, Criterion A
RF Conducted Immunity	IEC/EN 61000-4-6	Level 2, Criterion A
Magnetic Field Immunity	IEC/EN 61000-4-8	Level 2, Criterion A
Voltage dips, interruptions	IEC/EN 61000-4-11	Level 3, Criterion B

4. At class I equipment.