



SF-0603SP Series - Time Lag Surface Mount Fuses

BOURNS®

Average Time Current Curves



Minimum I²T V Clear Time Curves



Typical Part Marking

Represents total content. Layout may vary.



RATED CURRENT (A)	
F = 0.50	S = 2.00
I = 0.63	T = 2.50
K = 0.80	3 = 3.00
L = 1.00	U = 3.15
M = 1.25	W = 4.00
N = 1.60	Y = 5.00
P = 1.50	<u>6</u> = 6.00

How to Order

SF - 0603 SP 050 - 2

SinglFuse™
 Product Designator
 SMD Footprint
 1608 (EIA 0603) size
 Fuse Blow Type
 SP = Time lag
 Rated Current
 050-600 (500 mA - 6.00 A)
 Packaging Type
 - 2 = Tape & Reel (5,000 pcs./reel)

REV. A 08/17

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

SF-0603SP Series Tape and Reel Specifications

BOURNS®

Tape Dimensions		SF-0603SP Series per EIA 481-2
W		$\frac{8.0 \pm 0.2}{(.315 \pm .008)}$
P ₀		$\frac{4.0 \pm 0.1}{(.157 \pm .004)}$
P ₁		$\frac{4.0 \pm 0.1}{(.157 \pm .004)}$
P ₂		$\frac{2.0 \pm 0.05}{(.079 \pm .002)}$
A		$\frac{1.1 \pm 0.1}{(.043 \pm .004)}$
B		$\frac{1.9 \pm 0.1}{(.075 \pm .004)}$
F		$\frac{3.5 \pm 0.05}{(.138 \pm .002)}$
E		$\frac{1.75 \pm 0.1}{(.069 \pm .004)}$
D ₀		$\frac{1.5 \pm 0.1/-0}{(.059 \pm .004/-0)}$
T		$\frac{0.64 \pm 0.1}{(.025 \pm .004)}$
Reel Dimensions		
A		$\frac{180 \pm 0/-3.0}{(7.087 \pm 0/-1.18)}$
B Min.		$\frac{60.0}{(2.362)}$
C		$\frac{13.0 \pm 1.0}{(.512 \pm .039)}$
W		$\frac{9.0 \pm 1.0}{(.354 \pm .039)}$
T		$\frac{11.4 \pm 2.0}{(.449 \pm .079)}$

