SMD High Current Ceramic Micro Fuse



RoHS Compliant



Use in power tool battery packs

Specification

Current Rating : 50A Voltage Rating : 60V DC

Interrupting Current rating : 300 Amperes at 60V DC

300 amperes at 35V DC

Fuse Body Material : Ceramic

Termination Material : Copper (Cu), Tin (Sn)

Fuse Element : Copper (Cu), Tin (Sn)

Operating Temperature : -55°C to +125°C

Fuse Size : 7.3mm × 5.8mm × 4mm


Electrical Characteristics


ſ	Detina	100% Rating		250% Rating	
L	Rating	Min.	Max.	Min.	Max.
ſ	50A	4hr	-	-	60 sec

Part Number	Ampere Rating (A)	Voltage Rating (V)	Nominal Cold Resistance (Ohms)	Nominal Melting I ² t (A ² sec.)
MP000815	50	60	0.0007	1750

^{*} Measured at ≤10% of rated current at 25°C


Mechanical Dimensions





Dimensions: Millimetres

Recommended Land Pattern



Reflow Solder

Part Number Table

Description	Part Number	
SMD Fuse, 50A, 60V DC	MP000815	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands



^{*} Melting I2t at 1000% of current rating