

- Enclosed power supply with screw terminal connection
- Certification according to IEC/EN/ES 60601-1 3rd edition for 2 x MOPP
- Low leakage current <75 µA rated for BF applications
- Risk management process according to ISO 14971 incl. risk management file
- Acceptance criteria for electronic assemblies acc. to IPC-A-610 Level 3
- EMC compliance to IEC 60601-1-2 ed. 4
- Protection class I and II
- Operating up to 5000 m altitude
- Ready to meet ErP directive, <0.15 W no load power consumption
- 5 year product warranty



ES 60601-1 IEC 60601-1

The TPP 65 Series of 65 Watt AC/DC power supplies feature a reinforced double I/O isolation system according to latest medical safety standards (60601-1 3rd edition, 2 x MOPP). The earth leakage current is below 75 µA what makes the units suitable for BF (body floating) applications.

The excellent efficiency of up to 92% allows a high power density for the standard 2.44" x 3.0" packaging format. The full load operating temperature range is -40°C to +60°C while it goes up to 85°C with 50% load derating (for single output models). The EMC characteristic is dedicated for applications in industrial and domestic fields.

High reliability is provided by use of industrial quality grade components and an excellent thermal management. It makes the products an ideal solution for medical devices and for demanding safety and space critical applications.

Models								
Order Code	Output Power	Output 1		Output 2		Output 3		Efficiency typ.
		Vnom	I _{max}	Vnom	I _{max}	Vnom	I _{max}	
TPP 65-105	50 W	5 VDC	10'000 mA					90 %
TPP 65-112		12 VDC	5'420 mA					93 %
TPP 65-115		15 VDC	4'340 mA					94 %
TPP 65-124		24 VDC	2'710 mA					94 %
TPP 65-221		+12 VDC	5'420 mA	+5 VDC	8'000 mA			90 %
TPP 65-231		+15 VDC	4'340 mA	+5 VDC	8'000 mA			91 %
TPP 65-251		+24 VDC	2'710 mA	+5 VDC	8'000 mA			89 %
TPP 65-321M2		+12 VDC	5'420 mA	+5 VDC	8'000 mA	-12 VDC	600 mA	89 %
TPP 65-331M3		+15 VDC	4'340 mA	+5 VDC	8'000 mA	-15 VDC	600 mA	90 %
TPP 65-3512		+24 VDC	2'710 mA	+5 VDC	8'000 mA	+12 VDC	600 mA	89 %

Note - Total Power must not exceed 65 W.
 - Other output models are available on request.
 - Multi output models have a common ground.

Input Specifications

Input Voltage	- AC Range	85 - 264 VAC (Full Range)
	- DC Range	120 - 370 VDC (designed for, no certification)
Input Frequency		47 - 63 Hz
Input Current	- Full Load & Vin = 230 VAC	950 mA max.
	- Full Load & Vin = 115 VAC	1650 mA max.
Power Consumption	- at no Load	150 mW max. (Ready to meet ErP directive)
Input Inrush Current	- at 230 VAC	60 A max.
Input Protection		T 3.15 A / 250 VAC (Internal Fuse in L & N)

Output Specifications

Output Voltage Adjustment			±10% (by trim potentiometer) (only Output 1) Output power must no exceed rated power!
Voltage Set Accuracy			±1% max. (Output 1) ±2% max. (Output 2 and 3))
Regulation	- Input Variation (Vmin - Vmax)	single output models:	0.2% max.
		dual output models:	0.2% max.
		triple output models:	0.2% max.
	- Load Variation (0 - 100%)	single output models:	0.5% max. 0.7% max. (5 VDC model)
		dual output models:	0.5% max. (Output 1) 1.5% max. (Output 2)
		triple output models:	0.5% max. (Output 1) 1.5% max. (Output 2) 0.7% max. (Output 3)
- Cross Regulation (25% / 100% asym. load)	dual output models:	1.5% max.	
	triple output models:	1.5% max.	
Ripple and Noise (20 MHz Bandwidth)	- single output	5 VDC model:	75 mVp-p typ. (with 10 µF X7R)
		12 VDC model:	75 mVp-p typ. (with 10 µF X7R)
		15 VDC model:	75 mVp-p typ. (with 10 µF X7R)
		24 VDC model:	75 mVp-p typ. (with 1 µF X7R)
	- dual output	12 / 5 VDC model:	120 / 100 mVp-p typ. (with 10 µF X7R)
		15 / 5 VDC model:	150 / 100 mVp-p typ. (with 10 µF X7R)
		24 / 5 VDC model:	240 / 100 mVp-p typ. (with 10 µF X7R)
	- triple output	12 / 5 / -12 VDC model:	120 / 100 / 120 mVp-p typ. (with 10 µF X7R)
		15 / 5 / -15 VDC model:	150 / 100 / 150 mVp-p typ. (with 10 µF X7R)
		24 / 5 / 12 VDC model:	240 / 100 / 120 mVp-p typ. (with 10 µF X7R)
Capacitive Load	- single output	5 VDC model:	20'000 µF max.
		12 VDC model:	4'520 µF max.
		15 VDC model:	2'900 µF max.
		24 VDC model:	1'130 µF max.
	- dual output	12 / 5 VDC model:	2'500 / 3'000 µF max.
		15 / 5 VDC model:	1'200 / 3'000 µF max.
		24 / 5 VDC model:	625 / 3'000 µF max.
	- triple output	12 / 5 / -12 VDC model:	2'500 / 3'000 / 500 µF max.
		15 / 5 / -15 VDC model:	1'200 / 3'000 / 500 µF max.
		24 / 5 / 12 VDC model:	625 / 3'000 / 500 µF max.
Minimum Load			not required 0.5 W for Vout1 and Vout2 if Vout3 = Full Load
Temperature Coefficient			±0.02 %/K
Hold-up Time	- at 115 VAC		16 ms min.
Start-up Time	- at 230 VAC		1'000 ms max.
Output Current Limitation			120 - 160% of Iout max.
Short Circuit Protection			Continuous, automatic recovery
Overvoltage Protection			125 - 140% of Vout nom. (only Output 1)
Transient Response	- Response Deviation		3% max. (50% to 75% Load Step) (Output 1)
	- Response Time		600 µs typ. (50% to 75% Load Step) (Output 1)

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.