


CC06H

High I²t Chip™ 0603 size fuses



Product feature:

- 0603 (1608 metric) compact design utilizes less board space
- Halogen free, lead free and RoHS compliant
- High inrush withstand capability
- Fast-acting performance
- Ampacity alpha mark on fuse for easy identification
- Standard termination design for easy solderability
- Compatible with standard lead-free solder reflow and wave soldering processes
- Excellent environmental integrity

Applications

For secondary circuit protection in space constrained applications:

- LCD Backlight inverters
- Digital cameras
- DVD Players
- Bluetooth headsets
- Battery packs

Agency information

- cURus Recognized Guide and Card JDXY2/JDYX8, File E19180

Packaging

- TR - Packaging code suffix for tape-and-reel (8 mm wide tape on 178mm diameter reel - specification EIA 481-1)
- Quantity = 5000 fuses

Electrical characteristics

Amp Rating	% of Amp Rating	Opening Time
1-8 A	100	4 Hours
1-7 A	200	1-60 Seconds
1-8 A	250	5 Seconds Max

Specifications

Part Number	Amp Rating ⁵	Voltage Rating (Vdc)	Interrupting Rating ^{1,4} (A)	Typical Cold Resistance ² (Ω)	Typical Pre-Arcing ³ (I ² t)	Typical Voltage Drop (mV)	Typical Power Dissipation (W)	Alpha Marking	Agency Information (cURus)
CC06H1A	1	32	50	0.25	0.02	310	0.32	B	x
CC06H1.5A	1.5	32	50	0.13	0.07	250	0.38	H	x
CC06H2A	2	32	50	0.068	0.14	170	0.38	K	x
CC06H2.5A	2.5	32	50	0.05	0.25	155	0.38	L	x
CC06H3A	3	32	50	0.035	0.30	130	0.38	O	x
CC06H3.5A	3.5	32	50	0.023	0.50	100	0.35	R	x
CC06H4A	4	32	50	0.02	0.8	110	0.45	S	x
CC06H5A	5	32	50	0.013	1.6	95	0.48	T	x
CC06H6A	6	32	50	0.0076	2.6	80	0.48	V	x
CC06H7A	7	32	50	0.0056	3.3	80	0.56	X	x
CC06H8A	8	32/24	50/80	0.0040	4.5	75	0.60	Z	x

- DC Interrupting Rating (measured at rated voltage, time constant of less than 50 microseconds, battery source).
- DC Cold Resistance are measured at <10% of rated current in ambient temperature of 20 °C -
FOR REFERENCE ONLY - CONTROLLED VALUES HELD BY PLANT AND SUBJECT TO CHANGE WITHOUT NOTICE.
- Typical Pre-arcing I²t are measured at rated DC voltage, 10I_n current (not to exceed interrupting rating).
- The insulation resistance after breaking capacity test is higher than 0.1 MΩ when measured by 2X rated voltage.
- Device designed to carry rated current for 4 hours minimum. An operating current 80% or less of rated current is recommended, with further design derating required at elevated ambient temperature. See Temperature Derating Curve on next page.