

## Intelligent Power Module ( R-Series )


### Maximum Ratings and Characteristics

#### Absolute Maximum Ratings ( T<sub>c</sub>=25°C )

Items	Symbols	Ratings		Units	
		Min.	Max.		
DC Bus Voltage	V <sub>DC</sub>	0	900	V	
DC Bus Voltage (surge)	V <sub>DC(Surge)</sub>	0	1000		
DC Bus Voltage (short operating)	V <sub>SC</sub>	200	800		
Collector-Emitter Voltage	V <sub>CES</sub>	0	1200		
Inverter	Continuous	I <sub>C</sub>	75	A	
		1ms	I <sub>CP</sub>		150
		Duty=62.6%	-I <sub>C</sub>		75
Collector Power Dissipation <small>One Transistor</small>	P <sub>C</sub>		595	W	
Voltage of Power Supply for Driver	V <sub>CC</sub>	0	20	V	
Input Signal Voltage	V <sub>IN</sub>	0	V <sub>Z</sub>	V	
Input Signal Current	I <sub>IN</sub>		1	mA	
Alarm Signal Voltage	V <sub>ALM</sub>	0	V <sub>CC</sub>	V	
Alarm Signal Current	I <sub>ALM</sub>		15	mA	
Junction Temperature	T <sub>J</sub>		150	°C	
Operating Temperature	T <sub>OP</sub>	-20	100		
Storage Temperature	T <sub>stg</sub>	-40	125		
Isolation Voltage	A.C. 1min.	V <sub>iso</sub>	2500	V	
Screw Torque	Mounting *1		3.5	Nm	
	Terminals *1		3.5		

Note: \*1: Recommendable Value: 2.5 - 3.0 Nm (M5)

### Outline Drawing



#### Electrical Characteristics of Power Circuit ( at T<sub>J</sub>=25°C, V<sub>CC</sub>=15V )

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
INV	Collector Current At Off Signal Input	I <sub>CES</sub>	V <sub>CE</sub> =1200V, Input Terminal Open		1.0	mA
	Collector-Emitter Saturation Voltage	V <sub>CE(Sat)</sub>	I <sub>C</sub> =75A		2.6	V
	Forward Voltage of FWD	V <sub>F</sub>	-I <sub>C</sub> =75A		3.0	V

#### Electrical Characteristics of Control Circuit ( at T<sub>J</sub>=25°C, V<sub>CC</sub>=15V )

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
Current of P-Line Side Driver (One Unit)	I <sub>CCP</sub>	f <sub>SW</sub> =0~15kHz, T <sub>C</sub> =-20~100°C	3		18	mA
Current of N-Line Side Driver (Three Units)	I <sub>CCN</sub>	f <sub>SW</sub> =0~15kHz, T <sub>C</sub> =-20~100°C	10		65	
Input Signal Threshold Voltage	V <sub>IN(th)</sub>	On	1.00	1.35	1.70	V
		Off	1.25	1.60	1.95	
Input Zener Voltage	V <sub>Z</sub>	R <sub>IN</sub> =20kΩ		8.0		
Over Heating Protection Temperature Level	T <sub>COH</sub>	V <sub>DC</sub> =0V, I <sub>C</sub> =0A, Case Temp.	110		125	°C
Hysteresis	T <sub>CH</sub>			20		
IGBT Chips Over Heating Protec. Temp. Level	T <sub>JOH</sub>	Surface Of IGBT Chip	150			
Hysteresis	T <sub>IH</sub>			20		
Inverter Collector Current Protection Level	I <sub>OC</sub>	T <sub>J</sub> =125°C	113			A
Over Current Detecting Time	t <sub>DOC</sub>	T <sub>J</sub> =25°C		10		μs
Alarm Signal Hold Time	t <sub>ALM</sub>		1.5	2		ms
Limiting Resistor for Alarm	R <sub>ALM</sub>		1425	1500	1575	Ω
Under Voltage Protection Level	V <sub>UV</sub>		11.0		12.5	V
Hysteresis	V <sub>H</sub>		0.2			


#### Dynamic Characteristics ( at T<sub>C</sub>=T<sub>J</sub>=125°C, V<sub>CC</sub>=15V )

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
Switching Time	t <sub>ON</sub>	I <sub>C</sub> =50A, V <sub>DC</sub> =600V	0.3			μs
	t <sub>OFF</sub>				3.6	
	t <sub>RR</sub>	I <sub>F</sub> =50A, V <sub>DC</sub> =600V			0.4	

#### Thermal Characteristics

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	R <sub>th(i-c)</sub>	Inverter IGBT			0.21	°C/W
	R <sub>th(i-c)</sub>	Diode			0.47	
	R <sub>th(c-f)</sub>	With Thermal Compound		0.05		

## ■ Equivalent Circuit




### Drivers include following functions


- Short circuit protection circuit
- Amplifier for driver
- Undervoltage protection circuit
- Overcurrent protection circuit
- IGBT Chip overheating protection

## Control Circuit


Power Supply Current vs. Switching Frequency




Input Signal Threshold Voltage vs. Power Supply Voltage




Under Voltage vs. Junction Temperature




Under Voltage Hysteresis vs. Junction Temperature



Alarm Hold Time vs. Power Supply Voltage




Over Heating Characteristics




## ■ Inverter


Collector Current vs. Collector-Emitter Voltage




Collector Current vs. Collector-Emitter Voltage




Switching Time vs. Collector Current




Switching Time vs. Collector Current



Forward Voltage vs. Forward Current




Switching Loss vs. Collector Current




■ Inverter


Transient Thermal Resistance




Reverse Biased Safe Operating Area



Power Derating For IGBT  
(per device)




Power Derating For FWD  
(per device)




Switching Loss vs. Collector Current

$V_{DC}=600\text{V}$ ,  $V_{CC}=15\text{V}$ ,  $T_j=25^{\circ}\text{C}$




Switching Loss vs. Collector Current


$V_{DC}=300\text{V}$ ,  $V_{CC}=15\text{V}$ ,  $T_j=125^{\circ}\text{C}$



## ■ Inverter



## ■ Outline Drawing



**Weight: 440g**