



Dimensions


MS132 ≤ 10 A




MS132 > 10 A




MS132 ≤ 10 A + screw fixing kit



MS132 > 10 A + screw fixing kit



Wiring diagram



Approvals



Markings



Data at $T_A = 40\text{ °C}$ and at rated values, if nothing else indicated

Type			MS132
Technical data		Terminals	
Main circuit		1L1-3L3-5L5 2T1-4T2-6T3	
Rated operational voltage U_e acc. to IEC/EN 60947-1	a.c. d.c.		690 V -
Rated operational current I_e			see separate table
Rated current I_n /			see „Rated Operational Current“
Conventional free-air thermal current I_{th}			
Setting range - thermal overload protection			see ordering data
Rated instantaneous short-circuit current setting I_{cs}			see separate table
Rated service short-circuit breaking capacity I_{cs}			see separate table
Rated ultimate short-circuit breaking capacity I_{cu}			see separate table
Trip class acc. to IEC/EN 60947-4-1			see ordering data
Rated frequency acc. to IEC/EN 60947-1			50 / 60 Hz
Number of poles			3
Resistance per phase			see separate table
Power loss per phase	lower value of setting range upper value of setting range		see separate table see separate table
Isolation data			
Rated impulse withstand voltage U_{imp} acc. to IEC/EN 60947-1			6 kV
Rated insulation voltage U_i acc. to IEC/EN 60947-1			690 V
Pollution degree acc. to IEC/EN 60664			3
Electrical connection			
MS132 ≤ 10A			
Connecting capacity	solid flexible with ferrule flexible with ferrule isolated flexible without ferrule		1/2 x 1 ... 4 mm ² 1/2 x 0.75 ... 2.5 mm ² 1/2 x 0.75 ... 2.5 mm ² 1/2 x 0.75 ... 2.5 mm ²
Stripping length			9 mm
Tightening torque			0.8 ... 1.2 Nm
Connection screw			M3.5 (Pozidrive 2)
MS132-12, -16			
Connecting capacity	solid flexible with ferrule flexible with ferrule isolated flexible without ferrule		1/2 x 1 ... 4 mm ² 1/2 x 0.75 ... 2.5 mm ² 1/2 x 0.75 ... 2.5 mm ² 1/2 x 0.75 ... 2.5 mm ²
Stripping length			10 mm
Tightening torque			1.5 Nm
Connection screw			M4 (Pozidrive 2)
MS132-20, -25, -32			
Connecting capacity	solid flexible with ferrule flexible with ferrule isolated flexible without ferrule		1/2 x 2.5 ... 6 mm ² 1/2 x 1 ... 6 mm ² 1/2 x 1 ... 6 mm ² 1/2 x 2.5 ... 6 mm ²
Stripping length			10 mm
Tightening torque			2 Nm
Connection screw			M4 (Pozidrive 2)