

New FC-335

35 Amps switching in a 1.5 inch cube enclosure

- Non-latching, hermetically sealed, all welded construction
- Designed and built in accordance to MIL-PRF-6106
- Solder hook or terminal block configurations
- 3PST/NO (DM) contact configuration
- 28VDC and 115VAC coils available
- Corrosion protected metal case
- Rated at 25A for Double Voltage 230VAC!
- Drop-in replacement for the Leach 9324 or MS27418 with 40% increase in contact rating!



Load Type	Life (Min.) Cycles	Contact Rating	
		115Vac, 3 phase, 50 to 400 Hz	230VAC, 400Hz
Resistive	50,000	35A	25A

Weight: 0.452 LBS

1.5" x 1.5" Base
Dimension

*all ratings are preliminary

TE Connectivity Confidential & Proprietary. Do not reproduce or distribute.



SERIES FC-335
RELAY NON-LATCHING
3PST/NO (DM)
35A/28Vdc, 115 Vac – 50/60Hz, 400Hz

PRODUCT FACTS:

- Non-latching Hermetically Sealed Relay.
- Corrosion protected metal can.
- All welded construction.
- 28 Vdc & 115 Vac coils available.
- Weight 0.5 lbs Max.
(227 Grams Max).
- Designed and built in accordance to MIL- PRF-6106.
- 3-Pole 35A Contacts (Form X),
Switching in 1.5 inch³.
- Main contacts are suitable for use in 360-800 Hz variable frequency applications.



Dimensions shown for reference
 Only. Specifications subject to
 change.

PRODUCT DATA SHEET

29-Nov-2017 Rev

PH. 828-338-1087 FAX 828-338-1103
 1396 CHARLOTTE HIGHWAY, FAIRVIEW, NC 28730

SERIES FC-335

CAGE CODE

SCALE

NONE

SHEET

1 of 6