



MSP300

Pressure Transducer

SPECIFICATIONS

- ◆ **Analog Output or 14-Bit Digital Pressure with 11-Bit Temperature Output**
- ◆ **One Piece Stainless Steel Construction**
- ◆ **Low Cost**
- ◆ **17-4PH or 316L Stainless Steel**
- ◆ **Customizable**

The MSP300 pressure transducer from the Microfused line of TE is suitable for measurement of liquid or gas pressure, even for difficult media such as contaminated water, steam, and mildly corrosive fluids.

The transducer pressure cavity is machined from a solid piece of 17-4PH or 316L stainless steel. The standard version includes a 1/4 NPT pipe thread allowing a leak-proof, all metal sealed system. With excellent durability, there are no o-rings, welds or organics exposed to the pressure media.

TE's proprietary Microfused technology, derived from demanding aerospace applications, employs micromachined silicon piezoresistive strain gages fused with high temperature glass to a stainless steel diaphragm. This approach achieves media compatibility simply and elegantly while providing an exceptionally stable sensor without the PN junctions of conventional micromachined sensors.

This product is geared towards industrial and commercial OEMs for small to high volume applications. Standard configurations are suitable for many applications. Please contact factory for your customization needs.

FEATURES

- ◆ **One Piece Stainless Steel Construction**
- ◆ **Ranges up to 15kpsi**
- ◆ **Digital Pressure and Temperature Output or Analog mV/Amplified Output**
- ◆ **±1 %Span Accuracy**
- ◆ **UL Certification (analog only)**

APPLICATIONS

- ◆ **Pumps and Compressors**
- ◆ **Hydraulic/Pneumatic Systems**
- ◆ **Automotive Test Systems**
- ◆ **Energy and Water Management**
- ◆ **Medical Gas Pressure**
- ◆ **Leak Detection**
- ◆ **Remote Measuring Systems**
- ◆ **General Pressure Measurements**

STANDARD RANGES (ALL INTERMEDIATE RANGES ARE STANDARD)

Range (psi)	Range (Bar)	Gage/Compound
0 to 100	0 to 007	*
0 to 200	0 to 010	*
0 to 300	0 to 020	*
0 to 500	0 to 035	*
0 to 01k	0 to 070	*
0 to 03k	0 to 200	*
0 to 05k	0 to 350	*
0 to 10k	0 to 700	*
0 to 15k	0 to 01k	*

PERFORMANCE SPECIFICATIONS (ANALOG)

Supply Voltage: 5.0V, Ambient Temperature: 25°C (unless otherwise specified)

PARAMETERS	MIN	TYP	MAX	UNITS	NOTES
Pressure Accuracy (RSS combined Non Linearity, Hysteresis & Repeatability)	-1		1	%Span	BFSL @ 25°C
Pressure Cycles	1.00E+6			0~F.S. Cycles	
Proof Pressure	2X			Rated	
Burst Pressure	5X			Rated	
Isolation, Body to Any Lead	50			MΩ	@ 250Vdc
Long Term Stability (1 year)	-0.25		0.25	%Span	
Zero Thermal Error	-2.0		2.0	%Span	Over comp. temp
Span Thermal Error	-2.0		2.0	%Span	Over comp. temp
Zero Offset (mV Output)	-3.0		3.0	%Span	@ 25°C
Zero Offset (V Output)	-2.0		2.0	%Span	@ 25°C
Span Tolerance	-2.0		2.0	%Span	@ 25°C
Compensated Temperature	0		55	°C	
Operating Temperature	-20		+85	°C	
Storage Temperature	-40		+85	°C	
Load Resistance (R _L , mV Output)	1			MΩ	
Load Resistance (R _L , V Output)	5			KΩ	
Response Time		1		ms	
Bandwidth	DC to 1KHz (typical)				
Shock	50g, 11 msec Half Sine Shock per MIL-STD-202G, Method 213B, Condition A				
Vibration	±20g, MIL-STD-810C, Procedure 514.2-2, Curve L				
Wetted Material (except elastomer seal)	17-4PH or 316L Stainless Steel				

For custom configurations, consult factory.