

## Ratings and Specifications

### Ratings

#### Standard Models with Built-in Operation Indicators

##### Operating Coil, Single-pole and Double-pole Models

| Item | Rated voltage (V) | Rated current (mA) |         | Coil resistance (Ω) | Coil inductance (H) |             | Must-operate voltage (V) | Must-release voltage (V) | Maximum voltage (V)   | Power consumption (VA, W)     |
|------|-------------------|--------------------|---------|---------------------|---------------------|-------------|--------------------------|--------------------------|-----------------------|-------------------------------|
|      |                   | 50 Hz              | 60Hz    |                     | Armature OFF        | Armature ON |                          |                          |                       |                               |
| AC   | 12                | 106.5              | 91      | 46                  | 0.17                | 0.33        | 80% max.*1               | 30% min.*2               | 110% of rated voltage | Approx. 1.0 to 1.2 (at 60 Hz) |
|      | 24                | 53.8               | 46      | 180                 | 0.69                | 1.3         |                          |                          |                       |                               |
|      | 50                | 25.7               | 22      | 788                 | 3.22                | 5.66        |                          |                          |                       |                               |
|      | 100/110           | 11.7/12.9          | 10/11   | 3,750               | 14.54               | 24.6        |                          |                          |                       | Approx. 0.9 to 1.1 (at 60 Hz) |
|      | 110/120           | 9.9/10.8           | 8.4/9.2 | 4,430               | 19.2                | 32.1        |                          |                          |                       |                               |
|      | 200/220           | 6.2/6.8            | 5.3/5.8 | 12,950              | 54.75               | 94.07       |                          |                          |                       |                               |
|      | 220/240           | 4.8/5.3            | 4.2/4.6 | 18,790              | 83.5                | 136.4       |                          |                          |                       |                               |
| DC   | 6                 | 150                |         | 40                  | 0.16                | 0.33        | 80% max.*1               | 10% min.*2               | 110% of rated voltage | Approx. 0.9                   |
|      | 12                | 75                 |         | 160                 | 0.73                | 1.37        |                          |                          |                       |                               |
|      | 24                | 36.9               |         | 650                 | 3.2                 | 5.72        |                          |                          |                       |                               |
|      | 48                | 18.5               |         | 2,600               | 10.6                | 21.0        |                          |                          |                       |                               |
|      | 100/110           | 9.1/10             |         | 11,000              | 45.6                | 86.2        |                          |                          |                       |                               |

#### 3 poles

| Item | Rated voltage (V) | Rated current (mA) |           | Coil resistance (Ω) | Coil inductance (H) |             | Must-operate voltage (V) | Must-release voltage (V) | Maximum voltage (V)   | Power consumption (VA, W)     |
|------|-------------------|--------------------|-----------|---------------------|---------------------|-------------|--------------------------|--------------------------|-----------------------|-------------------------------|
|      |                   | 50 Hz              | 60Hz      |                     | Armature OFF        | Armature ON |                          |                          |                       |                               |
| AC   | 12                | 159                | 134       | 24                  | 0.12                | 0.21        | 80% max.*1               | 30% min.*2               | 110% of rated voltage | Approx. 1.6 to 2.0 (at 60 Hz) |
|      | 24                | 80                 | 67        | 100                 | 0.44                | 0.79        |                          |                          |                       |                               |
|      | 100/110           | 14.1/16            | 12.4/13.7 | 2,300               | 10.5                | 18.5        |                          |                          |                       |                               |
|      | 200/220           | 9.0/10.0           | 7.7/8.5   | 8,650               | 34.8                | 59.5        |                          |                          |                       |                               |
| DC   | 12                | 112                |           | 107                 | 0.45                | 0.98        | 80% max.*1               | 10% min.*2               | 110% of rated voltage | Approx. 1.4                   |
|      | 24                | 58.6               |           | 410                 | 1.89                | 3.87        |                          |                          |                       |                               |
|      | 48                | 28.2               |           | 1,700               | 8.53                | 13.9        |                          |                          |                       |                               |
|      | 100/110           | 12.7/13            |           | 8,500               | 29.6                | 54.3        |                          |                          |                       |                               |

#### 4 poles

| Item | Rated voltage (V) | Rated current (mA) |          | Coil resistance (Ω) | Coil inductance (H) |             | Must-operate voltage (V) | Must-release voltage (V) | Maximum voltage (V)   | Power consumption (VA, W)      |
|------|-------------------|--------------------|----------|---------------------|---------------------|-------------|--------------------------|--------------------------|-----------------------|--------------------------------|
|      |                   | 50 Hz              | 60Hz     |                     | Armature OFF        | Armature ON |                          |                          |                       |                                |
| AC   | 12                | 199                | 170      | 20                  | 0.1                 | 0.17        | 80% max.*1               | 30% min.*2               | 110% of rated voltage | Approx. 1.95 to 2.5 (at 60 Hz) |
|      | 24                | 93.6               | 80       | 78                  | 0.38                | 0.67        |                          |                          |                       |                                |
|      | 100/110           | 22.5/25.5          | 19/21.8  | 1,800               | 10.5                | 17.3        |                          |                          |                       |                                |
|      | 200/220           | 11.5/13.1          | 9.8/11.2 | 6,700               | 33.1                | 57.9        |                          |                          |                       |                                |
| DC   | 12                | 120                |          | 100                 | 0.39                | 0.84        | 80% max.*1               | 10% min.*2               | 110% of rated voltage | Approx. 1.5                    |
|      | 24                | 69                 |          | 350                 | 1.41                | 2.91        |                          |                          |                       |                                |
|      | 48                | 30                 |          | 1,600               | 6.39                | 13.6        |                          |                          |                       |                                |
|      | 100/110           | 15/15.9            |          | 6,900               | 32.0                | 63.7        |                          |                          |                       |                                |

**Note:** 1. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/–20% for the AC rated current and ±15% for the DC coil resistance.

2. The AC coil resistance and inductance values are reference values only. (at 60 Hz).

3. Operating characteristics were measured at a coil temperature of 23°C.

4. The maximum voltage capacity was measured at an ambient temperature of 23°C.

\*1. There is variation between products, but actual values are 80% max.

To ensure operation, apply at least 80% of the rated value (at a coil temperature of +23° C).

\*2. The actual values are 30% min. for AC and 10% min. for DC. To ensure release, use a value that is lower than the specified value.

Refer to **List of Certified Models** for a list of models that are certified for safety standards and the Electrical Appliances and Material Safety Act.

| Classification          |                                   | 1 pole                           |                                             | Double-, 3-, and 4-pole models    |                                             | Bifurcated contacts             |                                             |
|-------------------------|-----------------------------------|----------------------------------|---------------------------------------------|-----------------------------------|---------------------------------------------|---------------------------------|---------------------------------------------|
| Item                    | Load                              | Resistive load                   | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) | Resistive load                    | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) | Resistive load                  | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) |
| Contact type            | Single                            |                                  |                                             |                                   |                                             | Bifurcated                      |                                             |
| Contact materials       | Ag alloy                          |                                  |                                             |                                   |                                             | Ag                              |                                             |
| Rated load              | 15 A at 110 VAC<br>15 A at 24 VDC | 10 A at 110 VAC<br>7 A at 24 VDC | 10 A at 110 VAC<br>10 A at 24 VDC           | 7.5 A at 110 VAC<br>5 A at 24 VDC | 5 A at 110 VAC<br>5 A at 24 VDC             | 4 A at 110 VAC<br>4 A at 24 VDC |                                             |
| Rated carry current     | 15 A                              |                                  | 10 A                                        |                                   | 7 A                                         |                                 |                                             |
| Maximum contact voltage | 250 VAC<br>125 VDC                |                                  | 250 VAC<br>125 VDC                          |                                   | 250 VAC<br>125 VDC                          |                                 |                                             |
| Maximum contact current | 15 A                              | 15 A                             | 10 A                                        | 10 A                              | 7 A                                         | 7 A                             |                                             |

| Item                          | Type | Single-pole and double-pole models<br>(standard models and bifurcated contact models) | Single-pole, double-pole models<br>(models with built-in operation indicators, models with built-in diodes, and models with built-in CR circuits),<br>3-pole and 4-pole models |
|-------------------------------|------|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient operating temperature |      | -25 to 55°C<br>(with no icing or condensation)*1                                      | -25 to +40°C<br>(with no icing or condensation)*2                                                                                                                              |
| Ambient operating humidity    |      | 5% to 85%                                                                             |                                                                                                                                                                                |

**Note:**

- Some models in the LY1 and LY2 Series have an upper temperature limit of +40°C. This limitation is due to the diode junction temperature and the elements used.
- Refer to the ambient temperature and contact carry current characteristics data on page 5 to 7 for information on operation in temperature conditions that are not described here.
- When you apply a minimum of 10 A of current to an LY1 when it is used in combination with a PTF08A, PTF08A-E, or PT08, connect each of the following terminal pairs: (1) to (2), (3) to (4), and (5) to (6).

\*1. If the carry current is 4 A or less, the usable ambient temperature range is -25 to 70°C.

\*2. If the flowing current is 4 A or less, the usable ambient temperature range is -25 to 55°C.

## Characteristics

| Item                                     | Type                                   | Standard models, models with built-in operation indicators, models with built-in CR circuits, and models with built-in diodes       | Bifurcated contacts                                                                      |
|------------------------------------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Contact resistance*1                     |                                        | 50 mΩ max.                                                                                                                          |                                                                                          |
| Operating time*2                         |                                        | 25 ms max.                                                                                                                          |                                                                                          |
| Release time*2                           |                                        | 25 ms max.                                                                                                                          |                                                                                          |
| Maximum operating frequency              | Mechanical                             | 18,000 operations/h                                                                                                                 |                                                                                          |
|                                          | Rated load                             | 1,800 operations/h                                                                                                                  |                                                                                          |
| Insulation resistance*3                  |                                        | 100 MΩ min.                                                                                                                         |                                                                                          |
| Dielectric strength                      | Between coil and contacts              | 2,000 VAC at 50/60 Hz for 1 min.                                                                                                    |                                                                                          |
|                                          | Between contacts of different polarity |                                                                                                                                     |                                                                                          |
|                                          | Between contacts of the same polarity  | 1,000 VAC at 50/60 Hz for 1 min.                                                                                                    |                                                                                          |
| Vibration resistance                     | Destruction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)                                                                |                                                                                          |
|                                          | Malfunction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)                                                                |                                                                                          |
| Shock resistance                         | Destruction                            | 1,000 m/s <sup>2</sup>                                                                                                              |                                                                                          |
|                                          | Malfunction                            | 200 m/s <sup>2</sup>                                                                                                                |                                                                                          |
| Endurance                                | Mechanical                             | AC: 50,000,000 operations min.<br>DC: 100,000,000 operations min.<br>(switching frequency: 18,000 operations/h)                     |                                                                                          |
|                                          | Electrical*4                           | 1-, 3-, 4-pole: 200,000 operations min.<br>2-pole: 500,000 operations min.<br>(rated load, operating frequency: 1,800 operations/h) | 2-pole: 500,000 operations min.<br>(rated load, operating frequency: 1,800 operations/h) |
| Failure rate P value (reference value)*5 |                                        | 100 mA at 5 VDC                                                                                                                     | 10mA at 5 VDC                                                                            |
| Weight                                   |                                        | 1-pole and 2-pole: 40 g, 3-pole: Approx. 50 g, 4-pole: Approx. 70 g                                                                 |                                                                                          |

**Note:** The values at the left are initial values.

\*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method

\*2. Measurement conditions: With rated operating power applied, not including contact bounce.  
Ambient temperature condition: 23°C

\*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.  
Ambient temperature condition: 23°C

\*4. This value was measured at a switching frequency of 120 operations per minute.

\*5. This value was measured at a switching frequency of 120 operations per minute.

## Endurance Under Real Loads (Reference Only)

| Load type            | Item | LY1, 100 VAC                                                           |                           |                                           | LY2, 100 VAC                                                           |                           |                                           | LY4, 100 VAC                                                            |                           |                                           |
|----------------------|------|------------------------------------------------------------------------|---------------------------|-------------------------------------------|------------------------------------------------------------------------|---------------------------|-------------------------------------------|-------------------------------------------------------------------------|---------------------------|-------------------------------------------|
|                      |      | Conditions                                                             | Operating frequency       | Electrical life (×10,000 operations min.) | Conditions                                                             | Operating frequency       | Electrical life (×10,000 operations min.) | Conditions                                                              | Operating frequency       | Electrical life (×10,000 operations min.) |
| AC motor             |      | 400 W, 100 VAC single-phase with 35-A inrush current, 7-A current flow | ON for 10 s, OFF for 50 s | 5                                         | 200 W, 100 VAC single-phase with 25-A inrush current, 5-A current flow | ON for 10 s, OFF for 50 s | 20                                        | 200 W, 200 VAC three-phase with 5-A inrush current, 1-A current flow    | ON for 10 s, OFF for 50 s | 50                                        |
|                      |      |                                                                        |                           |                                           |                                                                        |                           |                                           | 750 W, 200 VAC three-phase with 18-A inrush current, 3.5-A current flow |                           | 7                                         |
| AC lamp              |      | 300 W, 100 VAC with 51-A inrush current, 3-A current flow              | ON for 5 s, OFF for 55 s  | 10                                        | 300 W, 100 VAC with 51-A inrush current, 3-A current flow              | ON for 5 s, OFF for 55 s  | 8                                         | 300 W, 100 VAC with 51-A inrush current, 3-A current flow               | ON for 5 s, OFF for 55 s  | 5                                         |
|                      |      | 500 W, 100 VAC with 78-A inrush current, 5-A current flow              |                           | 2.5                                       |                                                                        |                           |                                           |                                                                         |                           |                                           |
| Capacitor (2,000 μF) |      | 24 VDC with 50-A inrush current, 1-A current flow                      | ON for 1 s, OFF for 6 s   | 10                                        | 24 VDC with 50-A inrush current, 1-A current flow                      | ON for 1 s, OFF for 15 s  | 1                                         | 24 VDC with 50-A inrush current, 1-A current flow                       | ON for 1 s, OFF for 15 s  | 0.5                                       |
|                      |      |                                                                        |                           |                                           | 24 VDC with 20-A inrush current, 1-A current flow                      |                           | 15                                        | 24 VDC with 20-A inrush current, 1-A current flow                       |                           | 20                                        |
| AC solenoid          |      | 50 VA with 2.5-A inrush current, 0.25-A current flow                   | ON for 1 s, OFF for 2 s   | 150                                       | 50 VA with 2.5-A inrush current, 0.25-A current flow                   | ON for 1 s, OFF for 2 s   | 100                                       | 50 VA with 2.5-A inrush current, 0.25-A current flow                    | ON for 1 s, OFF for 2 s   | 100                                       |
|                      |      | 100 VA with 5-A inrush current, 0.5-A current flow                     |                           | 80                                        | 100 VA with 5-A inrush current, 0.5-A current flow                     |                           | 50                                        | 100 VA with 5-A inrush current, 0.5-A current flow                      |                           | 50                                        |