


■ Housing material: Metal (Nickel plated brass)

Note: Shaded models are normally stocked.

Sensing method			Appearance	Connection method	Sensing distance	Model			
						PNP output	NPN output		
Through-beam	Multi purpose		 axial	pre-wired	7 m	E3F2-7B4-M	E3F2-7C4-M		
				M12 connector		E3F2-7B4-M1-M	E3F2-7C4-M1-M		
	- precision detection - test input			pre-wired	10 m	E3F2-10B4-M	E3F2-10C4-M		
				M12 connector		E3F2-10B4-M1-M	E3F2-10C4-M1-M		
Retro-reflective (incl. reflector E39-R1)	Polarizing (with MSR function)	Fixed sensitivity	 axial	pre-wired	0.1 - 2 m ^(*)	E3F2-R2RB4-M	E3F2-R2RC4-M		
				M12 connector		E3F2-R2RB4-M1-M	E3F2-R2RC4-M1-M		
				pre-wired	0.1 - 4 m ^(*)	E3F2-R4B4F-M	E3F2-R4C4F-M		
				M12 connector		E3F2-R4B4F-M1-M	E3F2-R4C4F-M1-M		
		Adjustable sensitivity		pre-wired		E3F2-R4B4-M	E3F2-R4C4-M		
				M12 connector		E3F2-R4B4-M1-M	E3F2-R4C4-M1-M		
	Polarizing (with MSR function)		 radial	pre-wired	0.1 - 2 m ^(*)	E3F2-R2RB41-M	E3F2-R2RC41-M		
Diffuse reflective	Fixed sensing distance		 axial	pre-wired	0.1 m	E3F2-DS10B4-M	E3F2-DS10C4-M		
	Wide-beam characteristics			M12 connector		E3F2-DS10B4-M1-M	E3F2-DS10C4-M1-M		
	Adjustable sensing distance			pre-wired	0.3 m	E3F2-DS30B4-M	E3F2-DS30C4-M		
				M12 connector		E3F2-DS30B4-M1-M	E3F2-DS30C4-M1-M		
	Adjustable sensing distance		 radial	pre-wired	1 m	E3F2-D1B4-M	E3F2-D1C4-M		
				M12 connector		E3F2-D1B4-M1-M	E3F2-D1C4-M1-M		
							0.3 m	E3F2-DS30B41-M	E3F2-DS30C41-M
Background suppression	Fixed sensing distance		 axial	pre-wired	10 cm	E3F2-LS10B4-M	E3F2-LS10C4-M		
				M12 connector		E3F2-LS10B4-M1-M	E3F2-LS10C4-M1-M		




*1) with reflector E39-R1

*2) with reflector E39-R1S

Note: Standard cable length is 2 m. Models provided with a 5 m long cable are available. When ordering, specify the cable length by adding the length of the cable (e.g. E3F2-R2RB4 2M or E3F2-R2RB4 5M). For other cable length please contact your OMRON sales representative.

■ Housing material: Metal (Stainless steel)

Note: Shaded models are normally stocked.



Sensing method		Appearance	Connection method	Sensing distance	Model	
					PNP output	NPN output
Through-beam		 axial	pre-wired	7 m	E3F2-7B4-S	E3F2-7C4-S
			M12 connector		E3F2-7B4-M1-S	E3F2-7C4-M1-S
Retro-reflective (incl. reflector E39-R1)	Polarizing (with MSR function)	 axial	pre-wired	0.1 - 2 m (with reflector E39-R1)	E3F2-R2RB4-S	E3F2-R2RC4-S
			M12 connector		E3F2-R2RB4-M1-S	E3F2-R2RC4-M1-S
Diffuse reflective	Fixed sensitivity Wide-beam characteristics	 axial	pre-wired	0.1 m	E3F2-DS10B4-S	E3F2-DS10C4-S
			M12 connector		E3F2-DS10B4-M1-S	E3F2-DS10C4-M1-S
	Adjustable sensitivity		pre-wired	0.3 m	E3F2-DS30B4-S	E3F2-DS30C4-S
			M12 connector		E3F2-DS30B4-M1-S	E3F2-DS30C4-M1-S

Note: Standard cable length is 2 m. Models provided with a 5 m long cable are available. When ordering, specify the cable length by adding the length of the cable (e.g. E3F2-R2RB4-S 2M or E3F2-R2RB4-S 5M). For other cable length please contact your OMRON sales representative.

■ AC-Switching Models

Housing material: Plastic

Note: Shaded models are normally stocked.

Sensing method		Appearance	Connection method	Sensing distance	Model	
					Light-ON	Dark-ON
Through-beam		 axial	pre-wired	3 m	E3F2-3Z1	E3F2-3Z2
Retro-reflective (incl. reflector E39-R1)	Non-polarizing (without MSR function)	 axial	pre-wired	0.1 - 2 m (with reflector E39-R1)	E3F2-R2Z1	E3F2-R2Z2
Diffuse reflective	Fixed sensing distance Wide-beam characteristics	 axial	pre-wired	0.1 m	E3F2-DS10Z1-N	E3F2-DS10Z2-N

Note: Standard cable length is 2 m. Models provided with a 5 m long cable are available. When ordering, specify the cable length by adding the length of the cable (e.g. E3F2-R2Z1 2M or E3F2-R2Z1 5M). For other cable length please contact your OMRON sales representative.