



Engineering Data (Reference Value)


Sensing Position Characteristics



Sensing Position Characteristics



Repeated Sensing Position Characteristics

 $V_{CC} = 24 \text{ V}$

No. of repetitions: 20, $T_a = 25^\circ\text{C}$







Note: The data applies to dark status. Operation may be affected by external light interference or light coming through the sensing object.

I/O Circuit Diagrams

NPN Output

Model	Output configuration	Timing charts	Output circuit
EE-SX770 EE-SX771 EE-SX772	Dark-ON		
EE-SX870 EE-SX871 EE-SX872	Light-ON		
EE-SX770A EE-SX771A EE-SX772A	Dark-ON		
EE-SX870A EE-SX871A EE-SX872A	Light-ON		

PNP Output

Model	Output configuration	Timing chart	Output circuit
EE-SX770P EE-SX771P EE-SX772P	Dark-ON		
EE-SX870P EE-SX871P EE-SX872P	Light-ON		
EE-SX770R EE-SX771R EE-SX772R	Dark-ON		
EE-SX870R EE-SX871R EE-SX872R	Light-ON		

Safety Precautions

Refer to *Warranty and Limitations of Liability*.

**WARNING**

This product is not designed or rated for ensuring safety of persons either directly or indirectly. Do not use it for such purposes.



Precautions for Correct Use

Make sure that this product is used within the rated ambient environment conditions.