

**WIL-BM-JP-M12-3.0U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Motion detector for the WIL-LED luminaire in the Jackpac® housing With 3m supply cable and M12 cable for connection to the WIL lamp. Switching time adjustable.

**General ordering data**

Type	WIL-BM-JP-M12-3.0U
Order No.	<a href="#">2537710000</a>
GTIN (EAN)	4050118549164
Qty.	1 pc(s).

**WIL-BM-JP-M12-3.0U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

Width	51	Width (inches)	2.008 inch
Height	23 mm	Height (inches)	0.906 inch
Depth	36 mm	Depth (inches)	1.417 inch
Net weight	40 g		

**Temperatures**

Operating temperature, max.	60 °C	Operating temperature, min.	-20 °C
Operating temperature	-20 - 60°C		

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**Cable technical specifications**

Cable Material	PUR	Sheathing colour	black
Cable length	3 m	Core cross-section	0.34 mm <sup>2</sup>

**Connection data**

Coding	A	Connection thread	M12
Tightening torque	0.8 Nm	Wiring	PIN 4: + (black), PIN 3: - (blue)

**Electric data**

Rated voltage (text)	24 V DC	Rated current	< 3.0 A
----------------------	---------	---------------	---------

**General technical data**

Protection degree	IP20
-------------------	------

**Classifications**

ETIM 6.0	EC002955	ETIM 7.0	EC002955
----------	----------	----------	----------

**Approvals**

Approvals



ROHS	Conform
------	---------