

Bulletin 700-K Control Relays

Bulletin 700-K — Miniature Control Relays

- IEC compact industrial relay
- IP2X Finger Protection
- Bifurcated contacts for low-level signals
- Optional integrated coil protection diode



Standards Compliance

UL 508
 CSA C22.2 No. 14
 EN/IEC 60947-1, -5-1
 Meets the material restrictions for European Directive 2002/95/EC - EU-RoHS

Certifications

cULus Listed (File No. E33916, Guide NKCR/NKCR7)
 CE Marked
 CCC

4-Pole AC or DC Coil Voltage

AC-12		AC-15 (B600)							Connection Diagrams	Contacts		Pkg. Qty. ★	Cat. No.
I_{th} [A]		I_e [A]								N.O.	N.C.		
40 °C	60 °C	24/48V	120V	240V	400V	500V	600V	690V					
10	6	3	3	2	1	1	0.6	0.6		4	0	1	700-K40E-⊗
										3	1	1	700-K31Z-⊗
										2	2	1	700-K22Z-⊗
										1+1L‡	1+1L‡	1	700-KL22Z-⊗

★ May be ordered in package quantities of 20. Add letter **M** to the end of the cat. no. Example: **700-K40E-ZJM**.

‡ 1L = Late Break N.C. / Early Make N.O.

⊗ Coil Voltage Codes

The cat. no. as listed is incomplete. Select a coil voltage code from the table below to complete the cat. no. Example: 230V, 50/60 Hz: **Cat. No. 700-K40E-⊗** becomes **Cat. No. 700-K40E-KF**. For other voltages, consult your local Rockwell Automation sales office or Allen-Bradley distributor.

