


LF-G (ALFG)

REFERENCE DATA


Standard type

1. Coil temperature rise

Sample: ALFG1PF09, 6 pcs.
Point measured: coil inside
Ambient temperature: 20°C 68°F, 60°C 140°F
Contact carrying current: 22A




2. Ambient temperature characteristics and coil applied voltage




3. Electrical life test

(22A 250V AC Resistive load)
Sample: ALFG1PF09, 6 pcs.
Operation frequency: ON:OFF = 1.5s:1.5s
Ambient temperature: 85°C 185°F


Circuit:



Change of pick-up and drop-out voltage




Change of contact resistance




4. Electrical life test

(22A 250V AC cosφ = 0.8 Inductive load)
Sample: ALFG1PF09, 6 pcs.
Operation frequency: ON:OFF = 0.1s:10s
Ambient temperature: 85°C 185°F


Circuit:



Change of pick-up and drop-out voltage



Change of contact resistance



■ High capacity type


1. Coil temperature rise

Sample: ALFG2PF09, 6 pcs.


Point measured: coil inside

Ambient temperature: 20°C 68°F, 60°C 140°F

Contact carrying current: 31A



2. Ambient temperature characteristics and coil applied voltage



3. Electrical life test


(31A 250V AC $\cos\phi = 0.8$ Inductive load)

Sample: ALFG2PF09, 6 pcs.


Operation frequency: ON:OFF = 0.1s:10s

Ambient temperature: 85°C 185°F


Circuit:



Change of pick-up and drop-out voltage



Change of contact resistance




DIMENSIONS (mm inch)

Interested in CAD data? You can obtain CAD data for all products with a **CAD Data** mark from [your local Panasonic Electric Works representative](#).

CAD Data

External dimensions



Dimension:

Max. 1mm .039 inch:

1 to 3mm .039 to .118 inch: $\pm 0.2 \pm .008$

Min. 3mm .118 inch:


General tolerance

$\pm 0.1 \pm .004$

$\pm 0.2 \pm .008$


$\pm 0.3 \pm .012$

PC board pattern (Bottom view)



Tolerance: $\pm 0.1 \pm .004$

Schematic (Bottom view)



SAFETY STANDARDS

Certification authority	Standard type	High capacity type
UL, C-UL	22A 277V AC General Use (at 85°C 185°F)	31A 277V AC General Use (at 85°C 185°F)
VDE (VDE0435)	22A 250V AC $\cos\phi = 0.8$ (at 85°C 185°F)	31A 250V AC $\cos\phi = 0.8$ (at 85°C 185°F)