NEC

PNP SILICON POWER TRANSISTOR
2SA1395

DESCRIPTION The 2SA1395 is PNP silicon epitaxial transistor designed for switching regulator, DC-DC converter and high frequency power amplifier application.

FEATURES

- Easy mount by eliminating Insulation Sheet and Bushing.
- Low Collector Saturation Voltage.
- High Switching Speed.
- Complementary to 2SC3567.

PACKAGE DIMENSIONS
in millimeters (inches)



ABSOLUTE MAXIMUM RATINGS

Maximum Temperatures

- Storage Temperature . . . . . −55 to +150 °C
- Junction Temperature . . . . . 150 °C Maximum

Maximum Power Dissipation (T_a = 25 °C)

- Total Power Dissipation . . . . . 15 W

Maximum Voltages and Currents (T_a = 25 °C)

V_{CBO}	Collector to Base Voltage	−100	V
V_{CEO}	Collector to Emitter Voltage	−100	V
V_{EBO}	Emitter to Base Voltage	−7.0	V
$I_{C(DC)}$	Collector Current (DC)	−2.0	A
$I_{C(pulse)}$	Collector Current (pulse)*	−4.0	A
$I_{B(DC)}$	Base Current (DC)	−1.0	A

* PW ≦ 300 μs, Duty Cycle ≦ 10 %

ELECTRICAL CHARACTERISTICS (T_a = 25 °C)

SYMBOL	CHARACTERISTIC	MIN.	TYP.	MAX.	UNIT.	TEST CONDITIONS
t_{on}	Turn-on Time			0.5	μs	I_C = −1.0 A, I_{B1} = −I_{B2} = −0.1 A, R_L = 50 Ω, V_{CC} ≒ 50 V
t_{stg}	Storage Time			1.5	μs	
t_f	Fall Time			0.5	μs	
h_{FE1}	DC Current Gain**	40			–	V_{CE} = −5.0 V, I_C = −0.1 A
h_{FE2}	DC Current Gain**	40		200	–	V_{CE} = −5.0 V, I_C = −1.0 A
$V_{CE(sat)}$	Collector Saturation Voltage**			−0.6	V	I_C = −1.0 A, I_B = −0.1 A
$V_{BE(sat)}$	Base Saturation Voltage**			−1.5	V	I_C = −1.0 A, I_B = −0.1 A
$V_{CEO\ (SUS)}$	Collector to Emitter Sustaining Voltage	−100			V	I_C = −1.0 A, I_B = −0.1 A, L = 1 mH
$V_{CEX\ (SUS)1}$	Collector to Emitter Sustaining Voltage	−100			V	I_C = −1.0 A, I_{B1} = −I_{B2} = −0.1 A, L = 180 μH, Clamped
$V_{CEX\ (SUS)2}$	Collector to Emitter Sustaining Voltage	−100			V	I_C = −2.0 A, I_{B1} = −0.2 A, −I_{B2} = 0.1 A, L = 180 μH, Clamped
I_{CBO}	Collector Cutoff Current			−10	μA	V_{CB} = −100 V, I_E = 0
I_{CER}	Collector Cutoff Current			−1.0	mA	V_{CE} = −100 V, R_{BE} = 51 Ω, T_a = 125 °C
I_{CEX1}	Collector Cutoff Current			−10	μA	V_{CE} = −100 V, $V_{BE(OFF)}$ = 5.0 V
I_{CEX2}	Collector Cutoff Current			−1.0	mA	V_{CE} = −100 V, $V_{BE(OFF)}$ = 5.0 V, T_a = 125 °C
I_{EBO}	Emitter Cutoff Current			−10	μA	V_{EB} = −5.0 V, I_C = 0

** PW ≦ 350 μs, Duty Cycle ≦ 2 %

Classification of h_{FE2}

Rank	M	L	K
Range	40 to 80	60 to 120	100 to 200

Test Conditions: V_{CE} = −5.0 V, I_C = −1.0 A

TYPICAL CHARACTERISTICS (T_a = 25 °C)

TOTAL POWER DISSIPATION vs. CASE TEMPERATURE



FORWARD BIAS SAFE OPERATING AREA



OPERATING CURVE OF SAFE OPERATING AREA



TRANSIENT THERMAL RESISTANCE



REVERSE BIAS SAFE OPERATING AREA



COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE



DC CURRENT GAIN vs. COLLECTOR CURRENT



BASE AND COLLECTOR SATURATION VOLTAGE vs. COLLECTOR CURRENT



TURN ON TIME, STORAGE AND FALL TIME vs. COLLECTOR CURRENT



SWITCHING TIME (t_{on}, t_{stg}, t_f) TEST CIRCUIT