



Representative Image

Ref. No. 113981 | Catalog No. CL01A400T9

Description: Screw terminal 4P, AC1 16.5kW 380-400V, 48V/50-60Hz AC Bifreq. coil (GE)

EAN 8017018139815

Home > Power devices > Contactors > 4. Series CL: Contactor for general purpose application 9-105A AC3

Description:

- Power circuit (AC): Up to 690V
 - Control circuit: Alternating current up to 690V AC
Direct current up to 440V DC
 - Terminal numbering in accordance with EN 50005 and EN 50012
 - Fixing by clipping onto 35mm DIN-rail
 - Degree of protection IP20
 - screws protected against accidental contact in accordance with VDE 0106
 - Three coil terminals
- The types CL...E are also suitable for AC control
- Accessories:
- Mounting possibilities of front/side instantaneous auxiliary contact blocks, timed auxiliary contact blocks, mechanical latch, transient suppressor block and interface modules

Descriptors

Category	4. Series CL: Contactor for general purpose application 9-105A AC3
----------	--

Specifications

Series	Four-pole contactors from 25 to 140 A (AC1)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Screw terminal
Max. operating current AC1 Non-inductive loads	25 A
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	12 A
Electrical endurance: # operations AC1	1.5 x 10 ⁶
Power contacts	4NO
Control Voltage: AC (50/60 Hz)	48 V
Admissible power AC1 220V, 230V	9.5 kW
Admissible power AC1 380V, 400V	16.5 kW
Admissible power AC1 415V, 440V	18 kW
Admissible power AC1 500V	21.5 kW
Package (pcs)	5
Utilization Category	AC1
Number of main poles	4 poles 4NO
Class	1. Contactors

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Dimensions

Weight

0.280 kg