

Specification of Li-polymer Rechargeable Battery

Model No.: LP-402025-1S-3

Reported by: 陈声宇 Date: Jan,02,2012

Checked by: _____ Date : Jan,02,2012

Approved by: _____ Date: Jan,02,2012

1. Scope

This specification describes the definition, technical requirement, testing method, warning and caution of the Lithium ion polymer rechargeable battery. The specification only applies to DUBILIER'S Li-ion battery.

2. Product Model

Battery type: Rechargeable Lithium-ion Polymer Battery

Battery Model: LP-402025-1S-3

3. Ratings

- 3.1. Nominal Capacity[at 0.2C]: 155mAh (min);
165mAh (typical)
- 3.2. Nominal Voltage: 3.7V (average voltage at 0.2C discharge)
- 3.3. Charging Voltage: 4.20 \pm 0.05V
- 3.4. Max. Charging Current: 155mA
- 3.5. Charging Method: constant current constant voltage
- Standard Charge: 78mA (constant current) charge to 4.20V, then 4.2V (constant voltage) for 3.5hr or 3mA(0.02C) cut off
- Quick Charge: 155mA(constant current) charge to 4.20V, then 4.2V (constant voltage) for 3.0hr or 3mA (0.02C) cut off
- 3.6. Max. Continuous Discharge Current: 310mA
- 3.7. Discharge Cut-off Voltage: 2.75V
- 3.8. Battery Dimensions (Refer to the attached drawing)
- | | | |
|------------|---------------|--|
| Thickness: | 3.8 \pm 0.3 | |
| | | (Measured with weighing 300gf at 25 \pm 2°C) |
| Width: | 20 \pm 1 | |
| | | (Measured with weighing 300gf at 25 \pm 2°C) |
| Length: | 26 \pm 1 | |
- 3.9. Battery Weight: 4 \pm 0.2g
- 3.10. Operating Temperature
- | | |
|------------|---------------|
| Discharge: | -20°C ~ +60°C |
| Charging: | 0°C ~ +45°C |
- Storage in a 50% charged state
- | Temperature range | Duration | Typ. Capacity recovery |
|-------------------|----------|------------------------|
|-------------------|----------|------------------------|