Three Phase Rectifier Bridge

I_{dAV} = 68 A
V_{RRM} = 800-1600 V

Preliminary data

V_{RSM} V	V_{RRM} V	Types
900	800	VUO 68-08NO7
1300	1200	VUO 68-12NO7
1500	1400	VUO 68-14NO7
1700	1600	VUO 68-16NO7



Symbol	Test Conditions		Maximum Ratings	
I_{dAV} ①	T_C = 100°C, module		68	A
I_{FSM}	T_{VJ} = 45°C;	t = 10 ms (50 Hz), sine	300	A
	V_R = 0	t = 8.3 ms (60 Hz), sine	320	A
	T_{VJ} = T_{VJM}	t = 10 ms (50 Hz), sine	260	A
	V_R = 0	t = 8.3 ms (60 Hz), sine	280	A
I^2t	T_{VJ} = 45°C	t = 10 ms (50 Hz), sine	450	A^2s
	V_R = 0	t = 8.3 ms (60 Hz), sine	425	A^2s
	T_{VJ} = T_{VJM}	t = 10 ms (50 Hz), sine	340	A^2s
	V_R = 0	t = 8.3 ms (60 Hz), sine	325	A^2s
T_{VJ}			-40...+150	°C
T_{VJM}			150	°C
T_{stg}			-40...+125	°C
V_{ISOL}	50/60 Hz, RMS	t = 1 min	2500	V~
	$I_{ISOL} \leq$ 1 mA	t = 1 s	3000	V~
M_d	Mounting torque (M4)		1.5 - 2	Nm
			14 - 18	lb.in.
Weight	typ.		18	g

Symbol	Test Conditions		Characteristic Values		
I_R	V_R = V_{RRM};	T_{VJ} = 25°C	≤	0.5	mA
	V_R = V_{RRM};	T_{VJ} = T_{VJM}	≤	3	mA
V_F	I_F = 55 A;	T_{VJ} = 25°C	≤	1.46	V
V_{T0}	For power-loss calculations only			0.8	V
r_T				13	mΩ
R_{thJC}	per diode; DC current			1.1	K/W
	per module			0.18	K/W
R_{thJH}	per diode, DC current			1.6	K/W
	per module			0.27	K/W
d_S	Creeping distance on surface			11.2	mm
d_A	Creepage distance in air			9.7	mm
a	Max. allowable acceleration			50	m/s^2

Data according to IEC 60747 refer to a single diode unless otherwise stated
① for resistive load at bridge output.

IXYS reserves the right to change limits, test conditions and dimensions.

Features

- Package with DCB ceramic base plate
- Isolation voltage 3000 V~
- Planar passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering

Applications

- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling capability
- Small and light weight

Dimensions in mm (1 mm = 0.0394")



© 2000 IXYS All rights reserved