



ODYSSEY™
THE EXTREME BATTERY

**APPLICATION
MANUAL**

STARTING, LIGHTING &
IGNITION (SLI) DRYCELL™
BATTERY GUIDE

SIXTH EDITION

ODYSSEY™ THE EXTREME BATTERY

Preface to the Sixth Edition

The addition of four new members to the ODYSSEY™ family of premium batteries - the PC310, the PC1500 (a true BCI Group 34/78), the PC2150 (a true BCI Group 31 size) and the PC2250 - has necessitated this new edition. Just as in the previous editions of the battery guide, detailed performance data for the new batteries are included in this revision.

This edition provides an expanded treatment of the charging requirements for ODYSSEY batteries, including a detailed discussion of a three-step charge profile that will bring back a fully discharged battery in about 6 to 8 hours. Also discussed are design variations among chargers with this profile.

This edition also includes updated test data on ODYSSEY batteries.

TABLE OF CONTENTS

Introduction	3
Why use ODYSSEY batteries?	3
Specifications	4
Pulse discharge capabilities	5
Extended discharge characteristics	5
Performance data tables	6
ODYSSEY storage and deep discharge recovery	9
(A) How do I know the state of charge (SOC) of the battery?	9
(B) How long can the battery be stored?	10
(C) Can the battery recover from abusive storage conditions?	10
(1) German DIN standard test for overdischarge recovery	10
(2) High temperature discharged storage test	10
Low temperature performance	10
Parasitic loads	11
Shock, impact and vibration testing	11
(A) MIL S-901C shock, high impact test	11
(B) MIL S-167-1 for mechanical vibrations	11
(C) Ford™ vehicle vibration test	11
(D) Three axis vibration test	12
(E) Caterpillar™ 100-hour vibration test	12
(F) Shock and vibration test per IEC 61373, Sections 8-10	12
Charging ODYSSEY batteries	12
(A) Selecting the right charger for your battery	13
(B) Selecting battery type on your charger	14
Rapid charging of ODYSSEY batteries	14
Concluding remarks	14
Frequently asked SLI battery questions	15