

SS-5

250 V Subminiature, radial leaded, time-delay fuses



Product description

- Radial leaded, time delay with low breaking capacity
- Designed to IEC60127-3 Sheet 4
- Plastic cap and base, flammability UL 94V0
- Protects against harmful overcurrents in primary and secondary applications
- Small rectangular-leaded design utilizes less board space
- High frequency vibration: MIL-STD-202F, Method 201A
- Halogen free, lead free, RoHS compliant

Applications

Primary and secondary circuit protection:

- Power supplies
- Notebooks and laptops
- Appliances and white goods
- Lighting ballasts
- Power adapters
- Set top boxes
- LED/LCD televisions and displays
- Air conditioners
- Battery chargers

Agency information

- UL Recognition: File E19180, Guide JDYX2/JDYX8
- VDE: 40015513
- CQC: 08012025533
- PSE:
 - JET 1641-31007-1008 (1 A – 5 A)
 - JET 1641-31007-1009 (6.3 A)
- KC:
 - SU05011-8001 (400 mA – 800 mA)
 - SU05011-8002 (1 A – 2.5 A)
 - SU05011-8003 (3.15 A – 6.3 A)
- Semko:
 - 1516697 (630 mA, 1 A – 4 A)
 - 1124941 (500 mA, 800 mA, 5 A, 6.3 A)

Ordering

- Use ordering number (see page 6 for details)

Packaging suffixes

- -AP (1 000 parts Ammo pack, Pitch = 12.7)
- -BK (200 parts in a polybag, Lead L = 4.3 ± 0.3)
- -BK2 (200 parts in a polybag, Lead L = 21 ± 3.0)

Electrical characteristics

I_n	1.5I _n minimum minute	2.1I _n maximum minute	2.75I _n minimum ms	2.75I _n maximum s	4I _n minimum ms	4I _n maximum s	10I _n minimum ms	10I _n maximum ms
200 mA – 6.3 A	60	2	400	10	150	3	20	150

Product specifications

Part number	Current rating (A)	Voltage rating (V _{AC})	Interrupting rating at rated voltage ¹ (50 Hz) (A _{AC})	Typical DC cold resistance ² (mΩ)	Typical melting I ² t (A ² s)	Typical voltage drop ⁴ (mV)	cURus	KC	VDE	CQC	SEMKO	PSE+ JET ¹
SS-5-200mA	0.2	250	35	960	0.35	212	X		X	X		
SS-5-400mA	0.4	250	35	330	1.67	147	X	X	X	X		
SS-5-500mA	0.5	250	35	258	1.79	152	X	X	X	X	X	
SS-5-630mA	0.63	250	35	140	1.51	101	X	X	X	X	X	
SS-5-800mA	0.8	250	35	118	4.21	111	X	X	X	X	X	
SS-5-1A	1.0	250	35	80.8	7.40	94.5	X	X	X	X	X	X
SS-5-1.25A	1.25	250	35	62.4	12.8	93.5	X	X	X	X	X	X
SS-5-1.6A	1.6	250	35	41	23	71.5	X	X	X	X	X	X
SS-5-2A	2.0	250	35	31.2	29.8	75	X	X	X	X	X	X
SS-5-2.5A	2.5	250	35	24.3	40.3	74.5	X	X	X	X	X	X
SS-5-3.15A	3.15	250	35	16.8	67	62.5	X	X	X	X	X	X
SS-5-4A	4.0	250	40	12.8	87	65.4	X	X	X	X	X	X
SS-5-5A	5.0	250	50	7.35	120	43	X	X	X	X	X	X
SS-5-6.3A	6.3	250	63	7.4	176	59	X	X	X	X	X	X

1. 200 mA to 3.15 A measured at 35 A, 95% - 100% of PF on AC. 4 A – 6.3 A measured at 10 times of rating current 95% - 100% of PF on AC.

2. Typical cold resistance measured at < 10% of rated current

3. I²t value is measured at 10I_n DC

4. Typical voltage drop measured at 20 °C ambient temperature and rated current

Dimensions and packaging – mm [in]

