Converter - Brake - Inverter Module (CBI 1)
NPT IGBT

Three Phase Rectifier	Brake Chopper	Three Phase Inverter
V_{RRM} = 1600 V	V_{CES} = 1200 V	V_{CES} = 1200 V
I_{DAVM25} = 130 A	I_{C25} = 19 A	I_{C25} = 30 A
I_{FSM} = 320 A	$V_{CE(sat)}$ = 2.9 V	$V_{CE(sat)}$ = 3 V

Preliminary data

Part name (Marking on product)

MUBW30-12A6K





E72873

Pin configuration see outlines.

Features:

- High level of integration - only one power semiconductor module required for the whole drive
- Inverter with NPT IGBTs
- low saturation voltage
- positive temperature coefficient
- fast switching
- short tail current
- Epitaxial free wheeling diodes with hiperfast and soft reverse recovery
- Industry standard package with insu lated copper base plate and soldering pins for PCB mounting
- Temperature sense included

Application:

AC motor drives with

- Input from single or three phase grid
- Three phase synchronous or asynchronous motor
- Electric braking operation

Package:

- UL registered
- Industry standard E1-pack

IXYS reserves the right to change limits, test conditions and dimensions.

© 2007 IXYS All rights reserved

Ouput Inverter T1 - T6

Symbol	Definitions	Conditions		Ratings min.	typ.	max.	Unit
V_{CES}	*collector emitter voltage*	T_{VJ} = 25°C to 150°C				1200	V
V_{GES}	*max. DC gate voltage*	continuous				±20	V
V_{GEM}	*max. transient collector gate voltage*	transient				±30	V
I_{C25}	*collector current*		T_C = 25°C			30	A
I_{C80}			T_C = 80°C			21	A
P_{tot}	*total power dissipation*		T_C = 25°C			130	W
$V_{CE(sat)}$	*collector emitter saturation voltage*	I_C = 30 A; V_{GE} = 15 V	T_{VJ} = 25°C		3.0	3.8	V
			T_{VJ} = 125°C		3.4		V
$V_{GE(th)}$	*gate emitter threshold voltage*	I_C = 0.6 mA; V_{GE} = V_{CE}	T_{VJ} = 25°C	4.5		6.5	V
I_{CES}	*collector emitter leakage current*	V_{CE} = V_{CES}; V_{GE} = 0 V	T_{VJ} = 25°C			1	mA
			T_{VJ} = 125°C		1.5		mA
I_{GES}	*gate emitter leakage current*	V_{CE} = 0 V; V_{GE} = ±20 V				200	nA
C_{ies}	*input capacitance*	V_{CE} = 25 V; V_{GE} = 0 V; f = 1 MHz			1000		pF
$Q_{G(on)}$	*total gate charge*	V_{CE} = 600 V; V_{GE} = 15 V; I_C = 17.5 A			70		nC
$t_{d(on)}$	*turn-on delay time*	inductive load V_{CE} = 600 V; I_C = 15 A V_{GE} = ±15 V; R_G = 82 Ω	T_{VJ} = 125°C		100		ns
t_r	*current rise time*				80		ns
$t_{d(off)}$	*turn-off delay time*				500		ns
t_f	*current fall time*				70		ns
E_{on}	*turn-on energy per pulse*				2.3		mJ
E_{off}	*turn-off energy per pulse*				1.8		mJ
I_{CM}	*reverse bias safe operating area*	RBSOA; V_{GE} = ±15 V; R_G = 82 Ω L = 100 µH; clamped induct. load V_{CEmax} = V_{CES} - L_S·di/dt	T_{VJ} = 125°C		45		A
t_{SC} (SCSOA)	*short circuit safe operating area*	V_{CE} = 1200 V; V_{GE} = ±15 V; R_G = 82 Ω; non-repetitive	T_{VJ} = 125°C		10		µs
R_{thJC}	*thermal resistance junction to case*	(per IGBT)				0.95	K/W
R_{thCH}	*thermal resistance case to heatsink*	(per IGBT)			0.35		K/W

Output Inverter D1 - D6

Symbol	Definitions	Conditions		Ratings min.	typ.	max.	Unit
V_{RRM}	*max. repetitve reverse voltage*		T_{VJ} = 150°C			1200	V
I_{F25}	*forward current*		T_C = 25°C			49	A
I_{F80}			T_C = 80°C			32	A
V_F	*forward voltage*	I_F = 30 A; V_{GE} = 0 V	T_{VJ} = 25°C			2.9	V
			T_{VJ} = 125°C		2.0		V
I_{RM}	*max. reverse recovery current*	V_R = 600 V di_F/dt = -500 A/µs I_F = 30 A; V_{GE} = 0 V	T_{VJ} = 125°C		27		A
t_{rr}	*reverse recovery time*				150		ns
$E_{rec(off)}$	*reverse recovery energy*				tbd		µJ
R_{thJC}	*thermal resistance junction to case*	(per diode)				0.9	K/W
R_{thCH}	*thermal resistance case to heatsink*	(per diode)			0.3		K/W

T_C = 25°C unless otherwise stated

© 2007 IXYS All rights reserved

Brake Chopper T7

Symbol	Definitions	Conditions		Ratings min.	typ.	max.	Unit
V_{CES}	*collector emitter voltage*	T_{VJ} = 25°C to 150°C				1200	V
V_{GES}	*max. DC gate voltage*	continuous				±20	V
V_{GEM}	*max. transient collector gate voltage*	transient				±30	V
I_{C25}	*collector current*		T_C = 25°C			19	A
I_{C80}			T_C = 80°C			13	A
P_{tot}	*total power dissipation*		T_C = 25°C			90	W
$V_{CE(sat)}$	*collector emitter saturation voltage*	I_C = 15 A; V_{GE} = 15 V	T_{VJ} = 25°C		2.9	3.4	V
			T_{VJ} = 125°C		3.5		V
$V_{GE(th)}$	*gate emitter threshold voltage*	I_C = 0.4 mA; V_{GE} = V_{CE}	T_{VJ} = 25°C	4.5		6.5	V
I_{CES}	*collector emitter leakage current*	V_{CE} = V_{CES}; V_{GE} = 0 V	T_{VJ} = 25°C			0.5	mA
			T_{VJ} = 125°C		0.8		mA
I_{GES}	*gate emitter leakage current*	V_{CE} = 0 V; V_{GE} = ±20 V				100	nA
C_{ies}	*input capacitance*	V_{CE} = 25 V; V_{GE} = 0 V; f = 1 MHz			600		pF
$Q_{G(on)}$	*total gate charge*	V_{CE} = 600 V; V_{GE} = 15 V; I_C = 10 A			45		nC
$t_{d(on)}$	*turn-on delay time*	inductive load V_{CE} = 600 V; I_C = 10 A V_{GE} = ±15 V; R_G = 82 Ω	T_{VJ} = 125°C		45		ns
t_r	*current rise time*				40		ns
$t_{d(off)}$	*turn-off delay time*				290		ns
t_f	*current fall time*				60		ns
E_{on}	*turn-on energy per pulse*				1.2		mJ
E_{off}	*turn-off energy per pulse*				1.1		mJ
I_{CM}	*reverse bias safe operating area*	RBSOA; V_{GE} = ±15 V; R_G = 82 Ω L = 100 µH; clamped induct. load V_{CEmax} = V_{CES} - L_S·di/dt	T_{VJ} = 125°C		20		A
t_{SC} (SCSOA)	*short circuit safe operating area*	V_{CE} = 720 V; V_{GE} = ±15 V; R_G = 82 Ω; non-repetitive	T_{VJ} = 125°C		10		µs
R_{thJC}	*thermal resistance junction to case*	(per IGBT)				1.37	K/W
R_{thCH}	*thermal resistance case to heatsink*	(per IGBT)			0.45		K/W

Brake Chopper D7

Symbol	Definitions	Conditions		Ratings min.	typ.	max.	Unit
V_{RRM}	*max. repetitive reverse voltage*		T_{VJ} = 150°C			1200	V
I_{F25}	*forward current*		T_C = 25°C			15	A
I_{F80}			T_C = 80°C			10	A
V_F	*forward voltage*	I_F = 15 A; V_{GE} = 0 V	T_{VJ} = 25°C			3.5	V
			T_{VJ} = 125°C		2.0		V
I_R	*reverse current*	V_R = V_{RRM}	T_{VJ} = 25°C			0.06	mA
			T_{VJ} = 125°C		0.2		mA
I_{RM}	*max. reverse recovery current*	V_R = 600 V; I_F = 10 A			13		A
t_{rr}	*reverse recovery time*	di_F/dt = -400 A/µs	T_{VJ} = 125°C		110		ns
R_{thJC}	*thermal resistance junction to case*	(per diode)				2.5	K/W
R_{thCH}	*thermal resistance case to heatsink*	(per diode)			0.05		K/W

T_C = 25°C unless otherwise stated

IXYS reserves the right to change limits, test conditions and dimensions.

© 2007 IXYS All rights reserved

Input Rectifier Bridge D8 - D13

Symbol	Definitions	Conditions		Maximum Ratings	
V_{RRM}	*max. repetitive reverse voltage*			1600	V
I_{FAV}	*average forward current*	sine 180°	T_C = 80°C	31	A
I_{DAVM}	*max. average DC output current*	rectangular; d = $^1/_3$; bridge	T_C = 80°C	89	A
I_{FSM}	*max. surge forward current*	t = 10 ms; sine 50 Hz	T_C = 25°C	320	A
P_{tot}	*total power dissipation*		T_C = 25°C	80	W

Symbol	Conditions			Characteristic Values		
				min.	typ.	max.	
V_F	*forward voltage*	I_F = 30 A	T_{VJ} = 25°C		1.0	1.35	V
			T_{VJ} = 125°C		1.1		V
I_R	*reverse current*	$V_R = V_{RRM}$	T_{VJ} = 25°C			0.02	mA
			T_{VJ} = 125°C		0.4		mA
R_{thJC}	*thermal resistance junction to case*	(per diode)	T_{VJ} = 25°C			1.4	K/W
R_{thCH}	*thermal resistance case to heatsink*	(per diode)			0.45		K/W

Temperature Sensor NTC

Symbol	Definitions	Conditions		Ratings			
				min.	typ.	max.	Unit
R_{25}	*resistance*		T_C = 25°C	4.45	4.7	5.0	kΩ
$B_{25/85}$					3510		K

Module

Symbol	Definitions	Conditions	Ratings			
			min.	typ.	max.	Unit
T_{VJ}	*operating temperature*		-40		125	°C
T_{VJM}	*max. virtual junction temperature*				150	°C
T_{stg}	*storage temperature*		-40		125	°C
V_{ISOL}	*isolation voltage*	$I_{ISOL} \leq$ 1 mA; 50/60 Hz			2500	V~
M_d	*mounting torque*	(M4)	2.0		2.2	Nm
d_S	*creep distance on surface*		12.7			mm
d_A	*strike distance through air*		12.7			mm
Weight				40		g

Equivalent Circuits for Simulation



Symbol	Definitions	Conditions		Ratings			
				min.	typ.	max.	Unit
V_0	*rectifier diode*	D8 - D13	T_{VJ} = 125°C		0.90		V
R_0					9		mΩ
V_0	*IGBT*	T1 - T6	T_{VJ} = 125°C		tbd		V
R_0					tbd		mΩ
V_0	*free wheeling diode*	D1 - D6	T_{VJ} = 125°C		1.5		V
R_0					14		mΩ
V_0	*IGBT*	T7	T_{VJ} = 125°C		1.5		V
R_0					120		mΩ
V_0	*free wheeling diode*	D7	T_{VJ} = 125°C		1.46		V
R_0					63		mΩ

T_C = 25°C unless otherwise stated

IXYS reserves the right to change limits, test conditions and dimensions.

© 2007 IXYS All rights reserved

Outline Drawing

Dimensions in mm (1 mm = 0.0394“)



Product Marking

Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Ordering Code
Standard	MUBW 30-12A6K	MUBW30-12A6K	Box	10	499 854

© 2007 IXYS All rights reserved