



Main

Range of product	Modicon Premium Automation platform
Product or component type	Analog output module
Analogue output number	8

Complementary

Analogue output type	Current 0...20 mA Current 4...20 mA Voltage +/- 10 V
Analog/Digital conversion	13 bits 0...20 mA 13 bits 4...20 mA 13 bits + sign +/- 10 V
Conversion time	5 ms
Measurement resolution	1.28 mV +/- 10 V 2.56 µA 0...20 mA 2.56 µA 4...20 mA
Electrical connection	1 SUB-D 25 connector
Measurement error	0.14 % of full scale +/- 10 V 25 °C 0.21 % of full scale 0...20 mA 25 °C 0.21 % of full scale 4...20 mA 25 °C 0.28 % of full scale +/- 10 V 0...60 °C 0.52 % of full scale 0...20 mA 0...60 °C 0.52 % of full scale 4...20 mA 0...60 °C
Isolation between channels	Common point
Isolation between channels and bus	1000 Vrms
Isolation between channels and ground	1000 Vrms
Protection type	Overload protection Short-circuit protection
Output voltage limits	<= 30 V
Load impedance ohmic	< 600 Ohm 0...20 mA < 600 Ohm 4...20 mA > 1000 Ohm +/- 10 V
Load inductance	< 300 µH
Load capacitance	< 0.1 µF
Marking	CE
Current consumption	200 mA 5 V DC 300 mA 24 V DC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Module format	Standard
Environment	
Standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA 22-2 No 142 CSA 22-2 No 213 Class I Division 2 Group A CSA 22-2 No 213 Class I Division 2 Group B CSA 22-2 No 213 Class I Division 2 Group C CSA 22-2 No 213 Class I Division 2 Group D IEC 61131-2 UL 508
Product certifications	ABS BV DNV (Det Norske Veritas) GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation for storage 10...95 % without condensation for operation
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2
RoHS EUR conformity date	0835
RoHS EUR status	Compliant