RGB ELEKTRONIKA
Centrum automatyki przemysłowej

DATASHEET

TOSHIBA

MG15Q6ES51

OTHER SYMBOLS:

RGB ELEKTRONIKA AGACIAK CIACIEK SPÓŁKA JAWNA

Jana Dlugosza 2-6 Street
51-162 Wrocław
Poland

biuro@rgbelektronika.pl
+48 71 325 15 05

www.rgbelektronika.pl

www.rgbautomatyka.pl

YOUR PARTNER IN MAINTENANCE

Repair **this product** with RGB ELEKTRONIKA

ORDER A DIAGNOSIS »



At our premises in Wrocław, we have a fully equipped servicing facility. Here we perform all the repair works and test each later sold unit. Our trained employees, equipped with a wide variety of tools and having several testing stands at their disposal, are a guarantee of the highest quality service.

Buy **this product** at RGB AUTOMATYKA

BUY »

TOSHIBA GTR MODULE SILICON N CHANNEL IGBT

MG15Q6ES51

HIGH POWER SWITCHING APPLICATIONS

MOTOR CONTROL APPLICATIONS

- The Electrodes are Isolated from Case.
- High Input Impedance.
- 6 IGBTs Built Into 1 Package.

Unit in mm



JEDEC	—
EIAJ	—
TOSHIBA	2-108E1A

Weight : 185 g

EQUIVALENT CIRCUIT



961001EAA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Emitter Voltage		V_{CES}	1200	V
Gate-Emitter Voltage		V_{GES}	±20	V
Collector Current	DC	I_C (25°C / 80°C)	25 / 15	A
	1 ms	I_{CP} (25°C / 80°C)	50 / 30	
Forward Current	DC	I_F	15	A
	1 ms	I_{FM}	30	
Collector Power Dissipation (Tc = 25°C)		P_C	145	W
Junction Temperature		T_j	150	°C
Storage Temperature Range		T_{stg}	−40~125	°C
Isolation Voltage		V_{Isol}	2500 (AC 1 minute)	V
Screw Torque		—	6	N·m

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		I_{GES}	V_{GE} = ±20 V, V_{CE} = 0		—	—	±500	nA
Collector Cut-off Current		I_{CES}	V_{CE} = 1200 V, V_{GE} = 0		—	—	0.5	mA
Gate-Emitter Cut-off Voltage		$V_{GE\ (off)}$	I_C = 15 mA, V_{CE} = 5 V		—	6.0	—	V
Collector-Emitter Saturation Voltage		$V_{CE\ (sat)}$	I_C = 15 A, V_{GE} = 15 V	T_j = 25°C	—	2.8	3.2	V
				T_j = 125°C	—	3.1	3.7	
Input Capacitance		C_{ies}	V_{CE} = 10 V, V_{GE} = 0, f = 1 MHz		—	1850	—	pF
Switching Time	Rise Time	t_r	V_{CC} = 600 V, I_C = 15 A, V_{GE} = ±15 V, R_G = 82 Ω, T_j = 125°C (Note 1)		—	0.07	0.15	μs
	Turn-on Time	t_{on}			—	0.15	0.30	
	Fall Time	t_f			—	0.07	0.10	
	Turn-off Time	t_{off}			—	0.60	0.90	
Forward Voltage		V_F	I_F = 15 A, V_{GE} = 0		—	2.0	2.8	V
Reverse Recovery Time		t_{rr}	I_F = 15 A, V_{GE} = −10 V, di / dt = 200 A / μs		—	0.10	0.25	μs
Thermal Resistance		$R_{th\ (j-c)}$	Transistor Stage		—	—	0.86	°C / W
			Diode Stage		—	—	1.5	

(Note 1) Switching Time Test Circuit & Timing Chart



$I_C - V_{CE}$



$I_C - V_{CE}$



$V_{CE} - V_{GE}$



$V_{CE} - V_{GE}$



$V_{CE} - V_{GE}$



$I_C - V_{CE}$



SWITCHING TIME – I_C



SWITCHING TIME – R_G



SWITCHING LOSS – I_C



SWITCHING LOSS – R_G



C – V_{CE}



V_{CE}, V_{GE} – Q_G



I_F – V_F



t_{rr}, I_{rr}, E_{dsw} – I_F



$R_{th\,(t)}$ – t_w



SHORT CIRCUIT SOA



REVERSE BIAS SOA