

General Information

Extended Product Type:	VEM4
Product ID:	1SBN030111R1000
EAN:	3471523130616
Catalog Description:	VEM4 Mechanical and Electrical Interlock Unit
Long Description:	VEM4 Mechanical and Electrical Interlock Unit

Additional Information

ABB Industrial IT Suite:	Control IT
CB Certificate:	CB_SE_70922A2
CCC Certificate:	CCC_2013010304651497
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1...2.5 mm ²
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A
Country of Origin:	Poland (PL)
Customs Tariff Number:	85389099
Data Sheet, Technical Information:	1SBC100173C0201
Declaration of Conformity - CE:	1SBD250007U1000
E-nummer:	3210004
EAN:	3471523130616
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology
ETIM 6:	EC002498 - Accessories for low-voltage switch technology
Environmental Information:	1SBD250142E1000
GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SBC101028M6801
Invoice Description:	VEM4 Mechanical and Electrical Interlock Unit
Maximum Electrical Switching Frequency:	1200 _B7HUR cycles per hour
Maximum Mechanical Switching Frequency:	1800 cycles per hour
Minimum Order Quantity:	1 piece
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Order Multiple:	1 piece
Package Level 1 EAN:	3471523130616
Package Level 1 Gross Weight:	0.035 kg
Package Level 1 Height:	46 mm
Package Level 1 Length:	35 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	92 mm
Package Level 2 Units:	132 piece
Package Level 3 Units:	3168 piece

Product Main Type:	Accessories for Block Contactors
Product Name:	Mechanical and Electrical Interlock Unit
Product Net Weight:	0.035 kg
Product Packing Type:	Box
RINA Certificate:	RINA_ELE084013XG
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
RoHS Date:	20090609
RoHS Information:	1SBD251010E1000
Selling Unit of Measure:	piece
Short Description:	VEM4 Mechanical and Electrical Interlock Unit
Suitable For:	AF09 AF12 AF16 AF26 AF30 AF38
Terminal Type:	Screw Terminals
Tightening Torque:	Auxiliary Circuit 1.2 N·m
Tightening Torque UL/CSA:	Auxiliary Circuit 11 in·lb
UL Certificate:	UL_20091124-E312527-6-1
UL Listing Card:	UL_E312527
UNSPSC:	39120000
Wire Stripping Length:	Auxiliary Circuit 10 mm