

SIMATIC S7,
 TD 200 TEXT DISPLAY FOR S7-200,
 2 LINES,
 WITH CABLE (2.5M) AND MOUNTING ACCESSORIES



Operator control and monitoring	
Operating / fault messages	
Number of lines	2
Number of characters per line	20 ; 20 characters/line: ASCII, cyrillic; 10 characters/line: Chinese
Character size	5 mm
Display	
Design of display	LCD backlit
Supply voltage	
Rated value (DC)	24 V ; Power supply via the S7-200 communications interface or optional external power supply unit; the CPU sensor power supply (24 V DC) is not subjected to load
Input current	
Rated value at 24 V DC	120 mA
Interfaces	
Point-to-point	
Transmission rate, max.	187.5 kbit/s ; 9,6 / 19,2 / 187,5 kbit/s
1st interface	
Physics	RS 485
Functionality	

PPI	Yes ; for setting up a network with max. 126 nodes (S7-200, OP, TP, TBP, PG/PC)
PPI	
Number of nodes, max.	126
Degree and class of protection	
IP65	Yes ; Front
Ambient conditions	
Operating temperature	
Min.	0 °C
max.	60 °C
Storage/transport temperature	
Min.	-40 °C
max.	70 °C
Dimensions	
Width	148 mm
Height	76 mm
Depth	27 mm
Mounting cutout/device depth (W x H x D)	
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Cabinet/switchboard strength	0.3 mm ; 0.3 to 4 mm
Weights	
Weight, approx.	250 g
Status	Jun 16, 2014