MITSUBISHI

GT15 OPTION FUNCTION BOARD/OPTION FUNCTION BOARD WITH ADD-ON MEMORY

User's Manual

GT15-FNB GT15-QFNB GT15-QFNB16M GT15-QFNB32M GT15-QFNB48M

Thank you for purchasing the GOT1000 Series.

Prior to use, please read both this manual and detailed manual thoroughly to fully understand the product.

MODEL	GT15-FNB-U	
MODEL CODE	1D7M07	
IB(NA)-0800301-D(0603)MEE		



●SAFETY PRECAUTIONS●

(Always read these precautions before using this equipment.)

Before using this product, please read this manual and the relevant manuals introduced in this manual carefully and pay full attention to safety to handle the product correctly.

The precautions given in this manual are concerned with this prod-

In this manual, the safety precautions are ranked as "DANGER" and "CAUTION".



Indicates that incorrect handling may cause ♦ DANGER hazardous conditions, resulting in death or

Indicates that incorrect handling may cause A CAUTION hazardous conditions, resulting in medium or slight personal injury or physical damage.

Note that the A CAUTION level may lead to a serious accident according to the circumstances.

Always follow the precautions of both levels because they are important to personal safety.

Please save this manual to make it accessible when required and always forward it to the end user

[INSTALLATION PRECAUTIONS]

DANGER

- Before mounting or dismounting this unit to or from the GOT, always shut off GOT power externally in all phases. Not doing so can cause a unit failure or malfunction
- When installing this unit, wear an earth band, etc. to avoid the static electricity which can cause a unit destruction.

⚠ CAUTION

- Use this module in the environment given in the general specifications of the GT15 User's Manual. Not doing so can cause an electric shock, fire, malfunction or product damage or deterioration.
- When installing this unit to the GOT, fit it to the option function board interface of the GOT until it clicks.

 The installation failure can cause a malfunction due to the poor

[STARTUP AND MAINTENANCE PRECAUTIONS]

⚠ CAUTION

- Do not disassemble or modify any unit. This will cause failure, malfunction, injuries, or fire
- Do not touch the conductive areas and electronic parts of this
- unit directly. Doing so can cause a unit malfunction or failure.
- Always make sure to touch the grounded metal to discharge the electricity charged in the body, etc., before touching the unit.

 Failure to do so may cause a failure or malfunctions of the unit.

[DISPOSAL PRECAUTIONS]

⚠ CAUTION

Dispose of this product as industrial waste.

[TRANSPORTATION PRECAUTIONS]

⚠ CAUTION

Make sure to transport the GOT main unit and/or relevant unit(s) in the manner they will not be exposed to the impact exceeding the impact resistance described in the general specifications of the GT15 User's Manual, as they are precision devices. Failure to do so may cause the unit to fail. Check if the unit operates correctly after transportation.

Manuals

The following shows manuals relevant to this product.

Detailed Manual

Manual name		Manual Number (Type code)
GT15 User's Manual	(Option)	SH-080528ENG (1D7M23)

Relevant Manuals

For relevant manuals, refer to the PDF manual stored within the

© 2004 MITSUBISHI ELECTRIC CORPORATION

Compliance with the EMC and Low Voltage **Directives**

When incorporating the Mitsubishi GOT into other machinery or equipment and keeping compliance with the EMC and low voltage directives, refer to Chapter 4, "EMC Directives and Low Voltage Directives" of the manual (GT15 General Description) included with

The CE logo is printed on the rating plate of the GOT, indicating compliance with the EMC and low voltage directives. By making this product conform to the EMC directive and low voltage instruction, it is not necessary to make those steps

1. Overview

This User's Manual describes the GT15 option function board/ option function board with add-on memory (here in after abbreviated as option function board).

There are the following option function board types.
Installation of the option function board increases functions. Refer to the GT15 User's Manual for the applicable GOT, and to the GT Designer2 Version \square Screen Design Manual for the increased functions.

Model name	Description
GT15-FNB	Option function board Applicable for MELSEC-A/FX ladder monitor function
GT15-QFNB	Option function board Applicable for MELSEC-Q/QnA/A/FX ladder monitor function, multi-channel function
GT15-QFNB16M	Option function board with add-on memory (Option function+16MB) Applicable for MELSEC-Q/QnA/A/FX ladder monitor function, multi-channel function
GT15-QFNB32M	Option function board with add-on memory (Option function+32MB) Applicable for MELSEC-Q/QnA/A/FX ladder monitor function, multi-channel function
GT15-QFNB48M	Option function board with add-on memory (Option function+48MB) Applicable for MELSEC-Q/QnA/A/FX ladder monitor function, multi-channel function


2. Specifications

The performance specifications of the option function board are indicated below.

For the general specifications of the option function board, refer to the GT15 User's Manual to be used.

Item	Memory capacity	GOT memory capacity after installation
GT15-FNB	-	9MB
GT15-QFNB	-	9MB
GT15-QFNB16M	16MB	25MB
GT15-QFNB32M	32MB	41MB
GT15-QFNB48M	48MB	57MB

3. Part Names and External Dimensions



No.	Name	Description
1)	Connector	For connecting the option function board interface of the GOT
2)	Positioning crena	For positioning in the option function board installation
3)	Rating plate	

Warranty

Mitsubishi will not be held liable for damage caused by factors found not to be the cause of Mitsubishi; machine damage or lost profits caused by faults in the Mitsubishi products; damage, secondary damage, accident compensation caused by special factors unpredictable by Mitsubishi; damages to products other than Mitsubishi products; and to other duties.

⚠ For safe use

- This product has been manufactured as a general-purpose part for general industries, and has not been designed or manufactured to be incorporated in a device or system used in purposes related to
- Before using the product for special purposes such as nuclear power, electric power, aerospace, medicine or passenger movement vehicles, consult with Mitsubishi.

 This product has been manufactured under strict quality control.
- However, when installing the product where major accidents or losses could occur if the product fails, install appropriate backup or failsafe functions in the system.

Country/Region Sales office/Tel

U.K

Korea

Brazil

Nales office/Tel
Misubishi Electric Automation Inc.
Misubishi Electric Automation Inc.
500 Corporate Woods Parkway Vernon Hills, IL 60061
Tel: +1-847-478-2100
MELCO-TEC Rep. Come Assessoria Tecnica Ltda.
Rua Correia Dias, 184, Edificio Paraiso Trade Center-8 andar
Paraiso, Sao Paulo, SP Brazil
Tel: +455-11-5908-8331
Misubishi Electric Europe B.V. German Branch
Gothaer Strasse B 0-40880 Ratingen, GERMANY
Tel: +492-102-486-0
Misubishi Electric Europe B.V. UK Branch
Travellers Lane, Hatfield, Herts, Al-10 8XB, UK
Tel: +44-1707-276100
Misubishi Electric Europe B.V. Italian Branch
Centro Dir. Colleoni, Pal. Perseo-Ingr.2
Via Paracelso 12, 2004 14 grate B, Milano, Italy
Tel: +39-039-605344
Misubishi Electric Europe B.V. Spanish Branch
Carretera de Rubi To-80
08190 - Sant Loyal del Valles, Barcelona, Spain
Tel: +34-93-565-3131
Misubishi Telectric Europe B.V. French Branch
Misubishi Electric Europe B.V. French Branch

Mitsubishi Electric Europe B.V. French Branch 25 Boulevard des Bouvets, F-92741 Nanterre Cedex, France TEL: +33-1-5568-5568 France

ובנ: + י-ס-ו-ססטטטט Circuit Breaker Industries LTD. Tripswitch Drive, Elandsfontein Gauteng, South Africa Tel: +27-11-928-2000 South Africa

Hong Kong

Tel: +27-11-928-2000
Ryoden Automation Ltd.
10th Floor, Manulife Tower, 169 Electric
Road, North Point, HongKong
Tel: +852-2887-8870
Ryoden Automation Shanghai Ltd.
3F Block5 Building Automation
Instrumentation Plaza 103 Cao Bao Rd. Shanghai 200233 China
Tel: +86-21-6120-0808
Setsuyo Enterprise Co., Ltd.
6F., No. 105 Wu-Kung 3rd.RD, Wu-Ku Hsiang,
Talipei Hsine, Taiwan
Tel: +886-2-299-2499
HAN NEUNG TECHNO CO.,LTD.
1F Dong Seo Game Channel Bldg.,660-11, Deungchon-dong
Kangsec-ku, Seoul, Korea
Tel: +82-2-3660-9552
Mitsubishi Electric Asia Pte, Ltd.
307 Alexandra Road #05-01/02,
Mitsubishi Electric Asia Pte, Ltd.
307 Alexandra Road #05-01/02,
Mitsubishi Electric Asia Pte, Ltd.
308-28,29,30 S.V.City Building, Office Tower 2, Floor 17-18 Rama 3
Road, Bangkpongpang, Yannawa, Bangkok 10120
Tel: +66-2-682-6522
PT. Autoteknindo SUMBER MAKMUR
JI. Muara Karang Selatan Block a Utara No. 1 Kav. No.11 Kawasan Industri/Perquadnagna Jakarta - Utara 14440

Singapore

Road, Bangkongnain, Yannawa, Bangkok 10120 Tell: +66-2-682-6522 P.T. Autoteknindo SUMBER MAKMUR J. Muara Karang Selatan Block a Utara No.1 Kav. No.11 Kawasan Industri/Pergudangan Jakarta - Utara 14440 Tell: +62-21-663-0833 Messung Systems Put.Ltd. Electronic Sadan NO:111 Unit No15, M.I.D.C BHOSARI, PUNE-411026, India Tell: +91-20-712-2807 Mitsubishi Electric Australia Tell: +91-20-712-2807 Al8 Victoria Road, PostalBag, No 2, Rydalmers, N.S. W.2116, Australia Tell: +91-2-9684-7777 Indonesia


Australia

★MITSUBISHI ELECTRIC CORPORATION

When exported from Japan, this manual does not require application to the Ministry of Economy, Trade and Industry for service transaction permission. Specifications subject to change without notice Printed in Japan on recycled paper.


4. Installation Procedure

- (1) Power off the GOT.
- (2) Remove the expansion unit cover on the left side of the GOT.



(3) Insert the option function board to the option function board interface to which the positioning crenas are fitted.

(When the expansion unit is installed on the GOT, remove the installed unit before installing the option function board.)



(4) Push down the option function board until it clicks.

