SGX Europe Sp. Z o.o.
Building 11
Ligocka St. 103,
40-568 Katowice,
Poland

T: +48 (0) 32 438 4778

E: sales.is@sgxsensortech.com
www.sgxsensortech.com

PERFORMANCE

For test purposes, all data taken using the following conditions:
- Performance as tested in the SGX IR-EK2 Evaluation Kit directly after calibration.
- SGX linearisation and temperature compensation algorithms applied; see Infrared Sensor Application Notes.
- IR Source Voltage 5V, square wave, at 4 Hz and 50% duty cycle. Running the IR Source at 3V will decrease performance due to lower output signals.
- Ambient temperature (20°C) and pressure (101 kPa).
- All gases diluted in dry nitrogen.
- Performance for the Hydrocarbons refers to Methane only. Most other hydrocarbons will have an improved performance.
- Performance data is the same for the supported IR Source variants ("_1" variants).
- Refer to Application Notes for more information.

Sensor type	**IR15TT**		**IR15TT-M**		**IR15TT-R**		**IR15TT-D**	
Gas	**CO_2**	**Methane [5] / Hydrocarbons**	**CO_2**	**Methane [5] / Hydrocarbons**	**CO_2**	**Methane [5] / Hydrocarbons**	**Methane [5] / Hydrocarbons**	**Methane [5] / Hydrocarbons**
Concentration Range	Refer to Configurations Table							
Warm-up Times	<20 sec to operate <60 sec for Zero ±1% of Full Scale, <30 min to full specification at 20 °C							
Maximum Response Time (T_{90}) [1]	20 sec							
Peak-to-Peak Outputs (in N_2) [2] **Active (mV):**	10 to 29	24 to 58	10 to 29	12 to 47	18 to 45	8 to 21	12 to 47	24 to 58
Reference (mV):	18 to 43		18 to 43		10 to 24		18 to 43	
Sensitivity to Standard Test Gas [2] [3] **Minimum Absorbance:** **Maximum Absorbance:**	0.25 0.50	0.07 0.15	0.25 0.50	0.07 0.15	0.07 0.12	0.06 0.10	0.07 0.15	0.07 0.15
Typical Sensitivity for Gas Range [3]	Refer to Fractional Absorbance Curves							
Minimum Detection Level [4]	2ppm CO_2	30ppm CH_4	2ppm CO_2	30ppm CH_4	50ppm CO_2	60ppm CH_4	30ppm CH_4	30ppm CH_4
Maximum deviation from linearity (±) [6]								
0 to 0.5%v/v Range:	0.01%v/v	-------	0.01%v/v	-------	-------	-------	-------	-------
0 to 2%v/v Range:	0.05%v/v	-------	0.05%v/v	-------	-------	-------	-------	-------
0 to 2.5%v/v Range:	-------	-------	-------	-------	-------	-------	-------	-------
0 to 5%v/v Range:	0.10%v/v	0.15%v/v	0.10%v/v	0.15%v/v	-------	0.15%v/v	0.15%v/v	0.15%v/v
0 to 10%v/v Range:	-------	-------	-------	-------	0.20%v/v	-------	-------	-------
0 to 100%v/v Range:	-------	5%v/v	-------	5%v/v	2%v/v	5%v/v	5%v/v	5%v/v
Temperature Variation (± ppm / °C) [7] **Zero and Concentration Range Maximum (-20°C to +55°C)**								
Zero:	10	20	10	25	10	50	25	20
0.5%v/v:	25	-------	25	-------	-------	-------	-------	-------
2%v/v:	100	-------	100	-------	-------	-------	-------	-------
2.5%v/v:	-------	-------	-------	-------	-------	-------	150	-------
5%v/v:	250	150	250	200	-------	250	-------	150
10%v/v:	-------	-------	-------	-------	500	-------	-------	-------
100%v/v:	-------	1500	-------	2000	2500	2500	2000	1500
Short Term Stability (±) [8]:								
Zero:	5 ppm	0.01%v/v	5 ppm	0.01%v/v	20 ppm	0.01%v/v	0.01%v/v	0.01%v/v
0.5%v/v:	0.01%v/v	-------	0.01%v/v	-------	-------	-------	-------	-------
2%v/v:	0.05%v/v	-------	0.05%v/v	-------	-------	-------	-------	-------
2.5%v/v:	-------	-------	-------	-------	-------	-------	-------	-------
5%v/v:	0.10%v/v	0.10%v/v	0.10%v/v	0.08%v/v	-------	0.10%v/v	0.10%v/v	0.10%v/v
10%v/v:	-------	-------	-------	-------	0.1%v/v	-------	-------	-------
100%v/v:	-------	2%v/v	-------	2%v/v	1%v/v	3%v/v	2%v/v	2%v/v

© SGX Sensortech 2016

SGX Europe Sp. Z o.o.
Building 11
Ligocka St. 103,
40-568 Katowice,
Poland

T: +48 (0) 32 438 4778

E: sales.is@sgxsensortech.com
www.sgxsensortech.com

Sensor type	IR15TT		IR15TT-M		IR15TT-R		IR15TT-D	
Gas	**CO_2**	**Methane [5] / Hydrocarbons**	**CO_2**	**Methane [5] / Hydrocarbons**	**CO_2**	**Methane [5] / Hydrocarbons**	**Methane [5] / Hydrocarbons**	**Methane [5] / Hydrocarbons**
Humidity Response (+) [9] **Zero:** **0.5%v/v:** **2%v/v:** **2.5%v/v:** **5%v/v:** **10%v/v:** **100%v/v:**	Negligible	0.15%v/v ------- ------- ------- 0.30%v/v ------- 2%v/v	Negligible	0.10%v/v ------- ------- ------- 0.25%v/v ------- 2%v/v	Negligible	0.10%v/v ------- ------- ------- 0.25%v/v ------- 2%v/v	0.10%v/v ------- ------- ------- 0.25%v/v ------- 2%v/v	0.15%v/v ------- ------- ------- 0.30%v/v ------- 2%v/v
Pressure Effects [10]	Sensors shall meet specification within a ±5% change in ambient pressure from the ambient pressure during calibration							
MTBF (IR Source only)	>10 years for 5 V operation, >20 years for 3 V operation							
Vibration	Conforms to EN 60079-29-1							
Ingress Protection	Requires extra protection depending on application							

(1) Based upon an immediate step change in concentration at the aperature of the sensor.
(2) Production Test Limits, using standard test gases of Dry Nitrogen, 2%v/v Carbon Dioxide and 5%v/v Methane, where appropriate.
(3) A 0.30 absorbance is equivalent to a 30% decrease in the Active peak-to-peak output.
(4) The minimum detection level is the smallest detectable change in concentration based upon a 2 sigma variantion. The best detectable change occurs at 0% gas concentration due to the non-linear output of the detector (see Fractional Absorbance Curves).
(5) Performance for most hydrocarbons will be better than for methane for equiavlent concentrations, as methane is one of the lower sensitive gases compared to other hydocarbons.
(6) After linearisation using the recommended method of linearisation and based upon a calibration gas with a concentration >75% of the full-scale.
(7) Using average Alpha and Beta coefficients based upon test data from the instrument in which the sensor is being tested. Refer to Application Notes for information on calculating Alpha and Beta coefficients. Accuracy can be improved by measuring each sensor over temperature to define specific Alpha or Alpha & Beta coefficients.
(8) After sensor stabilisation and over a period of 8 hours.
(9) Difference in response when changed from 0 %RH to 90 %RH.
(10) Sensors can be used over a greater ambient pressure using pressure compensation of the concentration. An external pressure sensor will be requred for this.

FRACTIONAL ABSORBANCE CURVES

These show the typical sensitivity versus concentration before linearisation for the range of gases. For further explanation, refer to the Infrared Sensor Application Notes.

Primary Target Gases

IR15TT
IR15TT-M

0 - 5%
Carbon Dioxide



IR15TT
IR15TT-M

0 – 0.5%
Carbon Dioxide