


Delivery address: Mackenrodtstraße 14,
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
e-mail: mail@jumo.net
Internet: www.jumo.net

JUMO House
Temple Bank, Riverway
Harlow, Essex CM 20 2TT, UK
Phone: +44 1279 635533
Fax: +44 1279 635262
e-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk


885 Fox Chase, Suite 103
Coatesville PA 19320, USA
Phone: 610-380-8002
1-800-554-JUMO
Fax: 610-380-8009
e-mail: info@JumoUSA.com
Internet: www.JumoUSA.com




Dimensions




Type 901221/10



Type 901221/20



Type 901221/3x



Type 901221/40

Delivery address: Mackenrodtstraße 14,
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
e-mail: mail@jumo.net
Internet: www.jumo.net

JUMO House
Temple Bank, Riverway
Harlow, Essex CM 20 2TT, UK
Phone: +44 1279 635533
Fax: +44 1279 635262
e-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk

885 Fox Chase, Suite 103
Coatesville PA 19320, USA
Phone: 610-380-8002
1-800-554-JUMO
Fax: 610-380-8009
e-mail: info@JumoUSA.com
Internet: www.JumoUSA.com



Order details: Mineral-insulated thermocouples to DIN 43 710 and EN 60 584

(1) Basic version

901221/10 Mineral-insulated thermocouple with bare connecting wires



901221/20 Mineral-insulated thermocouple with standard flat emf-free connector



(2) Measuring insert / operating temperature in °C

x	x	1040	1 x Fe-Con J, operating temperature -200 to +800°C, sheath, Mat. Ref. 1.4541
x	x	1042	1 x Fe-Con L, operating temperature -200 to +800°C, sheath, Mat. Ref. 1.4541
x	x	1043	1 x NiCr-Ni K, operating temperature -200 to +1200°C, sheath, Mat. Ref. 2.4816
x	x	2042	2 x Fe-Con L, operating temperature -200 to +800°C, sheath, Mat. Ref. 1.4541
x	x	2043	2 x NiCr-Ni K, operating temperature -200 to +1200°C, sheath, Mat. Ref. 2.4816

(3) Protection tube diameter D in mm

x	x	0.5	0.5mm, only with Type 1 x NiCr-Ni K
x	x	1	1mm
x	x	1.5	1.5mm
x	x	2	2mm
x	x	3	3mm
x	x	4.5	4.5mm
x	x	6	6mm

(4) Fitting length EL in mm (50 ≤ EL ≤ 50000)

x	x	100	100mm
x	x	200	200mm
x	x	300	300mm
x	x	400	400mm
x	x	500	500mm
x	x	...	please specify in plain text (50mm steps)

(5) Extra codes

x	x	000	no extra code
x	x	309	uninsulated assembly (thermocouple welded to tip)

Order code (1) (2) (3) (4) (5) ,...

Order example 901221/10 - 1042 - 3 - 200 / 000¹

1. List extra codes in sequence, separated by commas.